



SPEC® CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Huawei

SPECint®2006 = **NC**

Huawei RH2288H V3 (Intel Xeon E5-2660 v4)

SPECint_base2006 = **NC**

CPU2006 license: 3175

Test date: Mar-2016

Test sponsor: Huawei

Hardware Availability: Mar-2016

Tested by: Huawei

Software Availability: Mar-2016

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not
a href="http://spec.org/cpu2006/Docs/runrules.html#rule_1.3.2">SPEC CPU run
up policy on gener

- 400.perlbench |
- 401.bzip2 |
- 403.gcc |
- 429.mcf |
- 445.gobmk |
- 456.hmmer |
- 458.sjeng |
- 462.libquantum |
- 464.h264ref |
- 471.omnetpp |
- 473.astar |
- 483.xalancbmk |

Hardware

CPU Name: Intel Xeon E5-2660 v4
 CPU Characteristics: Intel Turbo Boost Technology up to 3.20 GHz
 CPU MHz: 2000
 FPU: Integrated
 CPU(s) enabled: 28 cores, 2 chips, 14 cores/chip
 CPU(s) orderable: 1,2 chip
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 256 KB I+D on chip per core
 L3 Cache: 35 MB I+D on chip per chip
 Other Cache: None
 Memory: 256 GB (16 x 16 GB 2Rx4 PC4-2400T-R)
 Disk Subsystem: 1 x 1 T SATA, 7200 RPM
 Other Hardware: None

Software

Operating System: Red Hat Enterprise Linux Server release 7.0 (Maipo)
 3.10.0-123.el7.x86_64
 Compiler: C/C++: Version 16.0.0.101 of Intel C++ Studio XE for Linux
 Auto Parallel: Yes
 File System: ext4
 System State: Run level 3 (multi-user)
 Base Pointers: 32/64-bit
 Peak Pointers: 32/64-bit
 Other Software: Microquill SmartHeap V10.2



SPEC CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Huawei

SPECint2006 = NC

Huawei RH2288H V3 (Intel Xeon E5-2660 v4)

SPECint_base2006 = NC

CPU2006 license: 3175
Test sponsor: Huawei
Tested by: Huawei

Test date: Mar-2016
Hardware Availability: Mar-2016
Software Availability: Mar-2016

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not http://spec.org/cpu2006/Docs/runrules.html#rule_1.3.2 SPEC CPU run up policy on <https://www.spec.org/osg/policy.html#AppendixC> gener

Results Table

Benchmark	Base						Peak						
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	
400.perlbench	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
401.bzip2	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
403.gcc	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
429.mcf	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
445.gobmk	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
456.hammer	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
458.sjeng	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
462.libquantum	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
464.h264ref	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
471.omnetpp	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
473.astar	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
483.xalancbmk	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC

Results appear in the column in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

The config file option 'submit' was used.

Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"

Platform Notes

BIOS configuration:
Set Power Efficiency Mode to Custom
Set Sleep Mode to ES mode
Set Patrol Scrub to Disable
Set Hyper-Threading to Disable
Sysinfo program /speccpu/spec16/config/sysinfo.rev6914
\$Rev: 6914 \$ \$Date:: 2014-06-25 #\$ e3fbb8667b5a285932ceab81e28219e1
running on localhost.localdomain Tue Mar 15 10:10:54 2016

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Huawei

SPECint2006 = **NC**

Huawei RH2288H V3 (Intel Xeon E5-2660 v4)

SPECint_base2006 = **NC**

CPU2006 license: 3175

Test date: Mar-2016

Test sponsor: Huawei

Hardware Availability: Mar-2016

Tested by: Huawei

Software Availability: Mar-2016

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not
a href="http://spec.org/cpu2006/Docs/runrules.html#rule_1.3.2">SPEC CPU run
up policy on gener

Platform Notes (Continued)

<http://www.spec.org/cpu2006/Docs/config.html#ysinfo>

From /proc/cpuinfo

```

model name      : Intel(R) Xeon(R) CPU E5-2660 v4 @ 2.00GHz
 2 "physical id"s (chips)
 28 "processors"
cores, siblings (Caution: counting these is hw and system dependent. The
following excerpts from /proc/cpuinfo might not be reliable. Use with
caution.)
  cpu cores     : 14
  siblings      : 14
  physical 0    : cores 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14
  physical 1    : cores 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14
cache size     : 35840 KB

```

From /proc/meminfo

```

MemTotal:      263569784
HugePages_Total: 0
Hugepagesize:  2048 kB

```

From /etc/*release* /etc/*version*

```

os-release:
NAME="Red Hat Enterprise Linux Server"
VERSION="7.0 (Maipo)"
ID="rhel"
ID_LIKE="fedora"
VERSION_ID="7.0"
PRETTY_NAME="Red Hat Enterprise Linux Server 7.0 (Maipo)"
ANSI_COLOR="0;31"
CPE_NAME="cpe:/o:redhat:enterprise_linux:7.0:GA:server"
redhat-release: Red Hat Enterprise Linux Server release 7.0 (Maipo)
system-release: Red Hat Enterprise Linux Server release 7.0 (Maipo)
system-release-cpe: cpe:/o:redhat:enterprise_linux:7.0:ga:server

```

uname -a:

```

Linux localhost.localdomain 3.10.0-123.el7.x86_64 #1 SMP Mon May 5 11:16:57
EDT 2014 x86_64 x86_64 x86_64 GNU/Linux

```

run-level 3 Mar 15 10:09

SPEC is set to: /speccpu/spec16

```

Filesystem      Type      Size      Used Avail Use% Mounted on
/dev/sda2       ext4     865G     110G   712G  14% /

```

Additional information from dmidecode:

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Huawei

SPECint2006 = **NC**

Huawei RH2288H V3 (Intel Xeon E5-2660 v4)

SPECint_base2006 = **NC**

CPU2006 license: 3175

Test date: Mar-2016

Test sponsor: Huawei

Hardware Availability: Mar-2016

Tested by: Huawei

Software Availability: Mar-2016

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not
a href="http://spec.org/cpu2006/Docs/runrules.html#rule_1.3.2">SPEC CPU run
up policy on gener

Platform Notes (Continued)

Warning: Use caution when you interpret this section. The 'dmidecode' program reads system data which is "intended to allow hardware to be accurately determined", but the intent may not be met, as there are frequent changes to hardware, firmware, and the "DMTF SMBIOS" standard.

BIOS Insyde Corp. 3.09 02/22/2016

Memory:

8x NO DIMM NO DIMM 3 rank
8x Samsung M393A2G40EB1-CRC 16 GB 1 rank 2400 MHz
8x Samsung M393A2G40EB1-CRC 16 GB 1 rank 2400 MHz

(End of data from sysinfo program)

General Notes

Environment variables set by runspec before the start of the run:

KMP_AFFINITY = "granularity=fine,compact,1,0"

LD_LIBRARY_PATH = "/speccpu/spec16/libs/32:/speccpu/spec16/libs/64:/speccpu/spec16/sh"

OMP_NUM_THREADS = "28"

Binaries compiled on a system with 1x Intel Core i5-4670K CPU + 32GB memory using Redhat EL 7.1

Transparent Huge Pages enabled with:

echo always >/sys/kernel/mm/transparent_hugepage/enabled

runspec command invoked through numactl i.e.:

numactl --interleave=all runspec <etc>

Base Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks:

icpc -m64



SPEC CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Huawei

SPECint2006 =

Huawei RH2288H V3 (Intel Xeon E5-2660 v4)

SPECint_base2006

CPU2006 license: 3175

Test date: Mar-2016

Test sponsor: Huawei

Hardware Availability: Mar-2016

Tested by: Huawei

Software Availability: Mar-2016

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not http://spec.org/cpu2006/Docs/runrules.html#rule_1.3.2 SPEC CPU run up policy on <https://www.spec.org/osg/policy.html#AppendixC> gener

Peak Compiler Invocation (Continued)

473.astar: icpc -m64

Peak Portability Flags

400.perlbench: -D_FILE_OFFSET_BITS=64 -DSPEC_CPU_LINUX_IA32
401.bzip2: -DSPEC_CPU_LP64
403.gcc: -DSPEC_CPU_LP64
429.mcf: -DSPEC_CPU_LP64
445.gobmk: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64
458.sjeng: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX
464.h264ref: -DSPEC_CPU_LP64
471.omnetpp: -D_FILE_OFFSET_BITS=64
473.astar: -DSPEC_CPU_LP64
483.xalancbmk: -D_FILE_OFFSET_BITS=64 -DSPEC_CPU_LINUX

Peak Optimization Flags

C benchmarks:

400.perlbench: -xCORE-AVX2(pass 2) -prof-gen:threadsafe(pass 1)
-ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2)
-par-num-threads=1(pass 1) -prof-use(pass 2) -opt-prefetch
-ansi-alias
401.bzip2: -xCORE-AVX2(pass 2) -prof-gen:threadsafe(pass 1)
-ipo(pass 2) -O3(pass 2) -no-prec-div
-par-num-threads=1(pass 1) -prof-use(pass 2) -auto-ilp32
-opt-prefetch -ansi-alias
403.gcc: -xCORE-AVX2 -ipo -O3 -no-prec-div -inline-calloc
-opt-malloc-options=3 -auto-ilp32
429.mcf: -xCORE-AVX2 -ipo -O3 -no-prec-div -parallel
-opt-prefetch -auto-p32
445.gobmk: basepeak = yes

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Huawei

SPECint2006 = **NC**

Huawei RH2288H V3 (Intel Xeon E5-2660 v4)

SPECint_base2006 = **NC**

CPU2006 license: 3175

Test date: Mar-2016

Test sponsor: Huawei

Hardware Availability: Mar-2016

Tested by: Huawei

Software Availability: Mar-2016

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not
a href="http://spec.org/cpu2006/Docs/runrules.html#rule_1.3.2">SPEC CPU run
up policy on gener

Peak Optimization Flags (Continued)

456.hmmr: basepeak = yes

458.sjeng: -xCORE-AVX2(pass 2) -prof-gen:threadsafe(pass 2)
-ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2)
-par-num-threads=1(pass 1) -prof-use(pass 2) -unroll4

462.libquantum: basepeak = yes

464.h264ref: basepeak = yes

C++ benchmarks:

471.omnetpp: -xCORE-AVX2(pass 2) -prof-gen:threadsafe(pass 1)
-ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2)
-par-num-threads=1(pass 1) -prof-use(pass 2)
-opt-ra-region-category:block -ansi-alias
-Wl,-z,muldefs -L/sh -lsmartheap

473.astar: -xCORE-AVX2 -ipo -O3 -no-prec-div -opt-prefetch
-auto-p22 -Wl,-z,muldefs -L/sh -lsmartheap64

483.xalancbmk: -xCORE-AVX2 -ipo -O3 -no-prec-div -opt-prefetch
-ansi-alias -Wl,-z,muldefs -L/sh -lsmartheap

Peak Other Flags

C benchmark

402.mcf: -Dalloca=_alloca

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic16.0-official-linux64.html>

<http://www.spec.org/cpu2006/flags/Huawei-Platform-Settings-BDW-V1.0.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic16.0-official-linux64.xml>

<http://www.spec.org/cpu2006/flags/Huawei-Platform-Settings-BDW-V1.0.xml>



SPEC CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Huawei

SPECint2006 = **NC**

Huawei RH2288H V3 (Intel Xeon E5-2660 v4)

SPECint_base2006 = **NC**

CPU2006 license: 3175

Test date: Mar-2016

Test sponsor: Huawei

Hardware Availability: Mar-2016

Tested by: Huawei

Software Availability: Mar-2016

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not http://spec.org/cpu2006/Docs/runrules.html#rule_1.3.2 SPEC CPU run up policy on <https://www.spec.org/osg/policy.html#AppendixC> gener

Non-Compliant

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.
Report generated on Fri Oct 21 16:16:43 2016 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 7 April 2016.