



SPEC® CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

(Test Sponsor: Intel Corporation)

ASUS A88X-PRO Motherboard (AMD A4-7300 with Radeon HD Graphics)

SPECint®2006 = 28.3

SPECint_base2006 = 27.4

CPU2006 license: 13


Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Mar-2016

Hardware Availability: Jul-2014

Software Availability: Aug-2015



Hardware

CPU Name: AMD A4-7300
 CPU Characteristics: AMD Turbo CORE technology up to 4.00 GHz
 CPU MHz: 3800
 FPU: Integrated
 CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
 CPU(s) orderable: 1 chip
 Primary Cache: 64 KB I on chip per chip; 16 KB D on chip per core
 Secondary Cache: 1 MB I+D on chip per chip
 L3 Cache: None
 Other Cache: None
 Memory: 8 GB (2 x 4 GB 2Rx8 PC3-10600U-11)
 Disk Subsystem: Seagate Barracuda 250 GB SATA, 7200 RPM
 Other Hardware: None

Software

Operating System: Microsoft Windows 7 Enterprise 6.1.7601 Service Pack 1 Build 7601
 Compiler: C/C++: Version 16.0.0.110 of Intel C++ Studio XE for Windows;
 Libraries: Version 18.00.30723 of Microsoft Visual Studio 2013
 Auto Parallel: Yes
 File System: NTFS
 System State: Default
 Base Pointers: 32/64-bit
 Peak Pointers: 32/64-bit
 Other Software: SmartHeap Library Version 11.0 from <http://www.microquill.com/>



SPEC CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

(Test Sponsor: Intel Corporation)

ASUS A88X-PRO Motherboard (AMD A4-7300 with Radeon HD Graphics)

SPECint2006 = 28.3

SPECint_base2006 = 27.4

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Mar-2016

Hardware Availability: Jul-2014

Software Availability: Aug-2015

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	453	21.6	<u>457</u>	<u>21.4</u>	459	21.3	<u>362</u>	<u>27.0</u>	<u>362</u>	<u>27.0</u>	362	27.0
401.bzip2	637	15.2	<u>643</u>	<u>15.0</u>	643	15.0	<u>634</u>	<u>15.2</u>	<u>635</u>	<u>15.2</u>	635	15.2
403.gcc	551	14.6	559	14.4	<u>559</u>	<u>14.4</u>	<u>544</u>	<u>14.8</u>	<u>547</u>	<u>14.7</u>	547	14.7
429.mcf	290	31.4	<u>293</u>	<u>31.1</u>	293	31.1	<u>290</u>	<u>31.4</u>	<u>293</u>	<u>31.1</u>	293	31.1
445.gobmk	476	22.0	<u>471</u>	<u>22.3</u>	470	22.3	<u>445</u>	<u>23.6</u>	<u>446</u>	<u>23.5</u>	447	23.5
456.hammer	<u>208</u>	<u>44.8</u>	209	44.6	207	45.1	<u>208</u>	<u>44.8</u>	209	44.6	207	45.1
458.sjeng	589	20.5	<u>587</u>	<u>20.6</u>	585	20.7	<u>589</u>	<u>20.5</u>	<u>587</u>	<u>20.6</u>	585	20.7
462.libquantum	<u>95.6</u>	<u>217</u>	95.7	217	95.6	217	<u>95.6</u>	<u>217</u>	95.7	217	95.6	217
464.h264ref	<u>638</u>	<u>34.7</u>	641	34.5	636	34.8	<u>638</u>	<u>34.7</u>	641	34.5	636	34.8
471.omnetpp	<u>367</u>	<u>17.0</u>	367	17.0	366	17.1	<u>342</u>	<u>18.3</u>	342	18.3	342	18.3
473.astar	367	19.1	<u>367</u>	<u>19.1</u>	368	19.1	<u>367</u>	<u>19.1</u>	<u>367</u>	<u>19.1</u>	368	19.1
483.xalancbmk	281	24.5	<u>281</u>	<u>24.6</u>	280	24.6	<u>281</u>	<u>24.5</u>	<u>281</u>	<u>24.6</u>	280	24.6

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Compiler Invocation Notes

To compile these binaries, the Intel Compiler 16.0 was set up to generate 64-bit binaries with the command:

```
"psxevars.bat intel64" (shortcut provided in the Intel(r) Parallel Studio XE 2016 program folder)
```

Platform Notes

```
Sysinfo program C:\SPEC16.0/Docs/sysinfo
$Rev: 6775 $ $Date:: 2011-08-16 #$ \8787f7622badcf24e01c368b1db4377c
running on CltE03F49ACBFDE Tue Mar 22 11:48:18 2016
```

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see: <http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

```
Trying 'systeminfo'
OS Name : Microsoft Windows 7 Enterprise
OS Version : 6.1.7601 Service Pack 1 Build 7601
System Manufacturer: System manufacturer
System Model : System Product Name
Processor(s) : 1 Processor(s) Installed.
[01]: AMD64 Family 21 Model 19 Stepping 1 AuthenticAMD ~3800 Mhz
BIOS Version : American Megatrends Inc. 2502, 12/11/2015
Total Physical Memory: 7,364 MB
```

```
Trying 'wmic cpu get /value'
DeviceID : CPU0
```

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

(Test Sponsor: Intel Corporation)

ASUS A88X-PRO Motherboard (AMD A4-7300 with Radeon HD Graphics)

SPECint2006 = 28.3

SPECint_base2006 = 27.4

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Mar-2016

Hardware Availability: Jul-2014

Software Availability: Aug-2015

Platform Notes (Continued)

L2CacheSize : 24847
L3CacheSize : 0
MaxClockSpeed : 3800
Name : AMD A4-7300 APU with Radeon HD Graphics
NumberOfCores : 1
NumberOfLogicalProcessors: 2

(End of data from sysinfo program)

Component Notes

Tested systems can be used with Shin-G ATX case,
PC Power and Cooling 1200W power supply

General Notes

OMP_NUM_THREADS set to number of processors cores
KMP_AFFINITY set to granularity=fine,scatter
Binaries compiled on a system with 1x Intel Xeon E5-2699 v3 CPU
+ 64GB memory using Windows 8.1 Enterprise 64-bit

Base Compiler Invocation

C benchmarks:

icl -Qvc12 -Qstd=c99

C++ benchmarks:

icl -Qvc12

Base Portability Flags

400.perlbench: -DSPEC_CPU_P64 -DSPEC_CPU_WIN64_X64
401.bzip2: -DSPEC_CPU_P64
403.gcc: -DSPEC_CPU_P64 -DSPEC_CPU_WIN64
429.mcf: -DSPEC_CPU_P64
445.gobmk: -DSPEC_CPU_P64
456.hmmmer: -DSPEC_CPU_P64
458.sjeng: -DSPEC_CPU_P64
462.libquantum: -DSPEC_CPU_P64
464.h264ref: -DSPEC_CPU_P64 -DWIN32
471.omnetpp: -DSPEC_CPU_P64 -DSPEC_CPU_WIN64
473.astar: -DSPEC_CPU_P64
483.xalancbmk: -DSPEC_CPU_P64 -Qoption,cpp,--no_wchar_t_keyword -DWIN64



SPEC CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

(Test Sponsor: Intel Corporation)

ASUS A88X-PRO Motherboard (AMD A4-7300 with Radeon HD Graphics)

SPECint2006 = 28.3

SPECint_base2006 = 27.4

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Mar-2016

Hardware Availability: Jul-2014

Software Availability: Aug-2015

Base Optimization Flags

C benchmarks:

```
/arch:AVX -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qparallel
-Qauto-ilp32 /F64000000
```

C++ benchmarks:

```
/arch:AVX -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qcxx-features
-Qauto-ilp32 /F64000000 shlw64M.lib -link /FORCE:MULTIPLE
```

Base Other Flags

C benchmarks:

```
403.gcc: -Dalloca=_alloca
```

Peak Compiler Invocation

C benchmarks:

```
icl -Qvc12 -Qstd=c99
```

C++ benchmarks:

```
icl -Qvc12
```

Peak Portability Flags

Same as Base Portability Flags

Peak Optimization Flags

C benchmarks:

```
400.perlbench: /arch:AVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-prefetch
-Qauto-ilp32 /F64000000 shlw64M.lib
/F256000000 -link /FORCE:MULTIPLE
```

```
401.bzip2: /arch:AVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qopt-prefetch -Qansi-alias
-Qauto-ilp32 /F64000000
```

```
403.gcc: /arch:AVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qauto-ilp32 /F64000000
```

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

(Test Sponsor: Intel Corporation)

ASUS A88X-PRO Motherboard (AMD A4-7300 with Radeon HD Graphics)

SPECint2006 = 28.3

SPECint_base2006 = 27.4

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Mar-2016

Hardware Availability: Jul-2014

Software Availability: Aug-2015

Peak Optimization Flags (Continued)

429.mcf: basepeak = yes

445.gobmk: /arch:AVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O2 -Qprec-div- -Qansi-alias -Qauto-ilp32
/F64000000

456.hmmer: basepeak = yes

458.sjeng: basepeak = yes

462.libquantum: basepeak = yes

464.h264ref: basepeak = yes

C++ benchmarks:

471.omnetpp: /arch:AVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qansi-alias
-Qopt-ra-region-strategy=block -Qauto-ilp32 /F64000000
shlW64M.lib -link /FORCE:MULTIPLE

473.astar: basepeak = yes

483.xalancbmk: basepeak = yes

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic16.0-official-windows.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic16.0-official-windows.xml>



SPEC CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

(Test Sponsor: Intel Corporation)

ASUS A88X-PRO Motherboard (AMD A4-7300 with Radeon HD Graphics)

SPECint2006 = 28.3

SPECint_base2006 = 27.4

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Mar-2016

Hardware Availability: Jul-2014

Software Availability: Aug-2015

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.
Report generated on Tue Sep 20 15:06:24 2016 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 20 September 2016.