



SPEC® CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Inspur Corporation

SPECint_rate2006 = 7240

Inspur TS860G3 (Intel Xeon E7-8890 v4)

SPECint_rate_base2006 = 6980

CPU2006 license: 13


Test sponsor: Inspur Corporation

Tested by: Inspur Corporation

Test date: Oct-2016

Hardware Availability: Jun-2016

Software Availability: Mar-2016



Hardware

CPU Name:	Intel Xeon E7-8890 v4
CPU Characteristics:	Intel Turbo Boost Technology up to 3.40 GHz
CPU MHz:	2200
FPU:	Integrated
CPU(s) enabled:	192 cores, 8 chips, 24 cores/chip, 2 threads/core
CPU(s) orderable:	4,6,8 chip
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	256 KB I+D on chip per core
L3 Cache:	60 MB I+D on chip per chip
Other Cache:	None
Memory:	1 TB (64 x 16 GB 2Rx4 PC4-2133P-R, running at 1600 MHz)
Disk Subsystem:	4 x 600GB SAS, Raid 0
Other Hardware:	None

Software

Operating System:	Inspur K-UX release 3.0.5 (Inspur) 3.10.4-K_UX.x86_64
Compiler:	C/C++: Version 16.0.2.181 of Intel C++ Studio XE for Linux
Auto Parallel:	No
File System:	xfs
System State:	Run level 3 (multi-user)
Base Pointers:	32-bit
Peak Pointers:	32/64-bit
Other Software:	Microquill SmartHeap V10.2



SPEC CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Inspur Corporation

SPECint_rate2006 = 7240

Inspur TS860G3 (Intel Xeon E7-8890 v4)

SPECint_rate_base2006 = 6980

CPU2006 license: 13

Test date: Oct-2016

Test sponsor: Inspur Corporation

Hardware Availability: Jun-2016

Tested by: Inspur Corporation

Software Availability: Mar-2016

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	384	651	5760	653	5740	649	5780	384	535	7010	535	7010	536	7000
401.bzip2	384	1082	3430	1074	3450	1074	3450	384	1043	3550	1047	3540	1044	3550
403.gcc	384	653	4730	649	4760	650	4750	384	647	4780	647	4780	649	4770
429.mcf	384	426	8230	424	8260	423	8280	384	426	8230	424	8260	423	8280
445.gobmk	384	770	5230	769	5240	769	5240	384	758	5310	760	5300	758	5320
456.hammer	384	347	10300	347	10300	349	10300	384	313	11500	313	11400	315	11400
458.sjeng	384	857	5420	857	5420	857	5420	384	823	5640	823	5650	823	5650
462.libquantum	384	104	76500	104	76400	104	76500	384	104	76500	104	76400	104	76500
464.h264ref	384	879	9670	881	9650	880	9660	384	862	9860	861	9870	860	9880
471.omnetpp	384	827	2900	828	2900	828	2900	384	793	3030	794	3020	794	3020
473.astar	384	704	3830	703	3830	701	3840	384	704	3830	703	3830	701	3840
483.xalancbmk	384	375	7060	374	7090	372	7120	384	375	7060	374	7090	372	7120

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

The numactl mechanism was used to bind copies to processors. The config file option 'submit' was used to generate numactl commands to bind each copy to a specific processor. For details, please see the config file.

Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"

Platform Notes

BIOS and OS configuration:

SCALING_GOVERNOR set to Performance

Hardware Prefetch set to Disable

VT Support set to Disable

C1E Support set to Disable

Sysinfo program /home/spec16/config/sysinfo.rev6914

\$Rev: 6914 \$ \$Date::: 2014-06-25 #\\$ e3fbb8667b5a285932ceab81e28219e1

running on localhost.localdomain Thu Oct 13 22:29:03 2016

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:

<http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

From /proc/cpuinfo

model name : Intel(R) Xeon(R) CPU E7-8890 v4 @ 2.20GHz

8 "physical id"s (chips)

384 "processors"

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Inspur Corporation

SPECint_rate2006 = 7240

Inspur TS860G3 (Intel Xeon E7-8890 v4)

SPECint_rate_base2006 = 6980

CPU2006 license: 13

Test date: Oct-2016

Test sponsor: Inspur Corporation

Hardware Availability: Jun-2016

Tested by: Inspur Corporation

Software Availability: Mar-2016

Platform Notes (Continued)

cores, siblings (Caution: counting these is hw and system dependent. The following excerpts from /proc/cpuinfo might not be reliable. Use with caution.)

```
cpu cores : 24
siblings   : 48
physical 0: cores 0 1 2 3 4 5 8 9 10 11 12 13 16 17 18 19 20 21 24 25 26
27 28 29
physical 1: cores 0 1 2 3 4 5 8 9 10 11 12 13 16 17 18 19 20 21 24 25 26
27 28 29
physical 2: cores 0 1 2 3 4 5 8 9 10 11 12 13 16 17 18 19 20 21 24 25 26
27 28 29
physical 3: cores 0 1 2 3 4 5 8 9 10 11 12 13 16 17 18 19 20 21 24 25 26
27 28 29
physical 4: cores 0 1 2 3 4 5 8 9 10 11 12 13 16 17 18 19 20 21 24 25 26
27 28 29
physical 5: cores 0 1 2 3 4 5 8 9 10 11 12 13 16 17 18 19 20 21 24 25 26
27 28 29
physical 6: cores 0 1 2 3 4 5 8 9 10 11 12 13 16 17 18 19 20 21 24 25 26
27 28 29
physical 7: cores 0 1 2 3 4 5 8 9 10 11 12 13 16 17 18 19 20 21 24 25 26
27 28 29
cache size : 61440 KB
```

From /proc/meminfo

```
MemTotal:      1056714488 kB
HugePages_Total:       0
Hugepagesize:     2048 kB
```

From /etc/*release* /etc/*version*

```
inspur-release: Inspur K-UX release 3.0.5 (Inspur)
os-release:
```

```
  NAME="Inspur K-UX"
  VERSION="3 (Inspur)"
  ID="k-ux"
  VERSION_ID="3"
  PRETTY_NAME="Inspur K-UX 3 (Inspur)"
  ANSI_COLOR="0;31"
  CPE_NAME="cpe:/o:k-ux:k-ux:3"
  HOME_URL="http://www.inspur.com/"
system-release: Inspur K-UX release 3.0.5 (Inspur)
system-release-cpe: cpe:/o:k-ux:k-ux:3
```

uname -a:

```
Linux localhost.localdomain 3.10.4-K_UX.x86_64 #1 SMP Fri Sep 30 11:06:29 GMT
2016 x86_64 x86_64 x86_64 GNU/Linux
```

SPEC is set to: /home/spec16

```
Filesystem      Type  Size  Used Avail Use% Mounted on
/dev/mapper/ik-home xfs   2.2T  1.6T  563G  75% /home
```

Additional information from dmidecode:

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Inspur Corporation

SPECint_rate2006 = 7240

Inspur TS860G3 (Intel Xeon E7-8890 v4)

SPECint_rate_base2006 = 6980

CPU2006 license: 13

Test date: Oct-2016

Test sponsor: Inspur Corporation

Hardware Availability: Jun-2016

Tested by: Inspur Corporation

Software Availability: Mar-2016

Platform Notes (Continued)

Warning: Use caution when you interpret this section. The 'dmidecode' program reads system data which is "intended to allow hardware to be accurately determined", but the intent may not be met, as there are frequent changes to hardware, firmware, and the "DMTF SMBIOS" standard.

BIOS Inspur TS860G3_4.0.05 09/06/2016

Memory:

64x Hynix HMA42GR7AFR4N-TF 16 GB 2 rank , configured at 1600 MHz
128x NO DIMM Unknown

(End of data from sysinfo program)

General Notes

Environment variables set by runspec before the start of the run:

LD_LIBRARY_PATH = "/home/spec16/libs/32:/home/spec16/libs/64:/home/spec16/sh"

Binaries compiled on a system with 1x Intel Core i7-4790K CPU + 32GB memory using RedHat EL 7.2 glibc 2.17

Transparent Huge Pages enabled with:

echo always > /sys/kernel/mm/transparent_hugepage/enabled

Filesystem page cache cleared with:

echo 1> /proc/sys/vm/drop_caches

runspec command invoked through numactl i.e.:

numactl --interleave=all runspec <etc>

Base Compiler Invocation

C benchmarks:

icc -m32 -L/opt/intel/compilers_and_libraries_2016/linux/compiler/lib/ia32_lin

C++ benchmarks:

icpc -m32 -L/opt/intel/compilers_and_libraries_2016/linux/compiler/lib/ia32_lin

Base Portability Flags

```
400.perlbench: -D_FILE_OFFSET_BITS=64 -DSPEC_CPU_LINUX_IA32
401.bzip2: -D_FILE_OFFSET_BITS=64
403.gcc: -D_FILE_OFFSET_BITS=64
429.mcf: -D_FILE_OFFSET_BITS=64
445.gobmk: -D_FILE_OFFSET_BITS=64
456.hammer: -D_FILE_OFFSET_BITS=64
458.sjeng: -D_FILE_OFFSET_BITS=64
462.libquantum: -D_FILE_OFFSET_BITS=64 -DSPEC_CPU_LINUX
464.h264ref: -D_FILE_OFFSET_BITS=64
471.omnetpp: -D_FILE_OFFSET_BITS=64
```

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Inspur Corporation

SPECint_rate2006 = 7240

Inspur TS860G3 (Intel Xeon E7-8890 v4)

SPECint_rate_base2006 = 6980

CPU2006 license: 13

Test date: Oct-2016

Test sponsor: Inspur Corporation

Hardware Availability: Jun-2016

Tested by: Inspur Corporation

Software Availability: Mar-2016

Base Portability Flags (Continued)

473.astar: -D_FILE_OFFSET_BITS=64
483.xalancbmk: -D_FILE_OFFSET_BITS=64 -DSPEC_CPU_LINUX

Base Optimization Flags

C benchmarks:

-xCORE-AVX2 -ipo -O3 -no-prec-div -opt-prefetch
-opt-mem-layout-trans=3

C++ benchmarks:

-xCORE-AVX2 -ipo -O3 -no-prec-div -opt-prefetch
-opt-mem-layout-trans=3 -Wl,-z,muldefs -L/sh -lsmartheap

Base Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

Peak Compiler Invocation

C benchmarks (except as noted below):

icc -m32 -L/opt/intel/compilers_and_libraries_2016/linux/compiler/lib/ia32_lin

400.perlbench: icc -m64

401.bzip2: icc -m64

456.hmmer: icc -m64

458.sjeng: icc -m64

C++ benchmarks:

icpc -m32 -L/opt/intel/compilers_and_libraries_2016/linux/compiler/lib/ia32_lin

Peak Portability Flags

400.perlbench: -D_FILE_OFFSET_BITS=64 -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX_X64
401.bzip2: -D_FILE_OFFSET_BITS=64 -DSPEC_CPU_LP64
403.gcc: -D_FILE_OFFSET_BITS=64
429.mcf: -D_FILE_OFFSET_BITS=64

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Inspur Corporation

SPECint_rate2006 = 7240

Inspur TS860G3 (Intel Xeon E7-8890 v4)

SPECint_rate_base2006 = 6980

CPU2006 license: 13

Test date: Oct-2016

Test sponsor: Inspur Corporation

Hardware Availability: Jun-2016

Tested by: Inspur Corporation

Software Availability: Mar-2016

Peak Portability Flags (Continued)

```
445.gobmk: -D_FILE_OFFSET_BITS=64  
456.hmmer: -D_FILE_OFFSET_BITS=64 -DSPEC_CPU_LP64  
458.sjeng: -D_FILE_OFFSET_BITS=64 -DSPEC_CPU_LP64  
462.libquantum: -D_FILE_OFFSET_BITS=64 -DSPEC_CPU_LINUX  
464.h264ref: -D_FILE_OFFSET_BITS=64  
471.omnetpp: -D_FILE_OFFSET_BITS=64  
473.astar: -D_FILE_OFFSET_BITS=64  
483.xalancbmk: -D_FILE_OFFSET_BITS=64 -DSPEC_CPU_LINUX
```

Peak Optimization Flags

C benchmarks:

```
400.perlbench: -xCORE-AVX2(pass 2) -prof-gen:threadsafe(pass 1)  
               -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2)  
               -par-num-threads=1(pass 1) -prof-use(pass 2) -auto-ilp32  
  
401.bzip2: -xCORE-AVX2(pass 2) -prof-gen:threadsafe(pass 1)  
            -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2)  
            -par-num-threads=1(pass 1) -prof-use(pass 2) -opt-prefetch  
            -auto-ilp32 -ansi-alias  
  
403.gcc: -xCORE-AVX2 -ipo -O3 -no-prec-div  
  
429.mcf: basepeak = yes  
  
445.gobmk: -xCORE-AVX2(pass 2) -prof-gen:threadsafe(pass 1)  
            -prof-use(pass 2) -par-num-threads=1(pass 1) -ansi-alias  
            -opt-mem-layout-trans=3  
  
456.hmmer: -xCORE-AVX2 -ipo -O3 -no-prec-div -unroll12 -auto-ilp32  
  
458.sjeng: -xCORE-AVX2(pass 2) -prof-gen:threadsafe(pass 1)  
            -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2)  
            -par-num-threads=1(pass 1) -prof-use(pass 2) -unroll14  
            -auto-ilp32  
  
462.libquantum: basepeak = yes  
  
464.h264ref: -xCORE-AVX2(pass 2) -prof-gen:threadsafe(pass 1)  
              -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2)  
              -par-num-threads=1(pass 1) -prof-use(pass 2) -unroll12  
              -ansi-alias
```

C++ benchmarks:

```
471.omnetpp: -xCORE-AVX2(pass 2) -prof-gen:threadsafe(pass 1)  
              -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2)  
              -par-num-threads=1(pass 1) -prof-use(pass 2) -ansi-alias
```

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Inspur Corporation

SPECint_rate2006 = 7240

Inspur TS860G3 (Intel Xeon E7-8890 v4)

SPECint_rate_base2006 = 6980

CPU2006 license: 13

Test date: Oct-2016

Test sponsor: Inspur Corporation

Hardware Availability: Jun-2016

Tested by: Inspur Corporation

Software Availability: Mar-2016

Peak Optimization Flags (Continued)

471.omnetpp (continued):

```
-opt-ra-region-strategy=block -Wl,-z,muldefs  
-L/sh -lsmartheap
```

473.astar: basepeak = yes

483.xalancbmk: basepeak = yes

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic16.0-official-linux64.html>

<http://www.spec.org/cpu2006/flags/Inspur-Platform-Settings-V1.0-HSW.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic16.0-official-linux64.xml>

<http://www.spec.org/cpu2006/flags/Inspur-Platform-Settings-V1.0-HSW.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.

Report generated on Wed Nov 2 10:38:16 2016 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 1 November 2016.