



SPEC® CFP2006 Result

Copyright 2006-2017 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

Synergy 620 Gen9

(2.40 GHz, Intel Xeon E7-8894 v4)

SPECfp_rate2006 = 1210

SPECfp_rate_base2006 = 1180

CPU2006 license: 3


Test sponsor: HPE

Tested by: HPE

Test date: Feb-2017

Hardware Availability: Mar-2017

Software Availability: Nov-2016



Hardware

CPU Name: Intel Xeon E7-8894 v4
CPU Characteristics: Intel Turbo Boost Technology up to 3.40 GHz
CPU MHz: 2400
FPU: Integrated
CPU(s) enabled: 48 cores, 2 chips, 24 cores/chip, 2 threads/core
CPU(s) orderable: 1,2 chip
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 256 KB I+D on chip per core

Software

Operating System: SUSE Linux Enterprise Server 12 (x86_64) SP2, Kernel 4.4.21-69-default
Compiler: C/C++: Version 17.0.0.098 of Intel C/C++ Compiler for Linux;
Fortran: Version 17.0.0.098 of Intel Fortran Compiler for Linux
Auto Parallel: No
File System: xfs
System State: Run level 3 (multi-user)

Continued on next page

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2017 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise
(Test Sponsor: HPE)

Synergy 620 Gen9
(2.40 GHz, Intel Xeon E7-8894 v4)

SPECfp_rate2006 = 1210

SPECfp_rate_base2006 = 1180

CPU2006 license: 3

Test sponsor: HPE

Tested by: HPE

Test date: Feb-2017

Hardware Availability: Mar-2017

Software Availability: Nov-2016

L3 Cache: 60 MB I+D on chip per chip
Other Cache: None
Memory: 512 GB (32 x 16 GB 2Rx4 PC4-2400T-R,
running at 1600 MHz)
Disk Subsystem: 1 x 400 GB SAS SSD, RAID 0
Other Hardware: None

Base Pointers: 32/64-bit
Peak Pointers: 32/64-bit
Other Software: None

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	96	1754	744	<u>1753</u>	<u>744</u>	1752	745	96	1754	744	<u>1753</u>	<u>744</u>	1752	745
416.gamess	96	1045	1800	1044	1800	1046	1800	96	1003	1870	1009	1860	1006	1870
433.milc	96	1227	718	<u>1228</u>	<u>717</u>	1228	717	96	1227	718	<u>1228</u>	<u>717</u>	1228	717
434.zeusmp	96	704	1240	705	1240	703	1240	96	704	1240	705	1240	703	1240
435.gromacs	96	324	2120	325	2110	323	2120	96	313	2190	314	2190	313	2190
436.cactusADM	96	824	1390	825	1390	<u>825</u>	<u>1390</u>	96	824	1390	825	1390	825	1390
437.leslie3d	96	1697	532	<u>1696</u>	<u>532</u>	1692	533	96	1697	532	<u>1696</u>	<u>532</u>	1692	533
444.namd	96	507	1520	508	1510	<u>508</u>	<u>1520</u>	96	<u>501</u>	<u>1540</u>	500	1540	502	1530
447.dealII	96	421	2610	424	2590	<u>421</u>	<u>2610</u>	96	421	2610	424	2590	421	2610
450.soplex	96	1409	568	<u>1408</u>	<u>569</u>	1407	569	48	622	643	616	650	618	648
453.povray	96	222	2300	217	2350	<u>219</u>	<u>2330</u>	96	188	2720	<u>187</u>	<u>2740</u>	186	2740
454.calculix	96	308	2580	307	2580	<u>307</u>	<u>2580</u>	96	308	2580	307	2580	307	2580
459.GemsFDTD	96	2028	502	2026	503	2035	500	96	<u>2028</u>	<u>502</u>	2026	503	2035	500
465.tonto	96	646	1460	<u>659</u>	<u>1430</u>	663	1420	96	<u>619</u>	<u>1530</u>	628	1510	618	1530
470.lbm	96	1267	1040	1266	1040	1268	1040	96	<u>1267</u>	<u>1040</u>	1266	1040	1268	1040
481.wrf	96	1177	911	1179	909	<u>1178</u>	<u>910</u>	96	1176	912	1173	914	1176	912
482.sphinx3	96	1884	993	1903	983	<u>1898</u>	<u>986</u>	96	1884	993	1903	983	1898	986

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

The numactl mechanism was used to bind copies to processors. The config file option 'submit' was used to generate numactl commands to bind each copy to a specific processor. For details, please see the config file.

Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"
Transparent Huge Pages enabled by default
Filesystem page cache cleared with:
echo 1 > /proc/sys/vm/drop_caches
runspec command invoked through numactl i.e.:
numactl --interleave=all runspec <etc>



SPEC CFP2006 Result

Copyright 2006-2017 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

Synergy 620 Gen9

(2.40 GHz, Intel Xeon E7-8894 v4)

SPECfp_rate2006 = 1210

SPECfp_rate_base2006 = 1180

CPU2006 license: 3

Test sponsor: HPE

Tested by: HPE

Test date: Feb-2017

Hardware Availability: Mar-2017

Software Availability: Nov-2016

Platform Notes

BIOS Configuration:

HP Power Profile set to Custom
HP Power Regulator to HP Static High Performance Mode
Minimum Processor Idle Power Core C-State set to C6 State
Minimum Processor Idle Power Package C-State set to No Package State
QPI Snoop Configuration set to Cluster on Die
Collaborative Power Control set to Disabled
Thermal Configuration set to Maximum Cooling
Processor Power and Utilization Monitoring set to Disabled
Memory Refresh Rate set to 1x Refresh

Sysinfo program /home/cpu2006_copy/config/sysinfo.rev6993
Revision 6993 of 2015-11-06 (b5e8d4b4eb51ed28d7f98696cbe290c1)
running on synergy620_manju Wed Feb 15 08:16:43 2017

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:
<http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

From /proc/cpuinfo
model name : Intel(R) Xeon(R) CPU E7-8894 v4 @ 2.40GHz
 2 "physical id"s (chips)
 96 "processors"
cores, siblings (Caution: counting these is hw and system dependent. The following excerpts from /proc/cpuinfo might not be reliable. Use with caution.)
 cpu cores : 24
 siblings : 48
 physical 0: cores 0 1 2 3 4 5 8 9 10 11 12 13 16 17 18 19 20 21 24 25 26
 27 28 29
 physical 1: cores 0 1 2 3 4 5 8 9 10 11 12 13 16 17 18 19 20 21 24 25 26
 27 28 29
cache size : 61440 KB

From /proc/meminfo
MemTotal: 528262092 kB
HugePages_Total: 0
Hugepagesize: 2048 kB

From /etc/*release* /etc/*version*
SuSE-release:
 SUSE Linux Enterprise Server 12 (x86_64)
VERSION = 12
PATCHLEVEL = 2
This file is deprecated and will be removed in a future service pack or release.
Please check /etc/os-release for details about this release.
os-release:
NAME="SLES"
VERSION="12-SP2"
VERSION_ID="12.2"
PRETTY_NAME="SUSE Linux Enterprise Server 12 SP2"

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2017 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

Synergy 620 Gen9

(2.40 GHz, Intel Xeon E7-8894 v4)

SPECfp_rate2006 = 1210

SPECfp_rate_base2006 = 1180

CPU2006 license: 3

Test sponsor: HPE

Tested by: HPE

Test date: Feb-2017

Hardware Availability: Mar-2017

Software Availability: Nov-2016

Platform Notes (Continued)

ID="sles"

ANSI_COLOR="0;32"

CPE_NAME="cpe:/o:suse:sles:12:sp2"

uname -a:

```
Linux synergy620_manju 4.4.21-69-default #1 SMP Tue Oct 25 10:58:20 UTC 2016
(9464f67) x86_64 x86_64 x86_64 GNU/Linux
```

run-level 3 Feb 15 07:01

SPEC is set to: /home/cpu2006_copy

Filesystem	Type	Size	Used	Avail	Use%	Mounted on
/dev/sda4	xfs	331G	41G	290G	13%	/home

Additional information from dmidecode:

Warning: Use caution when you interpret this section. The 'dmidecode' program reads system data which is "intended to allow hardware to be accurately determined", but the intent may not be met, as there are frequent changes to hardware, firmware, and the "DMTF SMBIOS" standard.

BIOS HP I40 12/08/2016

Memory:

16x UNKNOWN NOT AVAILABLE

32x UNKNOWN NOT AVAILABLE 16 GB 2 rank 2400 MHz, configured at 1600 MHz

(End of data from sysinfo program)

Regarding the sysinfo display about the memory installed, the correct amount of memory is 512 GB and the dmidecode description should have one line reading as:
32x UNKNOWN NOT AVAILABLE 16 GB 2 rank 2400 MHz, configured at 1600 MHz

General Notes

Environment variables set by runspec before the start of the run:

LD_LIBRARY_PATH = "/home/cpu2006_copy/libs/32:/home/cpu2006_copy/libs/64:/home/cpu2006_copy/sh10.2"

Binaries compiled on a system with 1x Intel Core i7-4790K CPU + 32GB RAM
memory using Redhat Enterprise Linux 7.2

Base Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks:

icpc -m64

Fortran benchmarks:

ifort -m64

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2017 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

Synergy 620 Gen9

(2.40 GHz, Intel Xeon E7-8894 v4)

SPECfp_rate2006 = 1210

SPECfp_rate_base2006 = 1180

CPU2006 license: 3

Test sponsor: HPE

Tested by: HPE

Test date: Feb-2017

Hardware Availability: Mar-2017

Software Availability: Nov-2016

Base Compiler Invocation (Continued)

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

Base Portability Flags

```

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
  433.milc: -DSPEC_CPU_LP64
  434.zeusmp: -DSPEC_CPU_LP64
  435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
  437.leslie3d: -DSPEC_CPU_LP64
    444.namd: -DSPEC_CPU_LP64
    447.dealII: -DSPEC_CPU_LP64
    450.soplex: -DSPEC_CPU_LP64
    453.povray: -DSPEC_CPU_LP64
  454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
  465.tonto: -DSPEC_CPU_LP64
    470.lbm: -DSPEC_CPU_LP64
      481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
  482.sphinx3: -DSPEC_CPU_LP64

```

Base Optimization Flags

C benchmarks:

```

-xCORE-AVX2 -ipo -O3 -no-prec-div -no-prec-sqrt -static
-qopt-prefetch -fp-model fast=2
-qopt-prefetch-issue-excl-hint -auto-ilp32 -ansi-alias
-qopt-mem-layout-trans=3 -unroll-aggressive
-use-intel-optimized-headers -qopt-matmul -qopt-subscript-in-range
-qopt-assume-safe-padding -qopt-calloc -inline-calloc
-qopt-malloc-options=3

```

C++ benchmarks:

```

-xCORE-AVX2 -ipo -O3 -no-prec-div -no-prec-sqrt -static
-qopt-prefetch -fp-model fast=2
-qopt-prefetch-issue-excl-hint -auto-ilp32 -ansi-alias
-qopt-mem-layout-trans=3 -use-intel-optimized-headers
-unroll-aggressive -qopt-calloc -inline-calloc -qopt-malloc-options=3

```

Fortran benchmarks:

```

-xCORE-AVX2 -ipo -O3 -no-prec-div -no-prec-sqrt -static
-qopt-prefetch -fp-model fast=2
-qopt-prefetch-issue-excl-hint

```

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2017 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise
(Test Sponsor: HPE)

Synergy 620 Gen9
(2.40 GHz, Intel Xeon E7-8894 v4)

SPECfp_rate2006 = 1210

SPECfp_rate_base2006 = 1180

CPU2006 license: 3

Test sponsor: HPE

Tested by: HPE

Test date: Feb-2017

Hardware Availability: Mar-2017

Software Availability: Nov-2016

Base Optimization Flags (Continued)

Benchmarks using both Fortran and C:

```
-xCORE-AVX2 -ipo -O3 -no-prec-div -no-prec-sqrt -static
-qopt-prefetch -fp-model fast=2
-qopt-prefetch-issue-excl-hint -auto-ilp32 -ansi-alias
-qopt-mem-layout-trans=3 -unroll-aggressive
-use-intel-optimized-headers -qopt-matmul -qopt-subscript-in-range
-qopt-assume-safe-padding -qopt-calloc -inline-calloc
-qopt-malloc-options=3
```

Peak Compiler Invocation

C benchmarks:

```
icc -m64
```

C++ benchmarks (except as noted below):

```
icpc -m64
```

```
450.soplex: icpc -m32 -L/opt/intel/compilers_and_libraries_2017/linux/lib/ia32
```

Fortran benchmarks:

```
ifort -m64
```

Benchmarks using both Fortran and C:

```
icc -m64 ifort -m64
```

Peak Portability Flags

```
410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
    433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
    444.namd: -DSPEC_CPU_LP64
    447.dealII: -DSPEC_CPU_LP64
450.soplex: -D_FILE_OFFSET_BITS=64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
    470.lbm: -DSPEC_CPU_LP64
    481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64
```



SPEC CFP2006 Result

Copyright 2006-2017 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

Synergy 620 Gen9

(2.40 GHz, Intel Xeon E7-8894 v4)

SPECfp_rate2006 = 1210

SPECfp_rate_base2006 = 1180

CPU2006 license: 3

Test sponsor: HPE

Tested by: HPE

Test date: Feb-2017

Hardware Availability: Mar-2017

Software Availability: Nov-2016

Peak Optimization Flags

C benchmarks:

433.milc: basepeak = yes

470.lbm: basepeak = yes

482.sphinx3: basepeak = yes

C++ benchmarks:

444.namd: -xCORE-AVX2(pass 2) -prof-gen=threadsafe(pass 1)
-ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2)
-par-num-threads=1(pass 1) -no-prec-sqrt(pass 2)
-static(pass 2) -qopt-mem-layout-trans=3(pass 2)
-prof-use(pass 2) -fno-alias -auto-ilp32

447.dealII: basepeak = yes

450.soplex: -xCORE-AVX2(pass 2) -prof-gen=threadsafe(pass 1)
-ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2)
-par-num-threads=1(pass 1) -no-prec-sqrt(pass 2)
-static(pass 2) -qopt-mem-layout-trans=3(pass 2)
-prof-use(pass 2) -qopt-malloc-options=3

453.povray: -xCORE-AVX2(pass 2) -prof-gen=threadsafe(pass 1)
-ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2)
-par-num-threads=1(pass 1) -no-prec-sqrt(pass 2)
-static(pass 2) -qopt-mem-layout-trans=3(pass 2)
-prof-use(pass 2) -unroll4 -ansi-alias

Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: -prof-gen=threadsafe(pass 1) -prof-use(pass 2)
-xCORE-AVX2(pass 2) -par-num-threads=1(pass 1) -ipo(pass 2)
-O3(pass 2) -no-prec-div(pass 2) -no-prec-sqrt(pass 2)
-static(pass 2) -unroll12 -inline-level=0 -scalar-rep-

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: basepeak = yes

465.tonto: -prof-gen=threadsafe(pass 1) -prof-use(pass 2)
-xCORE-AVX2(pass 2) -par-num-threads=1(pass 1) -ipo(pass 2)
-O3(pass 2) -no-prec-div(pass 2) -no-prec-sqrt(pass 2)
-static(pass 2) -unroll4 -auto -inline-calloc
-qopt-malloc-options=3

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2017 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

Synergy 620 Gen9

(2.40 GHz, Intel Xeon E7-8894 v4)

SPECfp_rate2006 = 1210

SPECfp_rate_base2006 = 1180

CPU2006 license: 3

Test sponsor: HPE

Tested by: HPE

Test date: Feb-2017

Hardware Availability: Mar-2017

Software Availability: Nov-2016

Peak Optimization Flags (Continued)

Benchmarks using both Fortran and C:

```
435.gromacs: -xCORE-AVX2(pass 2) -prof-gen=threadsafe(pass 1)
              -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2)
              -par-num-threads=1(pass 1) -no-prec-sqrt(pass 2)
              -static(pass 2) -qopt-mem-layout-trans=3(pass 2)
              -prof-use(pass 2) -qopt-prefetch -auto-ilp32
```

```
436.cactusADM: basepeak = yes
```

```
454.calculix: basepeak = yes
```

```
481.wrf: -xCORE-AVX2 -ipo -O3 -no-prec-div -no-prec-sqrt -static
          -auto-ilp32
```

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/HP-Platform-Flags-Intel-V1.2-HSW-revE.html>
<http://www.spec.org/cpu2006/flags/HPE-Compiler-Flags-Intel-V1.2-HSW-revH.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/HP-Platform-Flags-Intel-V1.2-HSW-revE.xml>
<http://www.spec.org/cpu2006/flags/HPE-Compiler-Flags-Intel-V1.2-HSW-revH.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.

Report generated on Tue May 2 15:21:56 2017 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 2 May 2017.