



SPEC® CINT2006 Result

Copyright 2006-2017 Standard Performance Evaluation Corporation

Dell Inc.

SPECint®_rate2006 = 1210

PowerEdge C6320P (Intel Xeon Phi 7290F, 1.50 GHz)

SPECint_rate_base2006 = 1130

CPU2006 license: 55


Test date: Feb-2017

Test sponsor: Dell Inc.

Hardware Availability: Jan-2017

Tested by: Dell Inc.

Software Availability: Jan-2016



Hardware

CPU Name: Intel Xeon Phi 7290F
 CPU Characteristics: Intel Turbo Boost Technology up to 1.70 GHz
 CPU MHz: 1500
 FPU: Integrated
 CPU(s) enabled: 72 cores, 1 chip, 72 cores/chip, 4 threads/core
 CPU(s) orderable: 1 chip
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 1 MB I+D on chip per two cores
 L3 Cache: None
 Other Cache: None
 Memory: 400 GB (6 x 64 GB 2Rx8 PC4-2400T-R, 8 x 2 GB 7200 MHz MCDRAM)
 Disk Subsystem: 1 x 1 TB 7.2K SATA
 Other Hardware: None

Software

Operating System: SUSE Linux Enterprise Server 12 SP2 (x86_64) 4.4.16-56-default
 Compiler: C/C++; Version 16.0.2.181 of Intel C++ Studio XE for Linux
 Auto Parallel: No
 File System: btrfs
 System State: Run level 3 (multi-user)
 Base Pointers: 32-bit
 Peak Pointers: 32/64-bit
 Other Software: Microquill SmartHeap V10.2



SPEC CINT2006 Result

Copyright 2006-2017 Standard Performance Evaluation Corporation

Dell Inc.

SPECint_rate2006 = 1210

PowerEdge C6320P (Intel Xeon Phi 7290F, 1.50 GHz)

SPECint_rate_base2006 = 1130

CPU2006 license: 55

Test date: Feb-2017

Test sponsor: Dell Inc.

Hardware Availability: Jan-2017

Tested by: Dell Inc.

Software Availability: Jan-2016

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	288	4299	654	4419	637	4366	644	288	3792	742	3780	744	5855	481
401.bzip2	288	5001	556	4943	562	4671	595	288	4528	614	4535	613	4649	598
403.gcc	288	2772	836	2764	839	2800	828	288	2831	819	2808	826	2787	832
429.mcf	288	3402	772	3219	816	3254	807	288	3402	772	3219	816	3254	807
445.gobmk	288	3419	884	3423	883	3416	884	288	3041	993	3037	995	3022	1000
456.hammer	288	1656	1620	1693	1590	1656	1620	288	1231	2180	1228	2190	1233	2180
458.sjeng	288	4170	836	4158	838	4200	830	288	3990	873	4005	870	3979	876
462.libquantum	288	299	20000	298	20000	299	20000	288	299	20000	298	20000	299	20000
464.h264ref	288	4982	1280	4990	1280	4989	1280	288	4941	1290	4953	1290	4951	1290
471.omnetpp	288	2541	708	2546	707	2513	716	288	2150	837	2177	827	2163	832
473.astar	288	2969	681	2964	682	2983	678	288	2969	681	2964	682	2983	678
483.xalancbmk	288	1615	1230	1942	1020	1616	1230	288	1615	1230	1942	1020	1616	1230

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

The numactl mechanism was used to bind copies to processors. The config file option 'submit' was used to generate numactl commands to bind each copy to a specific processor. For details, please see the config file.

Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"

Platform Notes

BIOS settings:
 Virtualization Technology disabled
 System Profile set to Custom
 CPU Performance set to Maximum Performance
 C States set to autonomous
 C1E disabled
 Uncore Frequency set to Dynamic
 Energy Efficiency Policy set to Performance
 Memory Patrol Scrub disabled
 CPU Interconnect Bus Link Power Management disabled
 PCI ASPM L1 Link Power Management disabled
 Sysinfo program /root/cpu2006-1.2/config/sysinfo.rev6914
 \$Rev: 6914 \$ \$Date:: 2014-06-25 #\$ e3fbb8667b5a285932ceab81e28219e1
 running on linux-z6tq Mon Feb 13 18:18:38 2017

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2017 Standard Performance Evaluation Corporation

Dell Inc.

SPECint_rate2006 = 1210

PowerEdge C6320P (Intel Xeon Phi 7290F, 1.50 GHz)

SPECint_rate_base2006 = 1130

CPU2006 license: 55

Test date: Feb-2017

Test sponsor: Dell Inc.

Hardware Availability: Jan-2017

Tested by: Dell Inc.

Software Availability: Jan-2016

Platform Notes (Continued)

<http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

From /proc/cpuinfo

```

model name : Intel(R) Genuine Intel(R) CPU 0000 @ 1.50GHz
 1 "physical id"s (chips)
 288 "processors"
cores, siblings (Caution: counting these is hw and system dependent. The
following excerpts from /proc/cpuinfo might not be reliable. Use with
caution.)
  cpu cores : 72
  siblings  : 288
  physical 0: cores 0 1 2 3 8 9 10 11 12 13 14 15 18 19 20 21 22 23 24 25 26
 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 46 47 48 49 50 51 52 53
 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75
 cache size : 1024 KB

```

From /proc/meminfo

```

MemTotal:      396132044 kB
HugePages_Total:      0
Hugepagesize:    2048 kB

```

From /etc/*release* /etc/*version*

```

SuSE-release:
 SUSE Linux Enterprise Server 12 (x86_64)
 VERSION = 12
 PATCHLEVEL = 2
 # This file is deprecated and will be removed in a future service pack or
 release.
 # Please check /etc/os-release for details about this release.
os-release:
 NAME="SLES"
 VERSION="12-SP2"
 VERSION_ID="12.2"
 PRETTY_NAME="SUSE Linux Enterprise Server 12 SP2"
 ID="sles"
 ANSI_COLOR="0;32"
 CPE_NAME="cpe:/o:suse:sles:12:sp2"

```

uname -a:

```

Linux linux-z6tq 4.4.16-56-default #1 SMP Mon Aug 8 14:24:26 UTC 2016
(5b281a8) x86_64 x86_64 x86_64 GNU/Linux

```

run-level 3 Feb 13 15:41

SPEC is set to: /root/cpu2006-1.2

```

Filesystem      Type      Size  Used Avail Use% Mounted on
/dev/sdb2       btrfs    930G  15G  907G   2% /

```

Additional information from dmidecode:

Warning: Use caution when you interpret this section. The 'dmidecode' program reads system data which is "intended to allow hardware to be accurately determined", but the intent may not be met, as there are frequent changes to

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2017 Standard Performance Evaluation Corporation

Dell Inc.

SPECint_rate2006 = 1210

PowerEdge C6320P (Intel Xeon Phi 7290F, 1.50 GHz)

SPECint_rate_base2006 = 1130

CPU2006 license: 55
Test sponsor: Dell Inc.
Tested by: Dell Inc.

Test date: Feb-2017
Hardware Availability: Jan-2017
Software Availability: Jan-2016

Platform Notes (Continued)

hardware, firmware, and the "DMTF SMBIOS" standard.

BIOS Dell Inc. 1.1.3 12/001/2016

Memory:

6x Hynix HMAA8GL7MMR4N-UH 64 GB 4 rank 2400 MHz
8x INTEL N/A 2 GB 7200 MHz

(End of data from sysinfo program)

General Notes

Environment variables set by runspec before the start of the run:

LD_LIBRARY_PATH = "/root/cpu2006-1.2/libs/32:/root/cpu2006-1.2/libs/64:/root/cpu2006-1.2/sh"

Binaries compiled on a system with
Intel 2nd Generation Xeon Phi CPU
with 96GB DDR4 RAM memory using RedHat EL 7.2
Filesystem page cache cleared with:
echo 1> /proc/sys/vm/drop_caches
runspec command invoked through numactl i.e.:
numactl --interleave=all runspec <etc>

Base Compiler Invocation

C benchmarks:

icc -m32 -L/opt/intel/compilers_and_libraries_2016/linux/compiler/lib/ia32_lin

C++ benchmarks:

icpc -m32 -L/opt/intel/compilers_and_libraries_2016/linux/compiler/lib/ia32_lin

Base Portability Flags

400.perlbench: -D_FILE_OFFSET_BITS=64 -DSPEC_CPU_LINUX_IA32
401.bzip2: -D_FILE_OFFSET_BITS=64
403.gcc: -D_FILE_OFFSET_BITS=64
429.mcf: -D_FILE_OFFSET_BITS=64
445.gobmk: -D_FILE_OFFSET_BITS=64
456.hmmer: -D_FILE_OFFSET_BITS=64
458.sjeng: -D_FILE_OFFSET_BITS=64
462.libquantum: -D_FILE_OFFSET_BITS=64 -DSPEC_CPU_LINUX
464.h264ref: -D_FILE_OFFSET_BITS=64
471.omnetpp: -D_FILE_OFFSET_BITS=64
473.astar: -D_FILE_OFFSET_BITS=64
483.xalancbmk: -D_FILE_OFFSET_BITS=64 -DSPEC_CPU_LINUX



SPEC CINT2006 Result

Copyright 2006-2017 Standard Performance Evaluation Corporation

Dell Inc.

SPECint_rate2006 = 1210

PowerEdge C6320P (Intel Xeon Phi 7290F, 1.50 GHz)

SPECint_rate_base2006 = 1130

CPU2006 license: 55

Test date: Feb-2017

Test sponsor: Dell Inc.

Hardware Availability: Jan-2017

Tested by: Dell Inc.

Software Availability: Jan-2016

Base Optimization Flags

C benchmarks:

-xMIC-AVX512 -ipo -O3 -no-prec-div -opt-prefetch

C++ benchmarks:

-xMIC-AVX512 -ipo -O3 -no-prec-div -opt-prefetch -Wl,-z,muldefs
-L/sh -lsmartheap

Base Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

Peak Compiler Invocation

C benchmarks (except as noted below):

icc -m32 -L/opt/intel/compilers_and_libraries_2016/linux/compiler/lib/ia32_lin

400.perlbench: icc -m64

401.bzip2: icc -m64

456.hmmer: icc -m64

458.sjeng: icc -m64

C++ benchmarks:

icpc -m32 -L/opt/intel/compilers_and_libraries_2016/linux/compiler/lib/ia32_lin

Peak Portability Flags

400.perlbench: -D_FILE_OFFSET_BITS=64 -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX_X64

401.bzip2: -D_FILE_OFFSET_BITS=64 -DSPEC_CPU_LP64

403.gcc: -D_FILE_OFFSET_BITS=64

429.mcf: -D_FILE_OFFSET_BITS=64

445.gobmk: -D_FILE_OFFSET_BITS=64

456.hmmer: -D_FILE_OFFSET_BITS=64 -DSPEC_CPU_LP64

458.sjeng: -D_FILE_OFFSET_BITS=64 -DSPEC_CPU_LP64

462.libquantum: -D_FILE_OFFSET_BITS=64 -DSPEC_CPU_LINUX

464.h264ref: -D_FILE_OFFSET_BITS=64

471.omnetpp: -D_FILE_OFFSET_BITS=64

473.astar: -D_FILE_OFFSET_BITS=64

483.xalancbmk: -D_FILE_OFFSET_BITS=64 -DSPEC_CPU_LINUX



SPEC CINT2006 Result

Copyright 2006-2017 Standard Performance Evaluation Corporation

Dell Inc.

SPECint_rate2006 = 1210

PowerEdge C6320P (Intel Xeon Phi 7290F, 1.50 GHz)

SPECint_rate_base2006 = 1130

CPU2006 license: 55

Test date: Feb-2017

Test sponsor: Dell Inc.

Hardware Availability: Jan-2017

Tested by: Dell Inc.

Software Availability: Jan-2016

Peak Optimization Flags

C benchmarks:

400.perlbench: -xMIC-AVX512 -ipo -O3 -no-prec-div -prof-gen(pass 1)
-prof-use(pass 2) -par-num-threads=1(pass 1) -auto-ilp32

401.bzip2: -xMIC-AVX512 -ipo -O3 -no-prec-div -prof-gen(pass 1)
-prof-use(pass 2) -par-num-threads=1(pass 1) -opt-prefetch
-auto-ilp32 -ansi-alias

403.gcc: -xMIC-AVX512 -ipo -O3 -no-prec-div

429.mcf: basepeak = yes

445.gobmk: -xMIC-AVX512(pass 2) -prof-gen(pass 1)
-par-num-threads=1(pass 1) -prof-use(pass 2) -ansi-alias

456.hmmer: -xMIC-AVX512 -ipo -O3 -no-prec-div -unroll2 -auto-ilp32

458.sjeng: -xMIC-AVX512 -ipo -O3 -no-prec-div -prof-gen(pass 1)
-prof-use(pass 2) -par-num-threads=1(pass 1) -unroll4
-auto-ilp32

462.libquantum: basepeak = yes

464.h264ref: -xMIC-AVX512 -ipo -O3 -no-prec-div -prof-gen(pass 1)
-prof-use(pass 2) -par-num-threads=1(pass 1) -unroll2
-ansi-alias

C++ benchmarks:

471.omnetpp: -xMIC-AVX512 -ipo -O3 -no-prec-div -prof-gen(pass 1)
-prof-use(pass 2) -par-num-threads=1(pass 1) -ansi-alias
-opt-ra-region-strategy=block -Wl,-z,muldefs
-L/sh -lsmartheap

473.astar: basepeak = yes

483.xalancbmk: basepeak = yes

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca



SPEC CINT2006 Result

Copyright 2006-2017 Standard Performance Evaluation Corporation

Dell Inc.

SPECint_rate2006 = 1210

PowerEdge C6320P (Intel Xeon Phi 7290F, 1.50 GHz)

SPECint_rate_base2006 = 1130

CPU2006 license: 55

Test date: Feb-2017

Test sponsor: Dell Inc.

Hardware Availability: Jan-2017

Tested by: Dell Inc.

Software Availability: Jan-2016

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic16.0-official-linux64-revB.html>

<http://www.spec.org/cpu2006/flags/Dell-Platform-Flags-PowerEdge14G-revC.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic16.0-official-linux64-revB.xml>

<http://www.spec.org/cpu2006/flags/Dell-Platform-Flags-PowerEdge14G-revC.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.
Report generated on Wed Aug 23 13:13:02 2017 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 22 August 2017.