



SPEC CPU®2017 Floating Point Speed Result

Copyright 2017-2023 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

ProLiant DL325 Gen11

(3.60 GHz, AMD EPYC 9474F)

SPECSpeed®2017_fp_base =

SPECSpeed®2017_fp_peak =

CPU2017 License: 3

Test Sponsor: HPE

Tested by: HPE

Test Date: Dec-2022

Hardware Availability: Dec-2022

Software Availability: Nov-2022

SPEC has determined that this result does not comply with the SPEC CPU 2017 rules and reporting rules. Specifically, the test sponsor notified SPEC that the results were measured on an unsupported configuration.

Threads

603.bwaves_s

607.cactuBSSN_s

619.lbm_s

621.wrf_s

627.cam4_s

628.pop2_s

638.imagick_s

644.nab_s

649.fotonik3d_s

654.roms_s

Hardware

CPU Name: AMD EPYC 9474F

Nominal: 3600

Enabled: 48 cores, 1 chip

Orderable: 1 chip

Cache L1: 32 KB I + 32 KB D on chip per core

L2: 1 MB I+D on chip per core

L3: 256 MB I+D on chip per chip,
32 MB shared / 6 cores

Other: None

Memory: 768 GB (12 x 64 GB 2Rx4 PC5-4800B-R)

Storage: 1 x 480 GB SATA SSD

Other: None

OS:

Red Hat Enterprise Linux 9.0 (Plow)

Kernel 5.14.0-70.13.1.el9_0.x86_64

C/C++/Fortran: Version 4.0.0 of AOCC

Yes

HPE BIOS Version v1.12 11/24/2022 released
Nov-2022

File System:

xfs

System State:

Run level 3 (multi-user)

Base Pointers:

64-bit

Peak Pointers:

64-bit

Other:

None

Power Management: BIOS and OS set to prefer performance at
the cost of additional power usage



SPEC CPU®2017 Floating Point Speed Result

Copyright 2017-2023 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

ProLiant DL325 Gen11

(3.60 GHz, AMD EPYC 9474F)

~~SPECSpeed®2017_fp_base =~~

~~SPECSpeed®2017_fp_peak =~~

CPU2017 License: 3

Test Sponsor: HPE

Tested by: HPE

Test Date: Dec-2022

Hardware Availability: Dec-2022

Software Availability: Nov-2022

SPEC has determined that this result does not comply with the SPEC CPU 2017 rules and reporting rules. Specifically, the test sponsor notified SPEC that the results were measured on an unsupported configuration.

Results Table

Benchmark	Base								Peak							
	Threads	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Threads	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
603.bwaves_s	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
607.cactuBSSN_s	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
619.lbm_s	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
621.wrf_s	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
627.cam4_s	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
628.pop2_s	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
638.imagick_s	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
644.nab_s	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
649.fotonik3d_s	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
654.roms_s	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC

~~SPECSpeed®2017_fp_base =~~

~~SPECSpeed®2017_fp_peak =~~

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Compiler Notes

The AMD64 AOCC Compiler Suite is available at
<http://developer.amd.com/amd64-oc/>

Submit Notes

The config file option 'submit' was used.
 to bind copies to the cores.
See the configuration file for details.

Operating System Notes

'ulimit -s unlimited' was used to set environment stack size limit
'ulimit -l 2097152' was used to set environment locked pages in memory limit

runcpu command invoked through numactl i.e.:
numactl --interleave=all runcpu <etc>

To limit dirty cache to 8% of memory, 'sysctl -w vm.dirty_ratio=8' run as root.
To limit swap usage to minimum necessary, 'sysctl -w vm.swappiness=1' run as root.
To free node-local memory and avoid remote memory usage,
'sysctl -w vm.zone_reclaim_mode=1' run as root.
To clear filesystem caches, 'sync; sysctl -w vm.drop_caches=3' run as root.

(Continued on next page)



SPEC CPU®2017 Floating Point Speed Result

Copyright 2017-2023 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

ProLiant DL325 Gen11

(3.60 GHz, AMD EPYC 9474F)

SPECspeed®2017_fp_base =

SPECspeed®2017_fp_peak =

CPU2017 License: 3

Test Sponsor: HPE

Tested by: HPE

Test Date: Dec-2022

Hardware Availability: Dec-2022

Software Availability: Nov-2022

SPEC has determined that this result does not comply with the SPEC CPU 2017 rules and reporting rules. Specifically, the test sponsor notified SPEC that the results were measured on an unsupported configuration.

Operating System Notes (Continued)

To disable address space layout randomization (ASLR) to reduce run-to-run variability, 'sysctl -w kernel.randomize_va_space=0' run as root.

To enable Transparent Hugepages (THP) for all allocations:
'echo always > /sys/kernel/mm/transparent_hugepage/enabled' and
'echo always > /sys/kernel/mm/transparent_hugepage/defrag' run as root.

To always enable THP for peak runs of:

603.bwaves_s, 607.cactusSSN_s, 619.lbm_s, 627.cam4_s, 628.pop2_s, 638.imagick_s, 644.nab_s, 649.fotonik3d_s:
'echo madvise > /sys/kernel/mm/transparent_hugepage/enabled; echo always > /sys/kernel/mm/transparent_hugepage/defrag'
run as root.

To disable THP for peak runs of 621.wrf_s:

'echo never > /sys/kernel/mm/transparent_hugepage/enabled; echo always > /sys/kernel/mm/transparent_hugepage/defrag'
run as root.

To enable THP only on request for peak runs of 654.roms_s:

'echo madvise > /sys/kernel/mm/transparent_hugepage/enabled; echo madvise > /sys/kernel/mm/transparent_hugepage/defrag'
run as root.

Environment Variables Notes

Environment variables set by runcpu before the start of the run:

GOMP_CPU_AFFINITY = "0-7"
LD_LIBRARY_PATH = "/home/cpu2017/lib_speed_aocc400_genoa_B/lib/lib:
LIBOMP_NUM_HIDDEN_HELPERS_THREADS = "0"
MALLOC_CONF = "oversize_treshold:0,retain:true"
OMP_DYNAMIC = "false"
OMP_SCHEDULE = "static"
OMP_STEPPESIZE = "128M"
OMP_THREAD_LIMIT = "48"

Environment variables set by runcpu during the 603.bwaves_s peak run:

GOMP_CPU_AFFINITY = "0-47"

Environment variables set by runcpu during the 619.lbm_s peak run:

GOMP_CPU_AFFINITY = "0-47"

Environment variables set by runcpu during the 621.wrf_s peak run:

GOMP_CPU_AFFINITY = "0-47"

Environment variables set by runcpu during the 628.pop2_s peak run:

GOMP_CPU_AFFINITY = "0-47"

Environment variables set by runcpu during the 638.imagick_s peak run:

GOMP_CPU_AFFINITY = "0-47"

Environment variables set by runcpu during the 654.roms_s peak run:

GOMP_CPU_AFFINITY = "0 24 1 25 2 26 3 27 4 28 5 29 6 30 7 31 8 32 9 33 10 34 11 35 12 36 13 37 14 38 15 39
16 40 17 41 18 42 19 43 20 44 21 45 22 46 23 47"



SPEC CPU®2017 Floating Point Speed Result

Copyright 2017-2023 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

ProLiant DL325 Gen11

(3.60 GHz, AMD EPYC 9474F)

~~SPECSpeed®2017_fp_base =~~

~~SPECSpeed®2017_fp_peak =~~

CPU2017 License: 3

Test Sponsor: HPE

Tested by: HPE

Test Date: Dec-2022

Hardware Availability: Dec-2022

Software Availability: Nov-2022

SPEC has determined that this result does not comply with the SPEC CPU 2017 rules and reporting rules. Specifically, the test sponsor notified SPEC that the results were measured on an unsupported configuration.

General Notes

Binaries were compiled on a system with 2x AMD EPYC 9174 32-Core + 1.5TB Memory using RHEL 8.6

NA: The test sponsor attests, as of date of publication, that CVE-2017-5754 (Meltdown) is mitigated in the system as tested and documented.

Yes: The test sponsor attests, as of date of publication, that CVE-2017-5753 (Spectre variant 1) is mitigated in the system as tested and documented.

Yes: The test sponsor attests, as of date of publication, that CVE-2017-5715 (Spectre variant 2) is mitigated in the system as tested and documented.

Platform Notes

BIOS Configuration

Workload Profile set to General Work Frequency Compute
Determinism Control set to Manual
Performance Determinism set to Power-Deterministic
AMD SMT Option set to Disabled
Last-Level Cache (LLC) as NUMA Node set to Enabled
ACPI C2 Latency set to 18 microseconds
Memory PStates set to Default
Thermal Configuration set to Maximum Cooling
Workload Profile set to Custom
Power Regulator set to BIOS Control Mode

The system ROM used for this result contains microcode version 0xa10110e for the AMD EPYC 9nn4X family of processors. The reference code/AGESA version used in this ROM is version GenoaAPI - 0.0.1-L6

Sysinfo program: /home/cpu2017/bin/sysinfo
Rev: r6622 of 2022-04-07 982a61ec0915b55891ef0e16acafcc64d
running on localhost.localdomain Thu Apr 7 05:32:43 2022

SUT (System Under Test) info as seen by some common utilities.
For more information on this section, see
<https://www.spec.org/cpu2017/Docs/config.html#sysinfo>

From /proc/cpuinfo
model name : AMD EPYC 9474F 48-Core Processor
1 "physical id"s (chips)
48 "processors"
cores, siblings (Caution: counting these is hw and system dependent. The following
excerpts from /proc/cpuinfo might not be reliable. Use with caution.)
cpu cores : 48
siblings : 48
physical 0: cores 0 1 2 3 4 5 8 9 10 11 12 13 16 17 18 19 20 21 24 25 26 27 28 29
32 33 34 35 36 37 40 41 42 43 44 45 48 49 50 51 52 53 56 57 58 59 60 61

From lscpu from util-linux 2.37.4:
Architecture: x86_64
CPU op-mode(s): 32-bit, 64-bit

(Continued on next page)



SPEC CPU®2017 Floating Point Speed Result

Copyright 2017-2023 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

ProLiant DL325 Gen11

(3.60 GHz, AMD EPYC 9474F)

~~SPECspeed®2017_fp_base =~~

~~SPECspeed®2017_fp_peak =~~

CPU2017 License: 3

Test Sponsor: HPE

Tested by: HPE

Test Date: Dec-2022

Hardware Availability: Dec-2022

Software Availability: Nov-2022

SPEC has determined that this result does not comply with the SPEC CPU 2017 rules and reporting rules. Specifically, the test sponsor notified SPEC that the results were measured on an unsupported configuration.

Platform Notes (Continued)

Address sizes:
Byte Order:
CPU(s):
On-line CPU(s) list:
Vendor ID:
BIOS Vendor ID:
Model name:
BIOS Model name:
CPU family:
Model:
Thread(s) per core:
Core(s) per socket:
Socket(s):
Stepping:
Frequency boost:
CPU max MHz:
CPU min MHz:
BogoMIPS:
Flags:
pge mca cmov pat pse36 clflush mmx fxsr sse sse2 ht syscall nx mmxext fxsr_opt
pdpe1gb rdtscp lm stant_tsc rep_good noopl nonstop_tsc cpuid extd_apicid
aperfmpf rapl pni pdlq dq monitor ssse3 fma cx16 pcid sse4_1 sse4_2 x2apic movbe
popcnt aes xsaves vx f16c dbrand lahf_lm cmp_legacy svm extapic cr8_legacy abm sse4a
misalignsse 3dnowprefetch svw ibs skininit wdt tce topoext perfctr_core perfctr_nb
bpext perfctr_llc m6tx cpb cat_13 cdp_13 invpcid_single hw_pstate ssbd mba ibrs
ibpb stibp l1_l2_f16e bmi1 avx2 smep bmi2 erms invpcid cqm rdt_a avx512f
avx512dq rdseed rdseed洪 x smep avx512ifma clflushopt clwb avx512cd sha_ni avx512bw
avx512vl xsaveopt xsavec xgetbv1 xsaves cqmm_llc cqmm_occu_llc cqmm_mbmm_total
sm_mbmm_total avx512_bf16 clzero irperf xsaveerptr rdpru wbnoinvd amd_ppin arat npt
l1v svn_rk nrrip_save tsc_scale vmcb_clean flushbyasid decodeassist pausefilter
pfthreshold l1v_vmsave_vmload vgif v_spec_ctrl avx512vbmi umip pku ospke
avx512vbmi2 gfni vaes vpclmulqdq avx512_vnni avx512_bitalg avx512_vpopsrndq la57
avx512_vnni overflow_recov succor smca fsrm flush_ll1
L1d cache: AMD-V
L1i cache: 1.5 MiB (48 instances)
L2 cache: 1.5 MiB (48 instances)
L3 cache: 48 MiB (48 instances)
NUMA node(s): 256 MiB (8 instances)
NUMA node0 CPU(s): 8
NUMA node0 CPU(s): 0-5
NUMA node1 CPU(s): 24-29
NUMA node2 CPU(s): 12-17
NUMA node3 CPU(s): 36-41
NUMA node4 CPU(s): 18-23
NUMA node5 CPU(s): 42-47
NUMA node6 CPU(s): 6-11
NUMA node7 CPU(s): 30-35
Vulnerability Itlb multihit: Not affected
Vulnerability L1tf: Not affected
Vulnerability Mds: Not affected
Vulnerability Meltdown: Not affected

(Continued on next page)



SPEC CPU®2017 Floating Point Speed Result

Copyright 2017-2023 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise
(Test Sponsor: HPE)
ProLiant DL325 Gen11
(3.60 GHz, AMD EPYC 9474F)

SPECspeed®2017_fp_base =
SPECspeed®2017_fp_peak =

CPU2017 License: 3
Test Sponsor: HPE
Tested by: HPE

Test Date: Dec-2022
Hardware Availability: Dec-2022
Software Availability: Nov-2022

SPEC has determined that this result does not comply with the SPEC CPU 2017 rules and reporting rules. Specifically, the test sponsor notified SPEC that the results were measured on an unsupported configuration.

Platform Notes (Continued)

Vulnerability Spec store bypass: Mitigation; Spec Store Bypass disabled via prctl
Vulnerability Spectre v1: Mitigation; usercopy/swiotlb barriers and __user pointer sanitization
Vulnerability Spectre v2: Mitigation; Retpolines, IBPB conditional, IBRS_FW, STIBP disabled, RSB filling
Vulnerability Srbds: Not affected
Vulnerability Tsx async abort: Not affected

From lscpu --cache:

NAME	ONE-SIZE	ALL-SIZE	WAYS	TYPE	LEVEL	SETS	PHY-LINE	COHERENCY-SIZE
L1d	32K	1.5M	1	Data	1	64	1	64
L1i	32K	1.5M	1	Instruction	1	64	1	64
L2	1M	48M	16	Unified	2	2048	1	64
L3	32M	256M	16	Unified	3	32768	1	64

/proc/cpuinfo cache data
cache size : 1024 KB

From numactl --hardware
WARNING: a numactl 'node' might not correspond to a physical chip.
available: 8 nodes (0-7)
node 0 cpus: 0 1 2 3 4 5
node 0 size: 96520 MB
node 0 free: 96265 MB
node 1 cpus: 6 7 8 9 10 11 12 13 14 15 16 17
node 1 size: 96766 MB
node 1 free: 96590 MB
node 2 cpus: 12 13 14 15 16 17
node 2 size: 1766 MB
node 2 free: 96265 MB
node 3 cpus: 36 37 38 39 40 41
node 3 size: 96766 MB
node 3 free: 95597 MB
node 4 cpus: 18 19 20 21 22 23
node 4 size: 96766 MB
node 4 free: 96607 MB
node 5 cpus: 42 43 44 45 46 47
node 5 size: 96718 MB
node 5 free: 96396 MB
node 6 cpus: 6 7 8 9 10 11
node 6 size: 96766 MB
node 6 free: 96473 MB
node 7 cpus: 30 31 32 33 34 35
node 7 size: 96730 MB
node 7 free: 96530 MB
node distances:
node 0 1 2 3 4 5 6 7
0: 10 11 11 11 11 11 11 11
1: 11 10 11 11 11 11 11 11
2: 11 11 10 11 11 11 11 11

(Continued on next page)



SPEC CPU®2017 Floating Point Speed Result

Copyright 2017-2023 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

ProLiant DL325 Gen11

(3.60 GHz, AMD EPYC 9474F)

SPECSpeed®2017_fp_base =

SPECSpeed®2017_fp_peak =

CPU2017 License: 3

Test Sponsor: HPE

Tested by: HPE

Test Date: Dec-2022

Hardware Availability: Dec-2022

Software Availability: Nov-2022

SPEC has determined that this result does not comply with the SPEC CPU 2017 rules and reporting rules. Specifically, the test sponsor notified SPEC that the results were measured on an unsupported configuration.

Platform Notes (Continued)

```
3: 11 11 11 11 10 11 11 11 11  
4: 11 11 11 11 10 11 11 11 11  
5: 11 11 11 11 11 10 11 11 11  
6: 11 11 11 11 11 11 10 11 11  
7: 11 11 11 11 11 11 11 11 10

From /proc/meminfo
MemTotal: 792372436 kB
HugePages_Total: 0
Hugepagesize: 2048 kB

/sbin/tuned-adm active
    Current active profile: throughput-performance

/sys/devices/system/cpu/cpu*/cpu*/cq/scaling_governor has
    performance

From /etc/*release* /etc/*version*
os-release:
    NAME="Red Hat Enterprise Linux"
    VERSION="9.0 (Plow)"
    ID="rhel"
    ID_LIKE="fedora"
    VERSION_ID="9.0"
    PLATFORM_ID="platform:el9"
    PRETTY_NAME="Red Hat Enterprise Linux 9.0 (Plow)"
    ANSI_COLOR="0;32"
    redhat-release: Red Hat Enterprise Linux release 9.0 (Plow)
    system-release: Red Hat Enterprise Linux release 9.0 (Plow)
    system-release-cpe: cpe:/o:redhat:enterprise_linux:9::baseos

uname -a:
Linux localhost.localdomain 5.14.0-70.13.1.el9_0.x86_64 #1 SMP PREEMPT Thu Apr 14
2022 x86_64 x86_64 x86_64 GNU/Linux

Kernel self-reported vulnerability status:

CVE-2017-12207 (iTLB Multihit): Not affected
CVE-2018-3620 (L1 Terminal Fault): Not affected
Microarchitectural Data Sampling: Not affected
CVE-2017-5754 (Meltdown): Not affected
CVE-2018-3639 (Speculative Store Bypass): Mitigation: Speculative Store
Bypass disabled via prctl
CVE-2017-5753 (Spectre variant 1): Mitigation: usercopy/swaps
barriers and __user pointer
sanitization
CVE-2017-5715 (Spectre variant 2): Mitigation: Retpolines, IBPB:
conditional, IBRS_FW, STIBP:
disabled, RSB filling
CVE-2020-0543 (Special Register Buffer Data Sampling): Not affected
CVE-2019-11135 (TSX Asynchronous Abort): Not affected
```

(Continued on next page)



SPEC CPU®2017 Floating Point Speed Result

Copyright 2017-2023 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

ProLiant DL325 Gen11

(3.60 GHz, AMD EPYC 9474F)

SPECSpeed®2017_fp_base =

SPECSpeed®2017_fp_peak =

CPU2017 License: 3

Test Sponsor: HPE

Tested by: HPE

Test Date: Dec-2022

Hardware Availability: Dec-2022

Software Availability: Nov-2022

SPEC has determined that this result does not comply with the SPEC CPU 2017 rules and reporting rules. Specifically, the test sponsor notified SPEC that the results were measured on an unsupported configuration.

Platform Notes (Continued)

run-level 3 Apr 7 05:30

SPEC is set to: /home/cpu2017

Filesystem	Type	Size	Used	Avail	Use%	Mounted on
/dev/mapper/rhel-home	xfs	372G	17G	356G	4%	/home

From /sys/devices/virtual/dmi/id

Vendor	
HPE	

Product	
ProLiant DL325	Gen11

Product Family	
ProLiant	

Serial	
DL325GEN11-02	

Additional information from dmidecode 3.3 follows. WARNING: Use caution when you interpret this section. The 'dmidecode' program reads system data which is "intended to allow hardware to be accurately determined" but the intent may not be met, as there are frequent changes to hardware, firmware, and the "DMTF SMBIOS" standard.

Memory:

12x Hynix HMCG94MEBRA121N 64GB 2 rank 4800

BIOS:

BIOS Vendor	
HPE	

BIOS Version	
1.12	

BIOS Date	
1/24/2022	

BIOS Revision	
1.12	

Firmware Revision	
1.10	

(End of data from sysinfo program)

Compiler Version Notes

=====
+ 619.lbm_s(base, peak) 638.imagick_s(base, peak) 644.nab_s(base, peak)

AMD clang version 14.0.6 (CLANG: AOCC_4.0.0-Build#389 2022_10_07) (based on LLVM Mirror.Version.14.0.6)
Target: x86_64-unknown-linux-gnu
Thread model: posix
InstalledDir: /opt/AMD/aocc/aocc-compiler-rel-4.0-3206-389/bin

=====
C++, C, Fortran | 607.cactusBSSN_s(base, peak)

=====
AMD clang version 14.0.6 (CLANG: AOCC_4.0.0-Build#389 2022_10_07) (based on LLVM Mirror.Version.14.0.6)
Target: x86_64-unknown-linux-gnu
Thread model: posix
InstalledDir: /opt/AMD/aocc/aocc-compiler-rel-4.0-3206-389/bin
AMD clang version 14.0.6 (CLANG: AOCC_4.0.0-Build#389 2022_10_07) (based on LLVM Mirror.Version.14.0.6)
Target: x86_64-unknown-linux-gnu
Thread model: posix

(Continued on next page)



SPEC CPU®2017 Floating Point Speed Result

Copyright 2017-2023 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

ProLiant DL325 Gen11

(3.60 GHz, AMD EPYC 9474F)

SPECSpeed®2017_fp_base =

SPECSpeed®2017_fp_peak =

CPU2017 License: 3

Test Sponsor: HPE

Tested by: HPE

Test Date: Dec-2022

Hardware Availability: Dec-2022

Software Availability: Nov-2022

SPEC has determined that this result does not comply with the SPEC CPU 2017 rules and reporting rules. Specifically, the test sponsor notified SPEC that the results were measured on an unsupported configuration.

Compiler Version Notes (Continued)

InstalledDir: /opt/AMD/aocc/aocc-compiler-rel-4.0-3206-389/bin
AMD clang version 14.0.6 (CLANG: A_OCC_4.0.0-Build#389_2022_10_07) (based on LLVM Mirror.Version.14.0.6)

Target: x86_64-unknown-linux-gnu

Thread model: posix

InstalledDir: /opt/AMD/aocc/aocc-compiler-rel-4.0-3206-389/bin

=====
Fortran | 603.bwaves_s(base, peak) 642.fotonik3d_s(base, peak) 654.roms_s(base, peak)

AMD clang version 14.0.6 (CLANG: A_OCC_4.0.0-Build#389_2022_10_07) (based on LLVM Mirror.Version.14.0.6)

Target: x86_64-unknown-linux-gnu

Thread model: posix

InstalledDir: /opt/AMD/aocc/aocc-compiler-rel-4.0-3206-389/bin

=====
Fortran, C | 621.wrf_s(base, peak) 627.cam4_s(base, peak) 628.pop2_s(base, peak)

AMD clang version 14.0.6 (CLANG: A_OCC_4.0.0-Build#389_2022_10_07) (based on LLVM Mirror.Version.14.0.6)

Target: x86_64-unknown-linux-gnu

Thread model: posix

InstalledDir: /opt/AMD/aocc/aocc-compiler-rel-4.0-3206-389/bin

AMD clang version 14.0.6 (CLANG: A_OCC_4.0.0-Build#389_2022_10_07) (based on LLVM Mirror.Version.14.0.6)

Target: x86_64-unknown-linux-gnu

Thread model: posix

InstalledDir: /opt/AMD/aocc/aocc-compiler-rel-4.0-3206-389/bin

Base Compiler Invocation

Benchmarks:

clang

Fortran benchmarks:

flang

Benchmarks using both Fortran and C:

flang clang

Benchmarks using Fortran, C, and C++:

clang++ clang flang



SPEC CPU®2017 Floating Point Speed Result

Copyright 2017-2023 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

ProLiant DL325 Gen11

(3.60 GHz, AMD EPYC 9474F)

~~SPECspeed®2017_fp_base =~~

~~SPECspeed®2017_fp_peak =~~

CPU2017 License: 3

Test Sponsor: HPE

Tested by: HPE

Test Date: Dec-2022

Hardware Availability: Dec-2022

Software Availability: Nov-2022

SPEC has determined that this result does not comply with the SPEC CPU 2017 rules and reporting rules. Specifically, the test sponsor notified SPEC that the results were measured on an unsupported configuration.

Base Portability Flags

603.bwaves_s: -DSPEC_LP64
607.cactuBSSN_s: -DSPEC_LP64
619.lbm_s: -DSPEC_LP64
621.wrf_s: -DSPEC_CASE_FLAG -Mbyteswapi -DSPEC_LP64
627.cam4_s: -DSPEC_CASE_FLAG -DSPEC_LP64
628.pop2_s: -DSPEC_CASE_FLAG -Mbyteswapi -DSPEC_LP64
638.imagick_s: -DSPEC_LP64
644.nab_s: -DSPEC_LP64
649.fotonik3d_s: -DSPEC_LP64
654.roms_s: -DSPEC_LP64

Base Optimization Flags

C benchmarks:

-m64 -Wl,-mllvm -Wl,-align-all-nofallthru-blocks=6
-Wl,-mllvm -Wl,-reduce-array-computations=3 -O3 -march=znver4
-fveclib=AMDLIBM -ffast-math -fopenmp -flto -fstruct-layout=7
-mllvm -unroll-loops=50 -mllvm -inline-threshold=1000
-fremap-arrays -fsrip-mining -mllvm -reduce-array-computations=3
-DSPEC_OPENMP -zopt -fopenmp=libomp -lomp -lamdlibm -lamdaloc
-lf1lang

Fortran benchmarks:

-m64 -Wl,-align-all-nofallthru-blocks=6
-Wl,-mllvm -Wl,-reduce-array-computations=3
-Wl,-mllvm -Wl,-enable-X86-prefetching -DSPEC_OPENMP -O3 -march=znver4
-fveclib=AMDLIBM -ffast-math -fopenmp -flto -Mrecursive
-funroll-loops -mllvm -lsr-in-nested-loop
-mllvm -reduce-array-computations=3 -zopt -fopenmp=libomp -lomp
-lamdlibm -lamdaloc -lf1lang

Benchmarks using both Fortran and C:

-m64 -Wl,-mllvm -Wl,-align-all-nofallthru-blocks=6
-Wl,-mllvm -Wl,-reduce-array-computations=3
-Wl,-mllvm -Wl,-enable-X86-prefetching -O3 -march=znver4
-fveclib=AMDLIBM -ffast-math -fopenmp -flto -fstruct-layout=7
-mllvm -unroll-threshold=50 -mllvm -inline-threshold=1000

(Continued on next page)



SPEC CPU®2017 Floating Point Speed Result

Copyright 2017-2023 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

ProLiant DL325 Gen11

(3.60 GHz, AMD EPYC 9474F)

SPECspeed®2017_fp_base =

SPECspeed®2017_fp_peak =

CPU2017 License: 3

Test Sponsor: HPE

Tested by: HPE

Test Date: Dec-2022

Hardware Availability: Dec-2022

Software Availability: Nov-2022

SPEC has determined that this result does not comply with the SPEC CPU 2017 rules and reporting rules. Specifically, the test sponsor notified SPEC that the results were measured on an unsupported configuration.

Base Optimization Flags (Continued)

Benchmarks using both Fortran and C (continued):

```
-fremap-arrays -fstrip-mining -mllvm -reduce-array-computations=3  
-DSPEC_OPENMP -zopt -Mrecursive -funroll-loops  
-mllvm -lsrc-in-nested-loop -fopenmp=libomp -lomp -lamdlibm -lamdaloc  
-lflang
```

Benchmarks using Fortran, C, and C++:

```
-m64 -Wl,-mllvm -Wl,-align-all-nofallt -blocks=6  
-Wl,-mllvm -Wl,-reduce-array-computations=3  
-Wl,-mllvm -Wl,-x86-use-vectorupper=false -O3 -march=znver4  
-fveclib=AMDLIB -ffast-math -fopenmp -floop -fstruct-layout=7  
-mllvm -unroll-threshold=50 -mllvm -inline-threshold=1000  
-fremap-arrays -fstrip-mining -mllvm -reduce-array-computations=3  
-DSPEC_OPENMP -zopt -mllvm -unroll-threshold=100 -finline-aggressive  
-mllvm -loop-unswitch-threshold=200000 -Mrecursive -funroll-loops  
-mllvm -lsrc-in-nested-loop -fopenmp=libomp -lomp -lamdlibm -lamdaloc  
-lflang
```

Base Other Flags

C benchmarks:

```
-Wno-return-type -Wno-unused-command-line-argument  
  
-Wno-unused-command-line-argument
```

Benchmarks using both Fortran and C:

```
-Wno-return-type -Wno-unused-command-line-argument
```

Benchmarks using Fortran, C, and C++:

```
-Wno-return-type -Wno-unused-command-line-argument
```



SPEC CPU®2017 Floating Point Speed Result

Copyright 2017-2023 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

ProLiant DL325 Gen11

(3.60 GHz, AMD EPYC 9474F)

SPECspeed®2017_fp_base =

SPECspeed®2017_fp_peak =

CPU2017 License: 3

Test Sponsor: HPE

Tested by: HPE

Test Date: Dec-2022

Hardware Availability: Dec-2022

Software Availability: Nov-2022

SPEC has determined that this result does not comply with the SPEC CPU 2017 rules and reporting rules. Specifically, the test sponsor notified SPEC that the results were measured on an unsupported configuration.

Peak Compiler Invocation

C benchmarks:

clang

Fortran benchmarks:

flang

Benchmarks using both Fortran and C:

flang clang

Benchmarks using Fortran, C, and C++:

clang++ clang flang

Peak Portability Flags

Same as Base Portability Flags

Peak Optimization Flags

C benchmarks:

```
619.lbm_s: -m64 -Wl,-mllvm -Wl,-align-all-nofallthru-blocks=6
-Wl,-mllvm -Wl,-reduce-array-computations=3 -Ofast
-march=znver4 -fveclib=AMDLIBM -ffast-math -fopenmp
-flt -fstruct-layout=9 -mllvm -unroll-threshold=50
-freemap-arrays -fstrip-mining
-mllvm -inline-threshold=1000
-mllvm -reduce-array-computations=3 -DSPEC_OPENMP -zopt
-fopenmp=libomp -lomp -lamdlibm -lamdalloc -lflang
```

638.imagick_s: Same as 619.lbm_s

644.nab_s: basepeak = yes

Fortran benchmarks:

(Continued on next page)



SPEC CPU®2017 Floating Point Speed Result

Copyright 2017-2023 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

ProLiant DL325 Gen11

(3.60 GHz, AMD EPYC 9474F)

SPECspeed®2017_fp_base =

SPECspeed®2017_fp_peak =

CPU2017 License: 3

Test Sponsor: HPE

Tested by: HPE

Test Date: Dec-2022

Hardware Availability: Dec-2022

Software Availability: Nov-2022

SPEC has determined that this result does not comply with the SPEC CPU 2017 rules and reporting rules. Specifically, the test sponsor notified SPEC that the results were measured on an unsupported configuration.

Peak Optimization Flags (Continued)

603.bwaves_s: -m64 -Wl,-mllvm -Wl,-align-all-nofallthru-blocks=6
-Wl,-mllvm -Wl,-reduce-array-computations=3
-Wl,-mllvm -Wl,-enable-X86-prefetching -DSPEC_OPENMP
-Ofast -march=znver4 -fveclib=AMDLIBM -fstrict-aliasing
-fopenmp -Mrecursive -mllvm -reduce-array-computations=3
-fvector-transform -fscalar-transform -fopenmp=libomp
-lomp -lamdlibm -lamdalloc -lflang

649.fotonik3d_s: basepeak = yes

654.roms_s: Same as 603.bwaves_s

Benchmarks using both Fortran and C:

621.wrf_s: -m64 -Wl,-mllvm -Wl,-align-all-nofallthru-blocks=6
-Wl,-mllvm -Wl,-reduce-array-computations=3
-Wl,-mllvm -Wl,-enable-X86-prefetching -Ofast
-march=znver4 -fveclib=AMDLIBM -ffast-math -fopenmp
-flto -fstruct-layout=9 -mllvm -unroll-threshold=50
-fremap-arrays -fstrip-mining
-mllvm -inline-threshold=1000
-mllvm -reduce-array-computations=3 -DSPEC_OPENMP -zopt
-O3 -Mrecursive -fno-roll-loops -mllvm -lsr-in-nested-loop
-fopenmp=libomp -lomp -lamdlibm -lamdalloc -lflang

peak = yes

628.pop2_s: -m64 -Wl,-mllvm -Wl,-align-all-nofallthru-blocks=6
-Wl,-mllvm -Wl,-reduce-array-computations=3
-Wl,-mllvm -Wl,-enable-X86-prefetching -Ofast
-march=znver4 -fveclib=AMDLIBM -ffast-math -fopenmp
-flto -fstruct-layout=9 -mllvm -unroll-threshold=50
-fremap-arrays -fstrip-mining
-mllvm -inline-threshold=1000
-mllvm -reduce-array-computations=3 -DSPEC_OPENMP -zopt
-Mrecursive -fvector-transform -fscalar-transform
-fopenmp=libomp -lomp -lamdlibm -lamdalloc -lflang

(Continued on next page)



SPEC CPU®2017 Floating Point Speed Result

Copyright 2017-2023 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

ProLiant DL325 Gen11

(3.60 GHz, AMD EPYC 9474F)

SPECspeed®2017_fp_base =

SPECspeed®2017_fp_peak =

CPU2017 License: 3

Test Sponsor: HPE

Tested by: HPE

Test Date: Dec-2022

Hardware Availability: Dec-2022

Software Availability: Nov-2022

SPEC has determined that this result does not comply with the SPEC CPU 2017 rules and reporting rules. Specifically, the test sponsor notified SPEC that the results were measured on an unsupported configuration.

Peak Optimization Flags (Continued)

Benchmarks using Fortran, C, and C++:

607.cactuBSSN_s: basepeak = yes

Peak Other Flags

C benchmarks:

-Wno-return-type -Wno-unused-command-line-argument

Fortran benchmarks:

-Wno-unused-command-line-argument

Benchmarks using both Fortran and C:

-Wno-return-type -Wno-unused-command-line-argument

Benchmarks using Fortran, C, and C++:

-Wno-return-type -Wno-unused-command-line-argument

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2017/flags/HPE-Platform-Flags-AMD-Genoa-rev2.1.html>

<http://www.spec.org/cpu2017/flags/aocc400-flags.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2017/flags/HPE-Platform-Flags-AMD-Genoa-rev2.1.xml>

<http://www.spec.org/cpu2017/flags/aocc400-flags.xml>

SPEC CPU and SPECspeed are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester. For other inquiries, please contact info@spec.org.

Tested with SPEC CPU®2017 v1.1.8 on 2022-04-06 20:02:42-0400.

Report generated on 2023-09-12 17:55:43 by CPU2017 PDF formatter v6716.

Originally published on 2023-02-14.