



# SPEC CPU®2017 Floating Point Rate Result

Copyright 2017-2025 Standard Performance Evaluation Corporation

## Esconet Technologies Ltd.

Hexadata HDR-RM2386212I Ver: RLX  
(Intel Xeon E-2436)

SPECrate®2017\_fp\_base = 87.1

SPECrate®2017\_fp\_peak = 87.3

CPU2017 License: 6523


Test Sponsor: Esconet Technologies Ltd.

Tested by: Esconet Technologies Ltd.

Test Date: Feb-2025

Hardware Availability: May-2024

Software Availability: Jun-2024



### Hardware

CPU Name: Intel Xeon E-2436  
 Max MHz: 5000  
 Nominal: 2900  
 Enabled: 6 cores, 1 chip, 2 threads/core  
 Orderable: 1 chip  
 Cache L1: 32 KB I + 48 KB D on chip per core  
 L2: 2 MB I+D on chip per core  
 L3: 18 MB I+D on chip per chip  
 Other: None  
 Memory: 128 GB (4 x 32 GB 2Rx8 PC5-4800B-E, running at 4400)  
 Storage: 1 x 1920 GB SATA SSD  
 Other: CPU Cooling: Air

### Software

OS: SUSE Linux Enterprise Server 15 SP6  
 6.4.0-150600.21-default  
 Compiler: C/C++: Version 2023.2.3 of Intel oneAPI DPC++/C++  
 Compiler for Linux;  
 Fortran: Version 2023.2.3 of Intel Fortran  
 Compiler for Linux;  
 Parallel: No  
 Firmware: Version 1.19 released Jan-2024  
 File System: xfs  
 System State: Run level 3 (multi-user)  
 Base Pointers: 64-bit  
 Peak Pointers: 64-bit  
 Other: jemalloc memory allocator V5.0.1  
 Power Management: OS and BIOS set to prefer performance  
 at the cost of additional power usage.



# SPEC CPU®2017 Floating Point Rate Result

Copyright 2017-2025 Standard Performance Evaluation Corporation

## Esconet Technologies Ltd.

Hexadata HDR-RM2386212I Ver: RLX  
(Intel Xeon E-2436)

SPECrate®2017\_fp\_base = 87.1

SPECrate®2017\_fp\_peak = 87.3

CPU2017 License: 6523

Test Sponsor: Esconet Technologies Ltd.

Tested by: Esconet Technologies Ltd.

Test Date: Feb-2025

Hardware Availability: May-2024

Software Availability: Jun-2024

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
503.bwaves_r	12	325	370	330	365	<u>329</u>	<u>365</u>	12	325	370	330	365	<u>329</u>	<u>365</u>
507.cactuBSSN_r	12	<u>139</u>	<u>109</u>	139	109	140	109	12	139	109	140	109	<u>140</u>	<u>109</u>
508.namd_r	12	211	54.1	<u>211</u>	<u>54.1</u>	211	54.1	12	211	54.1	<u>211</u>	<u>54.1</u>	211	54.1
510.parest_r	12	695	45.2	698	45.0	<u>696</u>	<u>45.1</u>	12	705	44.5	694	45.3	<u>698</u>	<u>45.0</u>
511.povray_r	12	334	83.9	336	83.5	<u>335</u>	<u>83.7</u>	12	320	87.6	<u>321</u>	<u>87.4</u>	321	87.4
519.lbm_r	12	<u>260</u>	<u>48.6</u>	260	48.6	260	48.6	12	<u>260</u>	<u>48.6</u>	260	48.6	260	48.6
521.wrf_r	12	<u>379</u>	<u>70.9</u>	375	71.6	383	70.2	12	382	70.3	380	70.7	<u>381</u>	<u>70.6</u>
526.blender_r	12	<u>233</u>	<u>78.3</u>	233	78.3	232	78.7	12	<u>233</u>	<u>78.3</u>	233	78.3	232	78.7
527.cam4_r	12	213	98.7	213	98.5	<u>213</u>	<u>98.5</u>	12	<u>214</u>	<u>98.2</u>	213	98.5	215	97.6
538.imagick_r	12	128	233	129	231	<u>128</u>	<u>233</u>	12	128	233	129	231	<u>128</u>	<u>233</u>
544.nab_r	12	171	118	<u>170</u>	<u>119</u>	170	119	12	171	118	<u>170</u>	<u>119</u>	170	119
549.fotonik3d_r	12	<u>684</u>	<u>68.4</u>	684	68.4	684	68.3	12	<u>684</u>	<u>68.4</u>	684	68.4	684	68.3
554.roms_r	12	471	40.5	<u>470</u>	<u>40.5</u>	469	40.6	12	469	40.6	472	40.4	<u>470</u>	<u>40.6</u>

SPECrate®2017\_fp\_base = **87.1**

SPECrate®2017\_fp\_peak = **87.3**

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Submit Notes

The taskset mechanism was used to bind copies to processors. The config file option 'submit' was used to generate taskset commands to bind each copy to a specific processor. For details, please see the config file.

## Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"  
OS set to performance mode via cpupower frequency-set -g performance

## Environment Variables Notes

Environment variables set by runcpu before the start of the run:  
LD\_LIBRARY\_PATH = "/home/cpul7/lib/intel64:/home/cpul7/je5.0.1-64"  
MALLOC\_CONF = "retain:true"

## General Notes

Binaries compiled on a system with 2x Intel Xeon Platinum 8280M CPU + 384GB RAM memory using Red Hat Enterprise Linux 8.4  
Transparent Huge Pages enabled by default  
Prior to runcpu invocation  
Filesystem page cache synced and cleared with:  
sync; echo 3> /proc/sys/vm/drop\_caches  
jemalloc, a general purpose malloc implementation  
built with the RedHat Enterprise 7.5, and the system compiler gcc 4.8.5  
sources available from jemalloc.net or https://github.com/jemalloc/jemalloc/releases  
NA: The test sponsor attests, as of date of publication, that CVE-2017-5754 (Meltdown)

(Continued on next page)



# SPEC CPU®2017 Floating Point Rate Result

Copyright 2017-2025 Standard Performance Evaluation Corporation

## Esconet Technologies Ltd.

Hexadata HDR-RM2386212I Ver: RLX  
(Intel Xeon E-2436)

SPECrate®2017\_fp\_base = 87.1

SPECrate®2017\_fp\_peak = 87.3

**CPU2017 License:** 6523

**Test Sponsor:** Esconet Technologies Ltd.

**Tested by:** Esconet Technologies Ltd.

**Test Date:** Feb-2025

**Hardware Availability:** May-2024

**Software Availability:** Jun-2024

### General Notes (Continued)

is mitigated in the system as tested and documented.  
Yes: The test sponsor attests, as of date of publication, that CVE-2017-5753 (Spectre variant 1) is mitigated in the system as tested and documented.  
Yes: The test sponsor attests, as of date of publication, that CVE-2017-5715 (Spectre variant 2) is mitigated in the system as tested and documented.

### Platform Notes

BIOS Configuration:  
VT-d = Disabled  
CPU C States Support = Disabled  
AES = Disabled  
Intel (VMX) Virtualization Technology = Disabled  
DRAM frequency = DDR5-4400 (4400MHz)  
SATA Controller ALPM = Disabled

Sysinfo program /home/cpu17/bin/sysinfo  
Rev: r6732 of 2022-11-07 fe91c89b7ed5c36ae2c92cc097bec197  
running on localhost Mon Feb 24 03:58:26 2025

SUT (System Under Test) info as seen by some common utilities.

-----  
Table of contents  
-----

- 1. uname -a
- 2. w
- 3. Username
- 4. ulimit -a
- 5. sysinfo process ancestry
- 6. /proc/cpuinfo
- 7. lscpu
- 8. numactl --hardware
- 9. /proc/meminfo
- 10. who -r
- 11. Systemd service manager version: systemd 254 (254.10+suse.84.ge8d77af424)
- 12. Services, from systemctl list-unit-files
- 13. Linux kernel boot-time arguments, from /proc/cmdline
- 14. cpupower frequency-info
- 15. sysctl
- 16. /sys/kernel/mm/transparent\_hugepage
- 17. /sys/kernel/mm/transparent\_hugepage/khugepaged
- 18. OS release
- 19. Disk information
- 20. /sys/devices/virtual/dmi/id
- 21. dmidecode
- 22. BIOS

-----  
1. uname -a  
Linux localhost 6.4.0-150600.21-default #1 SMP PREEMPT\_DYNAMIC Thu May 16 11:09:22 UTC 2024 (36c1e09)  
x86\_64 x86\_64 x86\_64 GNU/Linux

-----  
2. w  
03:58:26 up 5:14, 1 user, load average: 9.77, 11.51, 11.84  
USER TTY FROM LOGIN@ IDLE JCPU PCPU WHAT  
root tty1 - 23:15 4:40m 0.84s 0.00s sh

(Continued on next page)



# SPEC CPU®2017 Floating Point Rate Result

Copyright 2017-2025 Standard Performance Evaluation Corporation

## Esconet Technologies Ltd.

Hexadata HDR-RM2386212I Ver: RLX  
(Intel Xeon E-2436)

SPECrate®2017\_fp\_base = 87.1

SPECrate®2017\_fp\_peak = 87.3

**CPU2017 License:** 6523

**Test Sponsor:** Esconet Technologies Ltd.

**Tested by:** Esconet Technologies Ltd.

**Test Date:** Feb-2025

**Hardware Availability:** May-2024

**Software Availability:** Jun-2024

### Platform Notes (Continued)

reportable-ic2023.2.3-lin-core-avx2-rate-smt-on-20231121.sh

-----  
3. Username

From environment variable \$USER: root

-----  
4. ulimit -a

```
core file size          (blocks, -c) unlimited
data seg size          (kbytes, -d) unlimited
scheduling priority    (-e) 0
file size              (blocks, -f) unlimited
pending signals        (-i) 512949
max locked memory      (kbytes, -l) 8192
max memory size        (kbytes, -m) unlimited
open files             (-n) 1024
pipe size              (512 bytes, -p) 8
POSIX message queues   (bytes, -q) 819200
real-time priority     (-r) 0
stack size             (kbytes, -s) unlimited
cpu time               (seconds, -t) unlimited
max user processes     (-u) 512949
virtual memory         (kbytes, -v) unlimited
file locks             (-x) unlimited
```

-----  
5. sysinfo process ancestry

```
/usr/lib/systemd/systemd --switched-root --system --deserialize=31
login -- root
-bash
sh reportable-ic2023.2.3-lin-core-avx2-rate-smt-on-20231121.sh
runcpu --nobuild --action validate --define default-platform-flags --define numcopies=12 -c
ic2023.2.3-lin-core-avx2-rate-20231121.cfg --define smt-on --define cores=6 --define physicallogical
--define no-numa --tune base,peak -o all --define drop_caches fprate
runcpu --nobuild --action validate --define default-platform-flags --define numcopies=12 --configfile
ic2023.2.3-lin-core-avx2-rate-20231121.cfg --define smt-on --define cores=6 --define physicallogical
--define no-numa --tune base,peak --output_format all --define drop_caches --nopower --runmode rate --tune
base:peak --size refrate fprate --nopreenv --note-preenv --logfile
$SPEC/tmp/CPU2017.002/templogs/preenv.fprate.002.0.log --lognum 002.0 --from_runcpu 2
specperl $SPEC/bin/sysinfo
$SPEC = /home/cpul7
```

-----  
6. /proc/cpuinfo

```
model name      : Intel(R) Xeon(R) E E-2436
vendor_id      : GenuineIntel
cpu family     : 6
model          : 183
stepping       : 1
microcode      : 0x122
bugs           : spectre_v1 spectre_v2 spec_store_bypass swapgs eibrs_pbrsb bhi
cpu cores      : 6
siblings       : 12
1 physical ids (chips)
12 processors (hardware threads)
physical id 0: core ids 0-5
physical id 0: apicids 0-11
```

Caution: /proc/cpuinfo data regarding chips, cores, and threads is not necessarily reliable, especially for virtualized systems. Use the above data carefully.

(Continued on next page)



# SPEC CPU®2017 Floating Point Rate Result

Copyright 2017-2025 Standard Performance Evaluation Corporation

## Esconet Technologies Ltd.

Hexadata HDR-RM2386212I Ver: RLX  
(Intel Xeon E-2436)

SPECrate®2017\_fp\_base = 87.1

SPECrate®2017\_fp\_peak = 87.3

**CPU2017 License:** 6523

**Test Sponsor:** Esconet Technologies Ltd.

**Tested by:** Esconet Technologies Ltd.

**Test Date:** Feb-2025

**Hardware Availability:** May-2024

**Software Availability:** Jun-2024

## Platform Notes (Continued)

### 7. lscpu

From lscpu from util-linux 2.39.3:

```

Architecture:                x86_64
CPU op-mode(s):              32-bit, 64-bit
Address sizes:               42 bits physical, 48 bits virtual
Byte Order:                  Little Endian
CPU(s):                      12
On-line CPU(s) list:        0-11
Vendor ID:                   GenuineIntel
BIOS Vendor ID:             Intel(R) Corporation
Model name:                  Intel(R) Xeon(R) E E-2436
BIOS Model name:            Intel(R) Xeon(R) E E-2436 To Be Filled By O.E.M. CPU @ 4.3GHz
BIOS CPU family:            179
CPU family:                  6
Model:                      183
Thread(s) per core:         2
Core(s) per socket:         6
Socket(s):                   1
Stepping:                    1
Frequency boost:             enabled
CPU(s) scaling MHz:         126%
CPU max MHz:                 2901.0000
CPU min MHz:                 800.0000
BogoMIPS:                   5836.80
Flags:                       fpu vme de pse tsc msr pae mce cx8 apic sep mtrr pge mca cmov pat
                             pse36 clflush dts acpi mmx fxsr sse sse2 ss ht tm pbe syscall nx
                             pdpe1gb rdtscp lm constant_tsc art arch_perfmon pebs bts rep_good
                             nopl xtopology nonstop_tsc cpuid aperfmperf tsc_known_freq pni
                             pclmulqdq dtes64 monitor ds_cpl smx est tm2 ssse3 sdbg fma cx16 xtpr
                             pdcm sse4_1 sse4_2 x2apic movbe popcnt tsc_deadline_timer xsave avx
                             f16c rdrand lahf_lm abm 3dnowprefetch cpuid_fault epb ssbd ibrs ibpb
                             stibp ibrs_enhanced fsgsbase tsc_adjust bmi1 avx2 smep bmi2 erms
                             invpcid rdseed adx smap clflushopt clwb intel_pt sha_ni xsaveopt
                             xsavec xgetbv1 xsaves split_lock_detect user_shstk avx_vnni dtherm
                             ida arat pln pts hfi umip pku ospke waitpkg gfni vpcmlmulqdq tme rdpid
                             movdiri movdir64b fsrm md_clear serialize pconfig arch_lbr ibt
                             flush_lld arch_capabilities
Lld cache:                   288 KiB (6 instances)
L1i cache:                   192 KiB (6 instances)
L2 cache:                    12 MiB (6 instances)
L3 cache:                    18 MiB (1 instance)
NUMA node(s):                1
NUMA node0 CPU(s):          0-11
Vulnerability Gather data sampling: Not affected
Vulnerability Itlb multihit:  Not affected
Vulnerability Lltf:          Not affected
Vulnerability Mds:           Not affected
Vulnerability Meltdown:      Not affected
Vulnerability Mmio stale data: Not affected
Vulnerability Reg file data sampling: Not affected
Vulnerability Retbleed:      Not affected
Vulnerability Spec rstack overflow: Not affected
Vulnerability Spec store bypass: Mitigation; Speculative Store Bypass disabled via prctl
Vulnerability Spectre v1:     Mitigation; usercopy/swapgs barriers and __user pointer sanitization
Vulnerability Spectre v2:     Mitigation; Enhanced / Automatic IBRS; IBPB conditional; RSB filling;
                             PBRSE-eIBRS SW sequence; BHI BHI_DIS_S
Vulnerability Srbds:         Not affected
Vulnerability Tsx async abort: Not affected

```

(Continued on next page)



# SPEC CPU®2017 Floating Point Rate Result

Copyright 2017-2025 Standard Performance Evaluation Corporation

## Esconet Technologies Ltd.

Hexadata HDR-RM2386212I Ver: RLX  
(Intel Xeon E-2436)

SPECrate®2017\_fp\_base = 87.1

SPECrate®2017\_fp\_peak = 87.3

**CPU2017 License:** 6523

**Test Sponsor:** Esconet Technologies Ltd.

**Tested by:** Esconet Technologies Ltd.

**Test Date:** Feb-2025

**Hardware Availability:** May-2024

**Software Availability:** Jun-2024

### Platform Notes (Continued)

From lscpu --cache:

NAME	ONE-SIZE	ALL-SIZE	WAYS	TYPE	LEVEL	SETS	PHY-LINE	COHERENCY-SIZE
L1d	48K	288K	12	Data	1	64	1	64
L1i	32K	192K	8	Instruction	1	64	1	64
L2	2M	12M	16	Unified	2	2048	1	64
L3	18M	18M	9	Unified	3	32768	1	64

8. numactl --hardware

NOTE: a numactl 'node' might or might not correspond to a physical chip.

```

available: 1 nodes (0)
node 0 cpus: 0-11
node 0 size: 128262 MB
node 0 free: 112824 MB
node distances:
node 0
0: 10

```

9. /proc/meminfo

MemTotal: 131340892 kB

10. who -r

run-level 3 Feb 23 22:44

11. Systemd service manager version: systemd 254 (254.10+suse.84.ge8d77af424)

```

Default Target Status
multi-user      running

```

12. Services, from systemctl list-unit-files

```

STATE UNIT FILES
enabled apparmor auditd cron firewalld getty@ irqbalance issue-generator kbdsettings kdump
kdump-early kdump-notify postfix purge-kernels rollback sshd systemd-pstore wicked
wickedd-auto4 wickedd-dhcp4 wickedd-dhcp6 wickedd-nanny
enabled-runtime systemd-remount-fs
disabled boot-sysctl ca-certificates chrony-wait chronyd console-getty debug-shell ebttables fsidd
grub2-once haveged issue-add-ssh-keys kexec-load lunmask nfs nfs-blkmap rpcbind
rpmconfigcheck serial-getty@ systemd-boot-check-no-failures systemd-confext
systemd-network-generator systemd-sysext systemd-time-wait-sync systemd-timesyncd
indirect systemd-userdbd wickedd

```

13. Linux kernel boot-time arguments, from /proc/cmdline

```

BOOT_IMAGE=/boot/vmlinuz-6.4.0-150600.21-default
root=UUID=0d9e72ce-443d-4279-9cbd-11b76fe0fa66
splash=silent
resume=/dev/disk/by-uuid/3a60289d-c070-402f-bb86-52386ad57a3d
mitigations=auto
quiet
security=apparmor
crashkernel=342M,high
crashkernel=72M,low

```

14. cpupower frequency-info

analyzing CPU 10:

(Continued on next page)



# SPEC CPU®2017 Floating Point Rate Result

Copyright 2017-2025 Standard Performance Evaluation Corporation

## Esconet Technologies Ltd.

Hexadata HDR-RM2386212I Ver: RLX  
(Intel Xeon E-2436)

SPECrate®2017\_fp\_base = 87.1

SPECrate®2017\_fp\_peak = 87.3

**CPU2017 License:** 6523

**Test Sponsor:** Esconet Technologies Ltd.

**Tested by:** Esconet Technologies Ltd.

**Test Date:** Feb-2025

**Hardware Availability:** May-2024

**Software Availability:** Jun-2024

### Platform Notes (Continued)

current policy: frequency should be within 800 MHz and 2.90 GHz.  
The governor "performance" may decide which speed to use within this range.

boost state support:

Supported: yes

Active: yes

```

-----
15. sysctl
kernel.numa_balancing          0
kernel.randomize_va_space     2
vm.compaction_proactiveness   20
vm.dirty_background_bytes     0
vm.dirty_background_ratio     10
vm.dirty_bytes                 0
vm.dirty_expire_centisecs     3000
vm.dirty_ratio                 20
vm.dirty_writeback_centisecs  500
vm.dirtytime_expire_seconds   43200
vm.extfrag_threshold          500
vm.min_unmapped_ratio         1
vm.nr_hugepages                0
vm.nr_hugepages_mempolicy     0
vm.nr_overcommit_hugepages    0
vm.swappiness                   60
vm.watermark_boost_factor     15000
vm.watermark_scale_factor     10
vm.zone_reclaim_mode          0
-----

```

```

-----
16. /sys/kernel/mm/transparent_hugepage
defrag          always defer+madvice [madvice] never
enabled         [always] madvice never
hpage_pmd_size 2097152
shmem_enabled   always within_size advise [never] deny force
-----

```

```

-----
17. /sys/kernel/mm/transparent_hugepage/khugepaged
alloc_sleep_millisecs  60000
defrag                  1
max_ptes_none           511
max_ptes_shared         256
max_ptes_swap           64
pages_to_scan           4096
scan_sleep_millisecs   10000
-----

```

```

-----
18. OS release
From /etc/*-release /etc/*-version
os-release SUSE Linux Enterprise Server 15 SP6
-----

```

```

-----
19. Disk information
SPEC is set to: /home/cpu17
Filesystem  Type  Size  Used Avail Use% Mounted on
/dev/sda3   xfs   728G  28G  700G  4% /home
-----

```

```

-----
20. /sys/devices/virtual/dmi/id
Vendor:      HEXADATA
-----

```

(Continued on next page)





# SPEC CPU®2017 Floating Point Rate Result

Copyright 2017-2025 Standard Performance Evaluation Corporation

## Esconet Technologies Ltd.

Hexadata HDR-RM2386212I Ver: RLX  
(Intel Xeon E-2436)

SPECrate®2017\_fp\_base = 87.1

SPECrate®2017\_fp\_peak = 87.3

**CPU2017 License:** 6523

**Test Sponsor:** Esconet Technologies Ltd.

**Tested by:** Esconet Technologies Ltd.

**Test Date:** Feb-2025

**Hardware Availability:** May-2024

**Software Availability:** Jun-2024

## Platform Notes (Continued)

Product: HDR-RM2386212I  
Serial: H5FSYR003208

### 21. dmidecode

Additional information from dmidecode 3.4 follows. **WARNING:** Use caution when you interpret this section. The 'dmidecode' program reads system data which is "intended to allow hardware to be accurately determined", but the intent may not be met, as there are frequent changes to hardware, firmware, and the "DMTF SMBIOS" standard.

#### Memory:

4x V-Color Technology Inc TE532G48D840 32 GB 2 rank 4800, configured at 4400

### 22. BIOS

(This section combines info from /sys/devices and dmidecode.)

BIOS Vendor: American Megatrends International, LLC.  
BIOS Version: 1.19  
BIOS Date: 01/05/2024  
BIOS Revision: 5.27

## Compiler Version Notes

=====  
C | 519.lbm\_r(base, peak) 538.imagick\_r(base, peak) 544.nab\_r(base, peak)  
=====

Intel(R) oneAPI DPC++/C++ Compiler for applications running on Intel(R) 64, Version 2023.2.3 Build x  
Copyright (C) 1985-2023 Intel Corporation. All rights reserved.

=====  
C++ | 508.namd\_r(base, peak) 510.parest\_r(base, peak)  
=====

Intel(R) oneAPI DPC++/C++ Compiler for applications running on Intel(R) 64, Version 2023.2.3 Build x  
Copyright (C) 1985-2023 Intel Corporation. All rights reserved.

=====  
C++, C | 511.povray\_r(base, peak) 526.blender\_r(base, peak)  
=====

Intel(R) oneAPI DPC++/C++ Compiler for applications running on Intel(R) 64, Version 2023.2.3 Build x  
Copyright (C) 1985-2023 Intel Corporation. All rights reserved.

Intel(R) oneAPI DPC++/C++ Compiler for applications running on Intel(R) 64, Version 2023.2.3 Build x  
Copyright (C) 1985-2023 Intel Corporation. All rights reserved.

=====  
C++, C, Fortran | 507.cactuBSSN\_r(base, peak)  
=====

Intel(R) oneAPI DPC++/C++ Compiler for applications running on Intel(R) 64, Version 2023.2.3 Build x  
Copyright (C) 1985-2023 Intel Corporation. All rights reserved.

Intel(R) oneAPI DPC++/C++ Compiler for applications running on Intel(R) 64, Version 2023.2.3 Build x  
Copyright (C) 1985-2023 Intel Corporation. All rights reserved.

Intel(R) Fortran Compiler for applications running on Intel(R) 64, Version 2023.2.3 Build x  
Copyright (C) 1985-2023 Intel Corporation. All rights reserved.

=====  
Fortran | 503.bwaves\_r(base, peak) 549.fotonik3d\_r(base, peak) 554.roms\_r(base, peak)  
=====

(Continued on next page)





# SPEC CPU®2017 Floating Point Rate Result

Copyright 2017-2025 Standard Performance Evaluation Corporation

**Esconet Technologies Ltd.**

Hexadata HDR-RM2386212I Ver: RLX  
(Intel Xeon E-2436)

SPECrate®2017\_fp\_base = 87.1

SPECrate®2017\_fp\_peak = 87.3

**CPU2017 License:** 6523

**Test Sponsor:** Esconet Technologies Ltd.

**Tested by:** Esconet Technologies Ltd.

**Test Date:** Feb-2025

**Hardware Availability:** May-2024

**Software Availability:** Jun-2024

## Compiler Version Notes (Continued)

-----  
Intel(R) Fortran Compiler for applications running on Intel(R) 64, Version 2023.2.3 Build x  
Copyright (C) 1985-2023 Intel Corporation. All rights reserved.  
-----

=====  
Fortran, C | 521.wrf\_r(base, peak) 527.cam4\_r(base, peak)  
-----

Intel(R) Fortran Compiler for applications running on Intel(R) 64, Version 2023.2.3 Build x  
Copyright (C) 1985-2023 Intel Corporation. All rights reserved.  
Intel(R) oneAPI DPC++/C++ Compiler for applications running on Intel(R) 64, Version 2023.2.3 Build x  
Copyright (C) 1985-2023 Intel Corporation. All rights reserved.  
-----

## Base Compiler Invocation

C benchmarks:

icx

C++ benchmarks:

icpx

Fortran benchmarks:

ifx

Benchmarks using both Fortran and C:

ifx icx

Benchmarks using both C and C++:

icpx icx

Benchmarks using Fortran, C, and C++:

icpx icx ifx

## Base Portability Flags

503.bwaves\_r: -DSPEC\_LP64  
507.cactuBSSN\_r: -DSPEC\_LP64  
508.namd\_r: -DSPEC\_LP64  
510.parest\_r: -DSPEC\_LP64  
511.povray\_r: -DSPEC\_LP64  
519.lbm\_r: -DSPEC\_LP64  
521.wrf\_r: -DSPEC\_LP64 -DSPEC\_CASE\_FLAG -convert big\_endian  
526.blender\_r: -DSPEC\_LP64 -DSPEC\_LINUX -funsigned-char  
527.cam4\_r: -DSPEC\_LP64 -DSPEC\_CASE\_FLAG

(Continued on next page)



# SPEC CPU®2017 Floating Point Rate Result

Copyright 2017-2025 Standard Performance Evaluation Corporation

**Esconet Technologies Ltd.**

SPECrate®2017\_fp\_base = 87.1

Hexadata HDR-RM2386212I Ver: RLX  
(Intel Xeon E-2436)

SPECrate®2017\_fp\_peak = 87.3

**CPU2017 License:** 6523

**Test Date:** Feb-2025

**Test Sponsor:** Esconet Technologies Ltd.

**Hardware Availability:** May-2024

**Tested by:** Esconet Technologies Ltd.

**Software Availability:** Jun-2024

## Base Portability Flags (Continued)

538.imagick\_r: -DSPEC\_LP64  
544.nab\_r: -DSPEC\_LP64  
549.fotonik3d\_r: -DSPEC\_LP64  
554.roms\_r: -DSPEC\_LP64

## Base Optimization Flags

### C benchmarks:

```
-w -std=c11 -m64 -Wl,-z,muldefs -xCORE-AVX2 -Ofast -ffast-math
-flto -mfpmath=sse -funroll-loops -qopt-mem-layout-trans=4
-Wno-implicit-int -ljemalloc -L/usr/local/jemalloc64-5.0.1/lib
```

### C++ benchmarks:

```
-w -std=c++14 -m64 -Wl,-z,muldefs -xCORE-AVX2 -Ofast -ffast-math
-flto -mfpmath=sse -funroll-loops -qopt-mem-layout-trans=4 -ljemalloc
-L/usr/local/jemalloc64-5.0.1/lib
```

### Fortran benchmarks:

```
-w -m64 -Wl,-z,muldefs -xCORE-AVX2 -Ofast -ffast-math -flto
-mfpmath=sse -funroll-loops -qopt-mem-layout-trans=4
-nostandard-realloc-lhs -align array32byte -auto -ljemalloc
-L/usr/local/jemalloc64-5.0.1/lib
```

### Benchmarks using both Fortran and C:

```
-w -m64 -std=c11 -Wl,-z,muldefs -xCORE-AVX2 -Ofast -ffast-math
-flto -mfpmath=sse -funroll-loops -qopt-mem-layout-trans=4
-Wno-implicit-int -nostandard-realloc-lhs -align array32byte -auto
-ljemalloc -L/usr/local/jemalloc64-5.0.1/lib
```

### Benchmarks using both C and C++:

```
-w -std=c++14 -m64 -std=c11 -Wl,-z,muldefs -xCORE-AVX2 -Ofast
-ffast-math -flto -mfpmath=sse -funroll-loops
-qopt-mem-layout-trans=4 -Wno-implicit-int -ljemalloc
-L/usr/local/jemalloc64-5.0.1/lib
```

### Benchmarks using Fortran, C, and C++:

```
-w -std=c++14 -m64 -std=c11 -Wl,-z,muldefs -xCORE-AVX2 -Ofast
-ffast-math -flto -mfpmath=sse -funroll-loops
-qopt-mem-layout-trans=4 -Wno-implicit-int -nostandard-realloc-lhs
-align array32byte -auto -ljemalloc -L/usr/local/jemalloc64-5.0.1/lib
```



# SPEC CPU®2017 Floating Point Rate Result

Copyright 2017-2025 Standard Performance Evaluation Corporation

**Esconet Technologies Ltd.**

SPECrate®2017\_fp\_base = 87.1

Hexadata HDR-RM2386212I Ver: RLX  
(Intel Xeon E-2436)

SPECrate®2017\_fp\_peak = 87.3

**CPU2017 License:** 6523

**Test Sponsor:** Esconet Technologies Ltd.

**Tested by:** Esconet Technologies Ltd.

**Test Date:** Feb-2025

**Hardware Availability:** May-2024

**Software Availability:** Jun-2024

## Peak Compiler Invocation

C benchmarks:

icx

C++ benchmarks:

icpx

Fortran benchmarks:

ifx

Benchmarks using both Fortran and C:

ifx icx

Benchmarks using both C and C++:

icpx icx

Benchmarks using Fortran, C, and C++:

icpx icx ifx

## Peak Portability Flags

Same as Base Portability Flags

## Peak Optimization Flags

C benchmarks:

519.lbm\_r: basepeak = yes

538.imagick\_r: basepeak = yes

544.nab\_r: basepeak = yes

C++ benchmarks:

508.namd\_r: basepeak = yes

510.parest\_r: -w -std=c++14 -m64 -Wl,-z,muldefs -xCORE-AVX2 -Ofast  
-ffast-math -flto -mfpmath=sse -funroll-loops  
-qopt-mem-layout-trans=4 -ljemalloc  
-L/usr/local/jemalloc64-5.0.1/lib

(Continued on next page)



# SPEC CPU®2017 Floating Point Rate Result

Copyright 2017-2025 Standard Performance Evaluation Corporation

**Esconet Technologies Ltd.**

SPECrate®2017\_fp\_base = 87.1

Hexadata HDR-RM2386212I Ver: RLX  
(Intel Xeon E-2436)

SPECrate®2017\_fp\_peak = 87.3

**CPU2017 License:** 6523

**Test Date:** Feb-2025

**Test Sponsor:** Esconet Technologies Ltd.

**Hardware Availability:** May-2024

**Tested by:** Esconet Technologies Ltd.

**Software Availability:** Jun-2024

## Peak Optimization Flags (Continued)

Fortran benchmarks:

503.bwaves\_r: basepeak = yes

549.fotonik3d\_r: basepeak = yes

```
554.roms_r: -w -m64 -Wl,-z,muldefs -xCORE-AVX2 -Ofast -ffast-math
-flto -mfpmath=sse -funroll-loops
-qopt-mem-layout-trans=4 -nostandard-realloc-lhs
-align array32byte -auto -ljemalloc
-L/usr/local/jemalloc64-5.0.1/lib
```

Benchmarks using both Fortran and C:

```
-w -m64 -std=c11 -Wl,-z,muldefs -xCORE-AVX2 -Ofast -ffast-math
-flto -mfpmath=sse -funroll-loops -qopt-mem-layout-trans=4
-Wno-implicit-int -nostandard-realloc-lhs -align array32byte -auto
-ljemalloc -L/usr/local/jemalloc64-5.0.1/lib
```

Benchmarks using both C and C++:

```
511.povray_r: -w -std=c++14 -m64 -std=c11 -Wl,-z,muldefs
-fprofile-generate(pass 1)
-fprofile-use=default.profddata(pass 2) -xCORE-AVX2 -flto
-Ofast -ffast-math -mfpmath=sse -funroll-loops
-qopt-mem-layout-trans=4 -Wno-implicit-int -ljemalloc
-L/usr/local/jemalloc64-5.0.1/lib
```

526.blender\_r: basepeak = yes

Benchmarks using Fortran, C, and C++:

```
-w -std=c++14 -m64 -std=c11 -Wl,-z,muldefs -xCORE-AVX2 -Ofast
-ffast-math -flto -mfpmath=sse -funroll-loops
-qopt-mem-layout-trans=4 -Wno-implicit-int -nostandard-realloc-lhs
-align array32byte -auto -ljemalloc -L/usr/local/jemalloc64-5.0.1/lib
```

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2017/flags/Intel-ic2023p2-official-linux64.html>

<http://www.spec.org/cpu2017/flags/Hexadata-Platform-Flags-Intel-rev1.7.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2017/flags/Intel-ic2023p2-official-linux64.xml>

<http://www.spec.org/cpu2017/flags/Hexadata-Platform-Flags-Intel-rev1.7.xml>



# SPEC CPU®2017 Floating Point Rate Result

Copyright 2017-2025 Standard Performance Evaluation Corporation

## Esconet Technologies Ltd.

Hexadata HDR-RM2386212I Ver: RLX  
(Intel Xeon E-2436)

SPECrate®2017\_fp\_base = 87.1

SPECrate®2017\_fp\_peak = 87.3

**CPU2017 License:** 6523

**Test Sponsor:** Esconet Technologies Ltd.

**Tested by:** Esconet Technologies Ltd.

**Test Date:** Feb-2025

**Hardware Availability:** May-2024

**Software Availability:** Jun-2024

SPEC CPU and SPECrate are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester. For other inquiries, please contact [info@spec.org](mailto:info@spec.org).

Tested with SPEC CPU®2017 v1.1.9 on 2025-02-23 17:28:26-0500.

Report generated on 2025-04-02 11:41:07 by CPU2017 PDF formatter v6716.

Originally published on 2025-04-02.