



# SPEChpc™ 2021 Small Result

Copyright 2021-2023 Standard Performance Evaluation Corporation

## xFusion


SPEChpc 2021\_sml\_base = 0.9291

xFusion 2288H V7 (Intel Xeon Platinum 8490H)

SPEChpc 2021\_sml\_peak = Not Run

hpc2021 License: 6488  
Test Sponsor: xFusion  
Tested by: xFusion

Test Date: Jan-2023  
Hardware Availability: Jan-2023  
Software Availability: Nov-2022



## Results Table

Benchmark	Base								Peak									
	Model	Ranks	Thrds/Rnk	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Model	Ranks	Thrds/Rnk	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
605.lbm_s	MPI	120	1	<b>1675</b>	<b>0.925</b>	1658	0.935											
613.soma_s	MPI	120	1	<b>1217</b>	<b>1.31</b>	1217	1.31											
618.tealeaf_s	MPI	120	1	<b>4237</b>	<b>0.484</b>	4229	0.485											
619.cvlleaf_s	MPI	120	1	<b>3282</b>	<b>0.503</b>	3282	0.503											
621.miniswp_s	MPI	120	1	566	1.94	<b>567</b>	<b>1.94</b>											
628.pot3d_s	MPI	120	1	3602	0.465	<b>3604</b>	<b>0.465</b>											
632.sph_exa_s	MPI	120	1	<b>788</b>	<b>2.92</b>	787	2.92											
634.hpgmgfv_s	MPI	120	1	1823	0.535	<b>1828</b>	<b>0.533</b>											
635.weather_s	MPI	120	1	<b>2097</b>	<b>1.24</b>	2095	1.24											

SPEChpc 2021\_sml\_base = **0.9291**

SPEChpc 2021\_sml\_peak = **Not Run**

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.



# SPEChpc™ 2021 Small Result

Copyright 2021-2023 Standard Performance Evaluation Corporation

## xFusion

SPEChpc 2021\_sml\_base = 0.9291

xFusion 2288H V7 (Intel Xeon Platinum 8490H)

SPEChpc 2021\_sml\_peak = Not Run

**hpc2021 License:** 6488  
**Test Sponsor:** xFusion  
**Tested by:** xFusion

**Test Date:** Jan-2023  
**Hardware Availability:** Jan-2023  
**Software Availability:** Nov-2022

### Hardware Summary

Type of System: Homogenous Cluster  
Compute Node: xFusion 2288H V7  
Interconnect: N/A  
Compute Nodes Used: 1  
Total Chips: 2  
Total Cores: 120  
Total Threads: 120  
Total Memory: 1 TB  
Max. Peak Threads: --

### Software Summary

Compiler: Intel oneAPI Compiler 2022.2.1  
MPI Library: Intel MPI Library for Linux\* OS, Version 2022.2.1 Build 20221020  
Other MPI Info: N/A  
Other Software: N/A  
Base Parallel Model: MPI  
Base Ranks Run: 120  
Base Threads Run: 1  
Peak Parallel Models: Not Run  
Minimum Peak Ranks: --  
Maximum Peak Ranks: --  
Max. Peak Threads: --  
Min. Peak Threads: --

## Node Description: xFusion 2288H V7

### Hardware

Number of nodes: 1  
Uses of the node: Compute  
Vendor: xFusion  
Model: xFusion 2288H V7  
CPU Name: Intel Xeon Platinum 8490H  
CPU(s) orderable: 2 chips  
Chips enabled: 2  
Cores enabled: 120  
Cores per chip: 60  
Threads per core: 1  
CPU Characteristics: Turbo Boost Technology up to 3.5 GHz  
CPU MHz: 1900  
Primary Cache: 32 KB I + 48 KB D on chip per core  
Secondary Cache: 2 MB I+D on chip per core  
L3 Cache: 112.5 MB I+D on chip per chip  
Other Cache: None  
Memory: 1 TB (16 x 64 GB 2Rx4 PC5-4800B-R)  
Disk Subsystem: 1 x 7.68 TB NVMe SSD  
Other Hardware: None  
Accel Count: --  
Accel Model: --  
Accel Vendor: --  
Accel Type: --  
Accel Connection: --  
Accel ECC enabled: --  
Accel Description: --  
Adapter: N/A  
Number of Adapters: 0  
Slot Type: N/A  
Data Rate: N/A  
Ports Used: 0

### Software

Accelerator Driver: N/A  
Adapter: N/A  
Adapter Driver: N/A  
Adapter Firmware: N/A  
Operating System: CentOS Linux release 8.2.2004  
4.18.0-193.el8.x86\_644  
Local File System: xfs  
Shared File System: N/A  
System State: Multi-user, run level 3  
Other Software: N/A

(Continued on next page)



# SPEChpc™ 2021 Small Result

Copyright 2021-2023 Standard Performance Evaluation Corporation

## xFusion

SPEChpc 2021\_sml\_base = 0.9291

xFusion 2288H V7 (Intel Xeon Platinum 8490H)

SPEChpc 2021\_sml\_peak = Not Run

**hpc2021 License:** 6488  
**Test Sponsor:** xFusion  
**Tested by:** xFusion

**Test Date:** Jan-2023  
**Hardware Availability:** Jan-2023  
**Software Availability:** Nov-2022

## Node Description: xFusion 2288H V7

### Hardware (Continued)

Interconnect Type: N/A

## Interconnect Description: N/A

### Hardware

Vendor: N/A  
Model: N/A  
Switch Model: N/A  
Number of Switches: 0  
Number of Ports: 0  
Data Rate: N/A  
Firmware: N/A  
Topology: N/A  
Primary Use: N/A

### Software

: --

## Submit Notes

The config file option 'submit' was used.  
export LD\_PRELOAD="/usr/lib64/libhugetlbfs.so \$LD\_PRELOAD"  
export OMP\_PROC\_BIND=true  
mpirexec.hydra -bootstrap ssh --bind-to core -np \$ranks -genv OMP\_NUM\_THREADS=\$threads \$command

## General Notes

Submitted\_by: luxu <luxu@xfusion.com>  
Submitted: Thu Jan 26 12:25:09 EST 2023  
Submission: hpc2021-20230110-00158.sub

## Compiler Version Notes

=====  
CC 605.lbm\_s(base) 613.soma\_s(base) 618.tealeaf\_s(base) 621.miniswp\_s(base)  
634.hpgmgfv\_s(base)  
-----

Intel(R) oneAPI DPC++/C++ Compiler 2022.1.0 (2022.1.0.20220316)  
Target: x86\_64-unknown-linux-gnu  
Thread model: posix  
InstalledDir: /mnt/share/opt/intel/2022.2.0/compiler/latest/linux/bin-llvm  
-----  
=====

(Continued on next page)



# SPEChpc™ 2021 Small Result

Copyright 2021-2023 Standard Performance Evaluation Corporation

## xFusion

SPEChpc 2021\_sml\_base = 0.9291

xFusion 2288H V7 (Intel Xeon Platinum 8490H)

SPEChpc 2021\_sml\_peak = Not Run

**hpc2021 License:** 6488  
**Test Sponsor:** xFusion  
**Tested by:** xFusion

**Test Date:** Jan-2023  
**Hardware Availability:** Jan-2023  
**Software Availability:** Nov-2022

### Compiler Version Notes (Continued)

CXXC 632.sph\_exa\_s(base)

-----  
Intel(R) oneAPI DPC++/C++ Compiler 2022.1.0 (2022.1.0.20220316)  
Target: x86\_64-unknown-linux-gnu  
Thread model: posix  
InstalledDir: /mnt/share/opt/intel/2022.2.0/compiler/latest/linux/bin-llvm  
-----

=====  
FC 619.clvleaf\_s(base) 628.pot3d\_s(base) 635.weather\_s(base)  
-----

ifx (IFORT) 2022.1.0 20220316  
Copyright (C) 1985-2022 Intel Corporation. All rights reserved.  
-----

### Base Compiler Invocation

C benchmarks:  
mpiicc -cc=icx

C++ benchmarks:  
mpiicpc -cxx=icx

Fortran benchmarks:  
mpiifort -fc=ifx

### Base Portability Flags

605.lbm\_s: -lstdc++  
613.soma\_s: -lstdc++ -DSPEC\_NO\_VAR\_ARRAY\_REDUCE  
618.tealeaf\_s: -lstdc++  
619.clvleaf\_s: -lstdc++  
621.miniswp\_s: -lstdc++  
628.pot3d\_s: -lstdc++  
632.sph\_exa\_s: -lstdc++  
634.hpgmgfv\_s: -lstdc++  
635.weather\_s: -lstdc++



# SPEChpc™ 2021 Small Result

Copyright 2021-2023 Standard Performance Evaluation Corporation

## xFusion

SPEChpc 2021\_sml\_base = 0.9291

xFusion 2288H V7 (Intel Xeon Platinum 8490H)

SPEChpc 2021\_sml\_peak = Not Run

**hpc2021 License:** 6488  
**Test Sponsor:** xFusion  
**Tested by:** xFusion

**Test Date:** Jan-2023  
**Hardware Availability:** Jan-2023  
**Software Availability:** Nov-2022

## Base Optimization Flags

C benchmarks:

```
-Ofast -ipo -xCORE-AVX512 -mprefer-vector-width=512 -fiopenmp  
-ansi-alias
```

C++ benchmarks:

```
-Ofast -ipo -xCORE-AVX512 -mprefer-vector-width=512 -fiopenmp  
-ansi-alias
```

Fortran benchmarks:

```
-Ofast -ipo -xCORE-AVX512 -mprefer-vector-width=512 -fiopenmp  
-nostandard-realloc-lhs -align array64byte
```

## Base Other Flags

C benchmarks:

```
-Ispecmpitime
```

C++ benchmarks:

```
-Ispecmpitime
```

Fortran benchmarks:

```
619.clvleaf_s: -Ispecmpitime
```

The flags file that was used to format this result can be browsed at

<http://www.spec.org/hpc2021/flags/Intel-oneAPI-icx2021-official-linux64.2023-01-27.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/hpc2021/flags/Intel-oneAPI-icx2021-official-linux64.2023-01-27.xml>

SPEChpc is a trademark of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester. For other inquiries, please contact [info@spec.org](mailto:info@spec.org).

Tested with SPEChpc2021 v1.1.7 on 2023-01-09 21:14:34-0500.  
Report generated on 2023-01-27 19:55:17 by hpc2021 PDF formatter v1.0.3.  
Originally published on 2023-01-27.