



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

SGI
SGI 2200 2X 400MHz R12k

SPECfp2000 = 343
SPECfp_base2000 = 319

SPEC license #: 4 Tested by: SGI Test date: Apr-2000 Hardware Avail: Jun-2000 Software Avail: Apr-2000

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
168.wupwise	1600	572	280	480	333
171.swim	3100	1033	300	1037	299
172.mgrid	1800	778	231	758	237
173.applu	2100	885	237	824	255
177.mesa	1400	484	289	451	310
178.galgel	2900	293	989	257	1131
179.art	2600	261	995	241	1078
183.quake	1300	586	222	575	226
187.facerec	1900	462	411	459	414
188.amp	2200	589	373	585	376
189.lucas	2000	773	259	779	257
191.fma3d	2100	1096	192	938	224
200.sixtrack	1100	553	199	548	201
301.apsi	2600	1034	252	775	335

Hardware

CPU: R12000
CPU MHz: 400
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip
CPU(s) orderable: 2, 4, 6, 8
Parallel: No
Primary Cache: 32KBI + 32KBD on chip
Secondary Cache: 8MB(I+D) off chip
L3 Cache: N/A
Other Cache: N/A
Memory: 2048MB
Disk Subsystem: 3 x 18 GB SCSI (striped)
Other Hardware: None

Software

Operating System: IRIX 6.5.8f
Compiler: MIPSpro 7.3.1.1m C, C++, Fortran90
SCSL 1.2 Math Library
File System: xfs
System State: Single-user

Notes/Tuning Information

Baseline optimization flags (for C benchmarks):

PASS1 : -Ofast=ip27 -IPA:use_intrinsic -fb_create /tmp/SPEC2000/FBDIR_base/\$(EXEBASE)

PASS2 : -Ofast=ip27 -IPA:use_intrinsic -fb_opt /tmp/SPEC2000/FBDIR_base/\$(EXEBASE)

Baseline optimization flags (for Fortran benchmarks): -Ofast=ip27 -LNO:fusion=2

Portability Flags:

178.galgel: -fixedform

Peak optimization flags:

note: all occurrences of (FEEDBACK) below means compiled with a two-step process:

PASS1 = -fb_create /tmp/SPEC2000/FBDIR_peak/\$(EXEBASE)

PASS2 = -fb_opt /tmp/SPEC2000/FBDIR_peak/\$(EXEBASE)

168.wupwise: -Ofast=ip27 -IPA:space=1000:linear=on:plimit=10000:callee_limit=5000 -INLINE:aggressive=on
-OPT:Olimit=0 -LNO:fusion=2:prefetch Ahead=5

171.swim: -Ofast=ip27 -LNO:cs2=8m:fission=2:ou=2

172.mgrid: -Ofast=ip27 -LNO:cs2=8m:fission=2:ou=2

173.applu: -Ofast=ip27 -LNO:ou_max=5:ou_prod_max=10:prefetch=0:fusion=2

177.mesa: -Ofast=ip27 -OPT:goto=off -LNO:opt=0 (FEEDBACK)

178.galgel: -Ofast=ip27 -LNO:ou_max=7 -lscs (FEEDBACK)

Standard Performance Evaluation Corporation

info@spec.org

http://www.spec.org



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

SGI
SGI 2200 2X 400MHz R12k

SPECfp2000 = **343**
SPECfp_base2000 = **319**

SPEC license #: 4 | Tested by: SGI | Test date: Apr-2000 | Hardware Avail: Jun-2000 | Software Avail: Apr-2000

Notes/Tuning Information (Continued)

```

RM_SOURCES = lapak.f90
179.art: -Ofast=ip27 -bigp_off -LNO:prefetch=0 -IPA:min_hot=15 (FEEDBACK)
183.quake: -Ofast=ip27 -LNO:prefetch=0 -TENV:X=4 -CG:ld_latency=7 -IPA:space=500 (FEEDBACK)
187.facerec: -Ofast=ip27 -fb_opt /tmp/SPEC2000/FBDIR_peak/$(EXEBASE) -LNO:fusion=2 (FEEDBACK)
188.ammp: -Ofast=ip27 -OPT:goto=off -IPA:space=500:plimit=900 (FEEDBACK)
189.lucas: -Ofast=ip27 -LNO:fusion=2:blocking=off -CG:ld_latency=4 -IPA:min_hot=8 (FEEDBACK)
191.fma3d: -Ofast=ip27 -bigp_off -LNO:prefetch=0 -OPT:goto=off:unroll_size=160:unroll_times_max=4
        -CG:ld_latency=2 (FEEDBACK)
200.sixtrack:= -Ofast=ip27 -IPA:maxdepth=2 -LNO:prefetch=0 (FEEDBACK)
301.apsi: -Ofast=ip27 -TENV:X=4 -LNO:prefetch=0:blocking=off -IPA:linear=on:use_intrinsic
The following O/S parameters were set:
setenv PAGESIZE_DATA 4096
setenv PAGESIZE_TEXT 4096
setenv PAGESIZE_STACK 4096
system -i ; percent_totalmem_4m_pages = 50 ; nlpages_4m = 128
limit stacksize 500000
The following is done before building each benchmark that requires (FEEDBACK):
rm -rf /tmp/SPEC2000/FBDIR_peak/$baseexe ; mkdir -p /tmp/SPEC2000/FBDIR_peak/$baseexe
or
rm -rf /tmp/SPEC2000/FBDIR_base/$baseexe ; mkdir -p /tmp/SPEC2000/FBDIR_base/$baseexe

```