



# CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Compaq Computer Corporation  
AlphaServer GS320 Model 6/731

SPECfp2000 = 444

SPECfp\_base2000 = 405

SPEC license #: 2 Tested by: Compaq NH Test date: Apr-2000 Hardware Avail: Jun-2000 Software Avail: Jul-2000

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
168.wupwise	1600	399	401	355	451
171.swim	3100	390	795	395	785
172.mgrid	1800	461	391	439	410
173.applu	2100	746	281	610	344
177.mesa	1400	258	542	244	574
178.galgel	2900	705	412	434	668
179.art	2600	214	1217	178	1461
183.quake	1300	896	145	901	144
187.facerec	1900	379	501	365	521
188.amp	2200	759	290	659	334
189.lucas	2000	432	463	434	461
191.fma3d	2100	614	342	597	352
200.sixtrack	1100	381	289	380	290
301.apsi	2600	739	352	730	356

### Hardware

CPU: Alpha 21264A  
CPU MHz: 731  
FPU: Integrated  
CPU(s) enabled: 1 core, 1 chip, 1 core/chip  
CPU(s) orderable: Up to 32 by 4  
Parallel: No  
Primary Cache: 64KB(I)+64KB(D) on chip  
Secondary Cache: 4MB off chip per CPU  
L3 Cache: None  
Other Cache: None  
Memory: 4GB  
Disk Subsystem: mfs (Memory File System)  
Other Hardware: Ethernet

### Software

Operating System: Tru64 Unix T5.1-9 (Release for GS160,GS320)  
Compiler: Compaq C T6.3-120-44A2I  
Compaq Fortran V5.3  
/usr/bin/f77: fort (not fort90)  
KAP Fortran V4.2  
KAP C 4.0  
File System: mfs  
System State: Multi-user

## Notes/Tuning Information

Baseline C: cc -arch ev6 -fast -O4 ONESTEP  
Fortran: kf90 -arch ev6 -O5 -fkapargs='-ur=-1' ONESTEP

Peak: -v -g3 -arch ev6 -non\_shared ONESTEP plus:  
168.wupwise: f77 -fast -O4 -pipeline -unroll 2  
171.swim: f90 -fast -O5 -transform\_loops  
172.mgrid: kf77 -O5 -transform\_loops -tune ev6 -unroll 8  
173.applu: f77 -fast -O5 -transform\_loops -unroll 14  
177.mesa: cc -fast -O4  
178.galgel: kf90 -O4 -unroll 2 -ldxml  
RM\_SOURCES = lapak.f90  
179.art: kcc -fast -O4 -ckapargs='-arl=4 -ur=4' -unroll 10  
183.quake: kcc -fast -ckapargs='-arl=4' -xtaso\_short  
187.facerec: f90 -fast -O4  
188.amp: cc -fast -O4 -xtaso\_short  
189.lucas: kf90 -fast -O5 -fkapargs='-ur=1' -unroll 1  
191.fma3d: kf90 -O4



# CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Compaq Computer Corporation  
AlphaServer GS320 Model 6/731

SPECfp2000 =	444
SPECfp_base2000 =	405

SPEC license #: 2 | Tested by: Compaq NH | Test date: Apr-2000 | Hardware Avail: Jun-2000 | Software Avail: Jul-2000

## Notes/Tuning Information (Continued)

```
200.sixtrack: f90 -fast -O5 -transform_loops
301.apsi: kf90 -O5 -transform_loops -unroll 8 -fkparg='-ur=1'
```

Portability: galgel: -fixed

Compaq C T6.3 is posted at <http://www.unix.digital.com/dtk/>  
It has been available as an ADK (Advanced Developers' Kit)  
since February, 2000; the final version will be posted  
in July, 2000.

The SPEC CPU2000 binaries were compiled under Unix V4.0F.

sysconfigtab settings:

```
max_proc_per_user = 4096
max_threads_per_user = 4096
per_proc_data_size = 21474836480
max_per_proc_data_size = 21474836480
per_proc_address_space = 21474836480
max_per_proc_address_space = 21474836480
```

Tru64 Unix V5.1 will ship in Jul-2000 for use on the GS160, GS320 platforms;  
the final version will ship Sep-2000.

Submitted\_by: henning@perfom.zko.dec.com

Submitted: Thu May 11 19:21:35 2000

Submission: cpu2000-20000511-00100.sub