



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Blade 1000 Model 1750

SPECint2000 = 393
SPECint_base2000 = 369

SPEC license #: 6 Tested by: Sun Microsystems, Palo Alto Test date: Mar-2001 Hardware Avail: Sep-2000 Software Avail: Mar-2001

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
164.gzip	1400	483	290	481	291	
175.vpr	1400	430	325	403	347	
176.gcc	1100	268	410	265	415	
181.mcf	1800	430	419	402	447	
186.crafty	1000	277	361	252	397	
197.parser	1800	523	344	482	373	
252.eon	1300	338	385	319	408	
253.perlbnk	1800	472	381	450	400	
254.gap	1100	421	261	413	266	
255.vortex	1900	386	493	322	591	
256.bzip2	1500	358	419	334	449	
300.twolf	3000	747	402	709	423	

Hardware

CPU: UltraSPARC-III
 CPU MHz: 750
 FPU: Integrated
 CPU(s) enabled: 1 core, 1 chip, 1 core/chip
 CPU(s) orderable: 1-2
 Parallel: None
 Primary Cache: 32KBI+64KBD on chip
 Secondary Cache: 8MB(I+D) off chip
 L3 Cache: None
 Other Cache: None
 Memory: 1GB
 Disk Subsystem: 1 x 18GB
 Other Hardware: --

Software

Operating System: Solaris 8 10/00
 Compiler: Forte Developer 6 update 1 w/ latest patches
 File System: UFS
 System State: Single User

Notes/Tuning Information

Portability:

176.gcc: -Dalloca=__builtin_alloca -DHOST_WORDS_BIG_ENDIAN
 186.crafty: -DSUN
 252.eon: -library=iostream
 253.perlbnk: -DSPEC_CPU2000_SOLARIS
 254.gap: -DSYS_IS_USG -DSYS_HAS_TIME_PROTO -DSYS_HAS_SIGNAL_PROTO
 -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_IOCTL_PROTO

Base C flags: -fast -xcrossfile -xprofile

Base C++ flags: -fast -xcrossfile -xprofile

Peak:

164.gzip: -fast -xalias_level=std -xcrossfile -W2,-whole -xprofile
 175.vpr: -fast -xalias_level=std -xcrossfile -xdepend -xregs=syst -W2,-whole -xprofile
 -lmopt
 176.gcc: -fast -xcrossfile -W2,-whole -Wc,-Qgsched-trace_late=1,-Qgsched-T4 -xprofile
 181.mcf: -fast -xcrossfile -xdepend -Wc,-Qgsched-trace_late=1,-Qgsched-T4 -xsafe=mem
 -xprofile
 186.crafty: -fast -xcrossfile -Wc,-Qgsched-trace_late=1,-Qgsched-T4
 -xalias_level=strong -xregs=syst -xchip=ultra2 -xprofile



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Blade 1000 Model 1750

SPECint2000 = 393
SPECint_base2000 = 369

SPEC license #: 6 | Tested by: Sun Microsystems, Palo Alto | Test date: Mar-2001 | Hardware Avail: Sep-2000 | Software Avail: Mar-2001

Notes/Tuning Information (Continued)

```

197.parser: -fast -xcrossfile -xdepend -xregs=syst -Wc,-Qgsched-trace_late=1,-Qgsched-T4
            -xalias_level=strong -xprofile
252.eon: -fast -xcrossfile -xsafe=mem -Qoption iropt -Mt500,-restrict_g,-restrict
         -Qoption cg -Qgsched-trace_late=1,-Qgsched-T4 -xprofile
253.perlbnk: -fast -Wc,-Qgsched-trace_late=1,-Qgsched-T4,-Qgsched-trace_spec_load=1
            -xcrossfile -xalias_level=std -xsafe=mem -xprofile
254.gap: -fast -xarch=v8 -W2,-crit,-whole -xcrossfile -Wc,-Qiselect-funcalign=32
         -xalias_level=std -xprofile
255.vortex: -fast -xsafe=mem -xcrossfile -W2,-Aheap,-reroll=1,-Aunroll,-Ms1,-Mt500,-Mr6000,-crit
            -Wc,-Qdepgraph-early_cross_call=1 -Wc,-Qiselect-funcalign=32 -Wc,-Qpeep-Sh0
            -xrestrict -xdepend -Wc,-Qgsched-trace_late=1,-Qgsched-T4 -xprofile
256.bzip2: -fast -xarch=v8 -W2,-Abopt -xcrossfile -xalias_level=strong
           -Wc,-Qiselect-funcalign=32 -xdepend -xregs=syst -xprofile
300.twolf: -fast -xalias_level=strong -W2,-whole -xsafe=mem -xprofile

```

Note: ONESTEP=yes for all benchmarks.

Forte Developer 6 update 1 patches include:
109503-02,109504-01,109505-08,109506-02,109508-04,109510-01,109513-06

Patch 111228-01 and obp 4.0.40 (or later) is required.

System configuration details located (as of June 2001) at
<http://www.sun.com/desktop/sunblade1000>