



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Blade 1000 Model 2750

SPECfp_rate2000 = 7.84

SPECfp_rate_base2000 = 7.02

SPEC license #: 6 Tested by: Sun Microsystems, Palo Alto Test date: Apr-2001 Hardware Avail: Sep-2000 Software Avail: Mar-2001

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	468	7.93	2	468	7.93
171.swim	2	1238	5.81	2	1220	5.90
172.mgrid	2	950	4.39	2	945	4.42
173.applu	2	1192	4.09	2	516	9.45
177.mesa	2	357	9.10	2	355	9.16
178.galgel	2	384	17.5	2	384	17.5
179.art	2	320	18.8	2	271	22.3
183.quake	2	754	4.00	2	719	4.20
187.facerec	2	352	12.5	2	342	12.9
188.amp	2	641	7.96	2	592	8.62
189.lucas	2	1180	3.93	4	1816	5.11
191.fma3d	2	869	5.61	4	1726	5.65
200.sixtrack	2	501	5.09	4	956	5.34
301.apsi	2	945	6.39	4	1805	6.68

Hardware

CPU: UltraSPARC-III
CPU MHz: 750
FPU: Integrated
CPU(s) enabled: 2 cores, 2 chips, 1 core/chip
CPU(s) orderable: 1-2
Parallel: None
Primary Cache: 32KBI+64KBD on chip
Secondary Cache: 8MB(I+D) off chip
L3 Cache: None
Other Cache: None
Memory: 1GB
Disk Subsystem: 1 x 18GB
Other Hardware: --

Software

Operating System: Solaris 8 10/00
Compiler: Forte Developer 6 update 1 w/ latest patches
File System: UFS
System State: Single User

Notes/Tuning Information

Portability:
178.galgel: -e -fixed

Base C flags: -fast -xcrossfile -xprofile -xalias_level=std
Base F90 flags: -fast -xcrossfile -xprofile

Peak:

168.wupwise: basepeak=yes
171.swim: -fast -xchip=ultra2
172.mgrid: f77 -fast -xregs=syst
173.applu: f77 -fast -Qoption iropt -Adata_access, -Mt6000, -Mm12000, -Mr40000, -Ma400, -whole -xregs=syst
177.mesa: -fast -xcrossfile -xalias_level=strong -xprofile
178.galgel: basepeak=yes
179.art: -fast -xalias_level=strong -xdepend -xregs=syst -xprofile -dn -lmopt
183.quake: -fast -xalias_level=strong -xdepend -xprofile -lmopt



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Blade 1000 Model 2750

SPECfp_rate2000 = 7.84
SPECfp_rate_base2000 = 7.02

SPEC license #: 6 | Tested by: Sun Microsystems, Palo Alto | Test date: Apr-2001 | Hardware Avail: Sep-2000 | Software Avail: Mar-2001

Notes/Tuning Information (Continued)

```
187.facerec: -fast -xcrossfile -stackvar -xprofile
188.ammf: -fast -xcrossfile -xalias_level=strong -xdepend -xregs=syst
        -W2,-whole -xprefetch -xprofile
189.lucas: -fast -qoption f90comp -array_pad_rows,1024 -Qoption iropt -whole -xprofile
191.fma3d: -fast -xcrossfile -stackvar -xprofile
200.sixtrack: -fast -xcrossfile -xprofile
301.apsi: -fast -qoption f90comp -expansion -xprofile
```

Note: ONESTEP=yes for all benchmarks.

Stack size set to unlimited by: ulimit -s unlimited

Forte Developer 6 update 1 patches include:

109503-07,109504-01,109505-08,109506-06,109508-01,109510-01,109513-06

Patch 111228-01 and obp 4.0.40 (or later) is required.

System configuration details located (as of June 2001) at
<http://www.sun.com/desktop/sunblade1000>