



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Dell
PowerEdge 6650 (2.0 GHz Xeon MP)

SPECint_rate2000 = 9.77
SPECint_rate_base2000 = 9.47

SPEC license #: 55 | Tested by: Dell, Round Rock, TX | Test date: Sep-2002 | Hardware Avail: Nov-2002 | Software Avail: Jun-2001

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	1	185	8.79	1	183	8.89
175.vpr	1	224	7.26	1	216	7.53
176.gcc	1	100	12.8	1	100	12.7
181.mcf	1	301	6.95	1	301	6.95
186.crafty	1	140	8.26	1	139	8.32
197.parser	1	231	9.02	1	230	9.09
252.eon	1	141	10.7	1	122	12.4
253.perlbnk	1	189	11.0	1	189	11.0
254.gap	1	152	8.37	1	151	8.45
255.vortex	1	170	13.0	1	145	15.2
256.bzip2	1	211	8.26	1	210	8.27
300.twolf	1	297	11.7	1	298	11.7

Hardware

CPU: Intel Xeon (400 MHz system bus)
CPU MHz: 2000
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip (Hyper-Threading Technology disabled)
CPU(s) orderable: 1, 2, 4
Parallel: No
Primary Cache: 12K(I) micro-ops + 8KB(D) on chip
Secondary Cache: 512KB(I+D) on chip
L3 Cache: 2048KB(I+D) on chip
Other Cache: None
Memory: 4 x 128MB DDR200
Disk Subsystem: 1 x 36GB SEAGATE ST336706LC
Other Hardware: None

Software

Operating System: Windows 2000 Advanced Server (SP2)
Compiler: Intel C++ Compiler 5.0.1 (020125Z)
Microsoft Visual C++ 6.0 (SP5)
MicroQuill SmartHeap Library 5.0
File System: NTFS
System State: Hyper-Threading Technology disabled in BIOS

Notes/Tuning Information

PORTABILITY FLAGS

176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

FEEDBACK-DIRECTED OPTIMIZATION

FDO: PASS1= -Qprof_gen PASS2= -Qprof_use

BASE TUNING

C: -Qipo +FDO -QxW shlW32M.lib
C++: -Qipo -QxW -GX -GR

PEAK TUNING

164.gzip: -Qipo +FDO -QxW -Oi- -Oa
175.vpr: -Qwp_ipo +FDO -QxW
176.gcc: -Qipo +FDO -QxW shlW32M.lib
181.mcf: -Qipo +FDO -QxW shlW32M.lib
186.crafty: -Qipo +FDO -QxW -Oa shlW32M.lib
197.parser: -Qipo +FDO -QxW
252.eon: -Qipo +FDO -QxW
253.perlbnk: -Qipo +FDO -QxW shlW32M.lib
254.gap: -Qipo +FDO -QaxW



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Dell
PowerEdge 6650 (2.0 GHz Xeon MP)

SPECint_rate2000 = 9.77

SPECint_rate_base2000 = 9.47

SPEC license #: 55 | Tested by: Dell, Round Rock, TX | Test date: Sep-2002 | Hardware Avail: Nov-2002 | Software Avail: Jun-2001

Notes/Tuning Information (Continued)

```
255.vortex: -Qwp_ipo +FDO -QxW -Oa
256.bzip2:  -Qipo +FDO -QxW shlw32M.lib
300.twolf:  -Qipo +FDO -QxW shlw32M.lib
EXTRA LIBRARIES
shlw32M.lib: MicroQuill SmartHeap Library 5.0
              www.microquill.com
```