



# CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

## IBM Corporation

IBM eServer pSeries 615 Model 6E3 (1200 MHz, 2 CPU)

SPECint\_rate2000 = 16.9

SPECint\_rate\_base2000 = 15.2

SPEC license #: 11 | Tested by: IBM, Austin, TX | Test date: May-2003 | Hardware Avail: Jun-2003 | Software Avail: May-2003

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	2	257	12.6	2	257	12.6
175.vpr	2	239	13.6	2	239	13.6
176.gcc	2	142	17.9	2	142	17.9
181.mcf	2	254	16.4	2	246	17.0
186.crafty	2	159	14.6	2	128	18.2
197.parser	2	578	7.23	2	280	14.9
252.eon	2	141	21.5	2	141	21.5
253.perlbnk	2	316	13.2	2	286	14.6
254.gap	2	170	15.1	2	157	16.2
255.vortex	2	178	24.8	2	176	25.1
256.bzip2	2	217	16.0	2	211	16.5
300.twolf	2	423	16.5	2	386	18.0

### Hardware

CPU: POWER4+  
 CPU MHz: 1200  
 FPU: Integrated  
 CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip, 1 processor chip/DCM  
 CPU(s) orderable: 1,2 (order by # cores)  
 Parallel: No  
 Primary Cache: 64KBI+32KBD (on chip) per core  
 Secondary Cache: 1536KB unified (on chip) per chip  
 L3 Cache: 8MB unified (off-chip) per DCM, 1 DCM in SUT  
 Other Cache: None  
 Memory: 4 GB  
 Disk Subsystem: 1x36GB SCSI, 10K RPM  
 Other Hardware: None

### Software

Operating System: AIX 5L V5.2  
 Compiler: IBM C for AIX, Version 6.0  
 IBM VisualAge C++ Professional for AIX, Version 6.0  
 File System: AIX/JFS  
 System State: Multi-User

## Notes/Tuning Information

### Integer Portability Flags:

```
176.gcc: -ma -DHOST_WORDS_BIG_ENDIAN
186.crafty: -DAIX
252.eon: srcalt=fmax_errno
        -I. -DNDEBUG
253.perlbnk: -DSPEC_CPU2000_AIX
254.gap: -DSYS_IS_BSD -DSYS_STRING_H -DSYS_HAS_TIME_PROTO
        -DSYS_HAS_MALLOC_PROTO -DSYS_HAS_CALLOC_PROTO
300.twolf: -DHAVE_SIGNED_CHAR
```

### Base Optimization Flags:

```
C:
-qpdf1/pdf2
-O5 -blpdata -qalign=natural
C++:
-qpdf1/pdf2
-O5 -lhuu -qalign=natural
```

### Integer Peak Optimization Flags

164.gzip



# CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

IBM Corporation

IBM eServer pSeries 615 Model 6E3 (1200 MHz, 2 CPU)

SPECint\_rate2000 = 16.9

SPECint\_rate\_base2000 = 15.2

SPEC license #: 11 | Tested by: IBM, Austin, TX | Test date: May-2003 | Hardware Avail: Jun-2003 | Software Avail: May-2003

## Notes/Tuning Information (Continued)

```

BASEPEAK = 1
"CC      = /usr/vac/bin/xlc"
175.vpr
BASEPEAK = 1
176.gcc
BASEPEAK = 1
181.mcf
fdpr -v -R3
-O5 -blpdata
186.crafty
-qpdf1/pdf2
fdpr -v -R3
-O3 -q64
197.parser
-O5 -blpdata -D_ILS_MACROS
252.eon
BASEPEAK = 1
253.perlbnk
-qpdf1/pdf2
-O5 -lhmu -qalign=natural
254.gap
-qpdf1/pdf2
-O5 -lhmu -qalign=natural
255.vortex
-qpdf1/pdf2
-O5 -lhmu -qalign=natural
256.bzip2
-qpdf1/pdf2
-O5 -blpdata -qarch=pwr3 -qtune=pwr3
300.twolf
-qpdf1/pdf2
-O5 -lhmu -qalign=natural -blpdata
"CC      = /usr/vac/bin/xlc"

```

Approved alternate-source file 252.eon.fmax\_errno.src.alt.tar.gz was used with 252.eon for POSIX-compatibility.

DCM: Acronym for "Dual-Chip Module"  
SUT: Acronym for "System Under Test"

IBM eServer pSeries 615 Model 6C3 (rack-mount server) and pSeries 615 Model 6E3 (deskside server) are electronically equivalent.

```

fpdr: Feedback directed program restructuring tool
/usr/spec2000 filesystem mounted with no JFS log file I/O.
APAR IY 43549 was applied to AIX to enable new hardware support.
ulimits set to unlimited.
C: IBM VAC++ invoked as cc except where noted as xlc
C++: IBM VAC++ invoked as xlc
Large page mode and memory affinity were set as follows:
vmo -r -o lpgg_regions=64 -o lpgg_size=16777216 -o memory_affinity=1
chuser capabilities=CAP_BYPASS_RAC_VMM,CAP_PROPAGATE $USER
shutdown -r
export MEMORY_AFFINITY=MCM

```