



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant DL580 G2(2.8GHz, Intel Xeon MP)

SPECfp2000 = 1094
SPECfp_base2000 = 1063

SPEC license #: 3 Test date: Sep-2003 Hardware Avail: Jul-2003 Software Avail: Jun-2003

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
168.wupwise	1600	129	1242	129	1236
171.swim	3100	248	1252	248	1252
172.mgrid	1800	191	941	191	941
173.applu	2100	258	815	256	819
177.mesa	1400	125	1121	125	1121
178.galgel	2900	131	2222	131	2218
179.art	2600	184	1417	152	1711
183.quake	1300	136	953	114	1140
187.facerec	1900	156	1220	154	1232
188.amp	2200	234	938	234	941
189.lucas	2000	179	1117	176	1135
191.fma3d	2100	234	899	234	899
200.sixtrack	1100	208	528	206	533
301.apsi	2600	269	968	269	968

Hardware

CPU: Intel Xeon MP (2.8GHz, 400MHz bus)
CPU MHz: 2800
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip (Hyper-Threading disabled)
CPU(s) orderable: 1,2,4
Parallel: No
Primary Cache: 12K micro-ops I + 8KBD on chip
Secondary Cache: 512KB(I+D) on chip
L3 Cache: 2048KB(I+D) on chip
Other Cache: N/A
Memory: 16x512MB PC1600
Disk Subsystem: 2x18.2GB 15K Ultra3 SCSI
Other Hardware:

Software

Operating System: Windows 2000 Advanced Server(Build 2195 SP3)
Compiler: Intel C++ Compiler 7.1 Build 20030801Z
Microsoft Visual Studio .NET 7.0.9466 (for libraries)
Intel Fortran Compiler 7.1 build 20030307Z
MicroQuill Smartheap Library 7.0
File System: NTFS
System State: Hyperthreading disabled in BIOS

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning: -QxW -Qipo -O3 +FDO ONESTEP=yes
Portability:
178.galgel: -FI /F32000000
Peak tuning:
168.wupwise: -Qipo -QxW +FDO ONESTEP=yes
171.swim: -Qipo -QxW -O3 +FDO ONESTEP=yes
172.mgrid: -Qipo -QaxW -O3 +FDO ONESTEP=yes
173.applu: -Qipo -QxW -O3 -Qscalar_rep- -Qauto +FDO ONESTEP=yes
177.mesa: -Qipo -QxW -O3 +FDO ONESTEP=yes
178.galgel: -Qipo -QxW -O3 +FDO ONESTEP=yes
179.art: -Qipo -Oa -Qunroll4 -Zp4 ONESTEP=yes
183.quake: -Qipo -QxW -Oa -Qrcd +FDO shlw32M.lib ONESTEP=yes
187.facerec: -Qipo -QaxW -O3 -Qunroll1 -Qscalar_rep- +FDO ONESTEP=yes
188.amp: -QxW -Oa ONESTEP=yes
189.lucas: -Qipo -QaxW
191.fma3d: basepeak=1
```



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant DL580 G2(2.8GHz, Intel Xeon MP)

SPECfp2000 = 1094
SPECfp_base2000 = 1063

SPEC license #: 3 | Test by: Hewlett-Packard Company, Houston TX | Test date: Sep-2003 | Hardware Avail: Jul-2003 | Software Avail: Jun-2003

Notes/Tuning Information (Continued)

200.sixtrack: -Qipo -QxW +FDO ONESTEP=yes
301.apsi: -Qipo -QxW -O3 +FDO ONESTEP=yes