



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Unisys Corporation

Unisys ES7000 ORION 540 (3.0GHz Xeon MP)

SPECint_rate2000 = 310

SPECint_rate_base2000 = 290

SPEC license #: 15 Tested by: Unisys Corporation Test date: Mar-2004 Hardware Avail: Apr-2004 Software Avail: Mar-2004

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	32	240	216	32	233	223
175.vpr	32	239	217	32	215	242
176.gcc	32	148	275	32	148	275
181.mcf	32	357	187	32	355	188
186.crafty	32	93.7	396	32	87.4	425
197.parser	32	167	401	32	156	429
252.eon	32	102	471	32	84.0	575
253.perlbnk	32	201	332	32	161	414
254.gap	32	375	109	32	374	109
255.vortex	32	213	330	32	196	360
256.bzip2	32	186	300	32	186	300
300.twolf	32	206	540	32	202	550

Hardware

CPU: Intel Xeon MP (400MHz system bus)
CPU MHz: 3000
FPU: Integrated
CPU(s) enabled: 32 cores, 32 chips, 1 core/chip(HT Technology disabled)
CPU(s) orderable: 16,20,24,28,32
Parallel: No
Primary Cache: 12K(I) micro-ops+8KBD on chip
Secondary Cache: 512KB(I+D) on chip
L3 Cache: 4096KB(I+D) on chip
Other Cache: 32MB L4 Cache off chip per 4 CPUs
Memory: 8GB
Disk Subsystem: 2X36GB SCSI RAID0 DISKs (15K rpm each)
Other Hardware:

Software

Operating System: MS Windows 2003 Datacenter Edition Build 3790
Compiler: Intel C++ Compiler 7.1 Build 20031229Z
Microsoft .NET Visual 7.0.9466 (for libraries)
SmartHeap Library Version 7.1
File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs : -Qxi -Qipo -Qfp_port
Base tuning for C++ programs: -QxW -Qipo -GX -GR
Portability flags:
176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
164.gzip: -QxW -Qipo -Oa -Oi- +FDO
175.vpr: -QxW -Qipo -O3 +FDO
176.gcc: basepeak=yes
181.mcf: -QxW -Qipo -O3 +FDO
186.crafty: -QxW -Qipo -Oa -O3 +FDO
197.parser: -QxW -Qipo -O3 +FDO
252.eon: -QxW -Qipo -O3 +FDO
253.perlbnk: -QxW -Qipo -O3 +FDO shlW32M.lib
254.gap: basepeak=yes
255.vortex: -QxW -Qipo -O3 +FDO
256.bzip2: basepeak=yes
```



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Unisys Corporation

Unisys ES7000 ORION 540 (3.0GHz Xeon MP)

SPECint_rate2000 = 310

SPECint_rate_base2000 = 290

SPEC license #: 15 | Tested by: Unisys Corporation | Test date: Mar-2004 | Hardware Avail: Apr-2004 | Software Avail: Mar-2004

Notes/Tuning Information (Continued)

300.twolf: -QxW -Qipo -O3 +FDO shlw32M.lib

Enabled two user settings in the BIOS :

1. "Adjacent Sector Prefetch"
2. "Prefetch Queue"

HT Technology disabled through Unisys Sentinel System Management Product