



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Unisys Corporation

Unisys ES7000 ORION 540 (3.0GHz Xeon MP)

SPECint_rate2000 = 171

SPECint_rate_base2000 = 159

SPEC license #: 15 Tested by: Unisys Corporation Test date: Mar-2004 Hardware Avail: Apr-2004 Software Avail: Mar-2004

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	16	189	137	16	186	140
175.vpr	16	232	112	16	206	126
176.gcc	16	109	187	16	109	187
181.mcf	16	347	96.3	16	341	98.0
186.crafty	16	93.6	198	16	86.7	214
197.parser	16	166	202	16	155	216
252.eon	16	102	236	16	83.8	288
253.perlbnk	16	184	181	16	149	225
254.gap	16	325	62.8	16	323	63.2
255.vortex	16	191	184	16	172	204
256.bzip2	16	157	178	16	157	178
300.twolf	16	205	271	16	201	276

Hardware

CPU: Intel Xeon MP (400MHz system bus)
CPU MHz: 3000
FPU: Integrated
CPU(s) enabled: 16 cores, 16 chips, 1 core/chip(HT Technology disabled)
CPU(s) orderable: 16,20,24,28,32
Parallel: No
Primary Cache: 12K(I) micro-ops+8KBD on chip
Secondary Cache: 512KB(I+D) on chip
L3 Cache: 4096KB(I+D) on chip
Other Cache: 32MB L4 Cache off chip per 4 CPUs
Memory: 4GB
Disk Subsystem: 2X36GB SCSI RAID0 DISKs (15K rpm each)
Other Hardware:

Software

Operating System: MS Windows 2003 Datacenter Edition Build 3790
Compiler: Intel C++ Compiler 7.1 Build 20031229Z
Microsoft .NET Visual 7.0.9466 (for libraries)
SmartHeap Library Version 7.1
File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs : -Qxi -Qipo -Qfp_port
Base tuning for C++ programs: -QxW -Qipo -GX -GR
Portability flags:
176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
164.gzip: -QxW -Qipo -Oa -Oi- +FDO
175.vpr: -QxW -Qipo -O3 +FDO
176.gcc: basepeak=yes
181.mcf: -QxW -Qipo -O3 +FDO
186.crafty: -QxW -Qipo -Oa -O3 +FDO
197.parser: -QxW -Qipo -O3 +FDO
252.eon: -QxW -Qipo -O3 +FDO
253.perlbnk: -QxW -Qipo -O3 +FDO shlW32M.lib
254.gap: basepeak=yes
255.vortex: -QxW -Qipo -O3 +FDO
256.bzip2: basepeak=yes
```



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Unisys Corporation
Unisys ES7000 ORION 540 (3.0GHz Xeon MP)

SPECint_rate2000 = 171
SPECint_rate_base2000 = 159

SPEC license #: 15 | Tested by: Unisys Corporation | Test date: Mar-2004 | Hardware Avail: Apr-2004 | Software Avail: Mar-2004

Notes/Tuning Information (Continued)

300.twolf: -QxW -Qipo -O3 +FDO shlw32M.lib

Enabled two user settings in the BIOS :

1. "Adjacent Sector Prefetch"
2. "Prefetch Queue"

HT Technology disabled through Unisys Sentinel System Management Product