



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
AlphaServer DS15/1000

SPECfp_rate2000 = 10.2

SPECfp_rate_base2000 = 7.91

SPEC license #: 2 | Tested by: HP | Test date: Jun-2004 | Hardware Avail: Jul-2004 | Software Avail: Jul-2004

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	1	251	7.39	1	118	15.8
171.swim	1	274	13.1	1	274	13.1
172.mgrid	1	381	5.48	1	277	7.54
173.applu	1	259	9.40	1	228	10.7
177.mesa	1	183	8.87	1	151	10.7
178.galgel	1	211	15.9	1	178	18.9
179.art	1	305	9.88	1	228	13.2
183.quake	1	399	3.78	1	156	9.65
187.facerec	1	264	8.36	1	236	9.32
188.amp	1	447	5.71	1	380	6.72
189.lucas	1	236	9.84	1	206	11.3
191.fma3d	1	343	7.11	1	296	8.22
200.sixtrack	1	289	4.42	1	257	4.96
301.apsi	1	312	9.68	1	297	10.2

Hardware

CPU: Alpha 21264C
 CPU MHz: 1000
 FPU: Integrated
 CPU(s) enabled: 1 core, 1 chip, 1 core/chip
 CPU(s) orderable: 1
 Parallel: No
 Primary Cache: 64KB(I)+64KB(D) on chip
 Secondary Cache: 2MB
 L3 Cache: None
 Other Cache: None
 Memory: 2GB; 512MB RIMMs
 Disk Subsystem: 36GB Ultra 160 10KRPM
 Other Hardware: None

Software

Operating System: Tru64 UNIX V5.1B (Rev. 2650)
 +IPK
 Compiler: Compaq C V6.5-011-48C5K
 Program Analysis Tools V2.0
 Spike V5.2 (510 USG)
 HP Fortran V5.5A-3548-48D88
 HP Fortran 77 V5.5A-3548-48D88
 KAP Fortran V4.3 000607
 KAP Fortran 77 V4.1 980926
 KAP C V4.1 000607
 File System: UFS
 System State: Multi-user

Notes/Tuning Information

Baseline C: cc -arch ev6 -fast -O4 ONESTEP
 Fortran: f90 -arch ev6 -fast -O5 ONESTEP

Peak:

All use -g3 -arch ev6 -non_shared ONESTEP
 except these (which use only the tunings shown below):
 173.applu 188.amp 191.fma3d
 Individual benchmark tuning:
 168.wupwise: kf77 -call_shared -inline all -tune ev67
 -unroll 12 -automatic -align commons -arch ev67
 -fkapargs=' -aggressive=c -fuse
 -fuselevel=1 -so=2 -r=1 -o=1 -interleave
 -ur=6 -ur2=060 ' +PFB
 171.swim: same as base
 172.mgrid: kf90 -call_shared -arch generic -O5 -inline
 manual -nopipeline -transform_loops -unroll 9 -automatic



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
AlphaServer DS15/1000

SPECfp_rate2000 = 10.2
SPECfp_rate_base2000 = 7.91

SPEC license #: 2 | Tested by: HP | Test date: Jun-2004 | Hardware Avail: Jul-2004 | Software Avail: Jul-2004

Notes/Tuning Information (Continued)

```

-fkparms='-aggressive=a -fuse -interleave
-ur=2 -ur3=5 -cachesize=128,16000 ' +PFB
173.applu: kf90 -O5 -transform_loops
-fkparms='-o=0 -nointerleave -ur=14
-ur2=260 -ur3=18' +PFB
177.mesa: kcc -fast -O4 +CFB +IFB
178.galgel: f90 -O5 -fast -unroll 5 -automatic
179.art: kcc -assume whole_program -ldensemalloc
-call_shared -assume restricted_pointers
-unroll 16 -inline none -ckparms='
-fuse -fuselevel=1 -ur=3' +PFB
183.equake: cc -call_shared -arch generic -fast -O4
-ldensemalloc -assume restricted_pointers
-inline speed -unroll 13 -xtaso_short +PFB
187.facerec: f90 -O4 -nopipeline -inline all
-non_shared -speculate all -unroll 7
-automatic -assume accuracy_sensitive
-math_library fast +IFB
188.ampp: cc -arch host -O4 -ifo -assume nomath_errno
-assume trusted_short_alignment -fp_reorder
-readonly_strings -ldensemalloc -xtaso_short
-assume restricted_pointers -unroll 9
-inline speed +CFB +IFB +PFB
189.lucas: kf90 -O5 -fkparms='-ur=1' +PFB
191.fma3d: kf90 -O4 -transform_loops -fkparms='-cachesize=128,16000 ' +PFB
200.sixtrack: f90 -fast -O5 -assume accuracy_sensitive
-notransform_loops +PFB
301.apsi: kf90 -O5 -inline none -call_shared -speculate all
-align commons -fkparms=' -aggressive=ab
-tune=ev5 -fuse -ur=1 -ur2=60 -ur3=20
-cachesize=128,16000'

```

Most benchmarks are built using one or more types of profile-driven feedback. The types used are designated by abbreviations in the notes:

+CFB: Code generation is optimized by the compiler, using feedback from a training run. These commands are done before the first compile (in phase "fdo_pre0"):

```

mkdir /tmp/pp
rm -f /tmp/pp/${baseexe}*

```

and these flags are added to the first and second compiles:

```

PASS1_CFLAGS = -prof_gen_noopt -prof_dir /tmp/pp
PASS2_CFLAGS = -prof_use_feedback -prof_dir /tmp/pp

```

(Peak builds use /tmp/pp above; base builds use /tmp/pb.)

+IFB: Icache usage is improved by the post-link-time optimizer Spike, using feedback from a training run. These commands are used (in phase "fdo_postN"):

```

mv ${baseexe} oldexe
spike oldexe -feedback oldexe -o ${baseexe}

```



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
AlphaServer DS15/1000

SPECfp_rate2000 = 10.2
SPECfp_rate_base2000 = 7.91

SPEC license #: 2 | Tested by: HP | Test date: Jun-2004 | Hardware Avail: Jul-2004 | Software Avail: Jul-2004

Notes/Tuning Information (Continued)

+PFB: Prefetches are improved by the post-link-time optimizer Spike, using feedback from a training run. These commands are used (in phase "fdo_post_makeN"):

```
rm -f *Counts*
mv ${baseexe} oldexe
pixie -stats dstride oldexe 1>pixie.out 2>pixie.err
mv oldexe.pixie ${baseexe}
```

A training run is carried out (in phase "fdo_runN"), and then this command (in phase "fdo_postN"):

```
spike oldexe -fb oldexe -stride_prefetch -o ${baseexe}
```

When Spike is used for both Icache and Prefetch improvements, only one spike command is actually issued, with the Icache options followed by the Prefetch options.

vm:

```
vm_bigpg_enabled = 1
vm_bigpg_thresh = 6
vm_swap_eager = 0
ubc_maxpercent = 50
```

proc:

```
max_per_proc_address_space = 34359738368
max_per_proc_data_size = 34359738368
max_per_proc_stack_size = 34359738368
max_proc_per_user = 2048
max_threads_per_user = 4096
maxusers = 2048
per_proc_address_space = 34359738368
per_proc_data_size = 34359738368
per_proc_stack_size = 34359738368
```

Portability: galgel: -fixed

Information on UNIX V5.1B Patches can be found at <http://ftpl.service.digital.com/public/unix/v5.1b/>

Processes were bound to CPUs using "runon".