



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Java Workstation W2100z

SPECint_rate2000 = 36.0
SPECint_rate_base2000 = 32.5

SPEC license #: 6 Tested by: Sun Microsystems, Santa Clara Test date: Jun-2004 Hardware Avail: Jul-2004 Software Avail: May-2004

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	2	96.9	33.5	2	96.5	33.6
175.vpr	2	130	25.0	2	120	27.1
176.gcc	2	68.1	37.5	2	68.1	37.5
181.mcf	2	278	15.0	2	174	24.0
186.crafty	2	48.0	48.3	2	48.0	48.3
197.parser	2	168	24.8	2	144	29.0
252.eon	2	75.8	39.8	2	61.4	49.1
253.perlbnk	2	111	37.6	2	104	40.2
254.gap	2	76.2	33.5	2	76.2	33.5
255.vortex	2	81.3	54.2	2	81.3	54.2
256.bzip2	2	113	30.7	2	113	30.7
300.twolf	2	239	29.2	2	189	36.9

Hardware

CPU: AMD Opteron (TM) 250
 CPU MHz: 2400
 FPU: Integrated
 CPU(s) enabled: 2 cores, 2 chips, 1 core/chip
 CPU(s) orderable: 2
 Parallel: No
 Primary Cache: 64KBI + 64KBD on chip
 Secondary Cache: 1024KB (I+D) on chip
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 8x1GB, PC3200 CL3 DDR SDRAM ECC Registered
 Disk Subsystem: SCSI, 73GB, 10K RPM
 Other Hardware: None

Software

Operating System: Red Hat Enterprise Linux WS 3 (AMD64)
 Compiler: PathScale EKO Compiler Suite, Release 1.1
 Red Hat gcc 3.5 ssa (from RHEL WS 3.0)
 File System: Linux/ext3
 System State: Multi-user, Run level 3

Notes/Tuning Information

Feedback-directed optimization is indicated by "+FDO", which means, unless otherwise noted:

```
PASS1: -fb_create fbdata
PASS2: -fb_opt fbdata
```

Compiler: pathcc (PathScale C) unless otherwise noted.

If other compilers are used, they are indicated as:

```
g++      Gnu C++
pathCC   PathScale C++
```

Integer base tuning:

```
C programs: pathcc -O3 -ipa +FDO
C++ programs: pathCC -Ofast +FDO
```

Peak Tuning:

```
164.gzip: -O3 -ipa -WOPT:val=0 -CG:p2align_freq=10000 +FDO
175.vpr: -O2 -ipa -OPT:alias=disjoint -LNO:prefetch Ahead=2
-CG:p2align_freq=500000 -INLINE:aggressive=on
-IPA:space=300:plimit=10000:callee_limit=5000:linear=on
```



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Java Workstation W2100z

SPECint_rate2000 = 36.0
SPECint_rate_base2000 = 32.5

SPEC license #: 6 | Tested by: Sun Microsystems, Santa Clara | Test date: Jun-2004 | Hardware Avail: Jul-2004 | Software Avail: May-2004

Notes/Tuning Information (Continued)

```

+FDO
176.gcc:      basepeak = true
181.mcf:      -O3 -static -OPT:Ofast -m32 +FDO
186.crafty:   basepeak = true
197.parser:   -O3 -ipa -m32 -IPA:ctype=on +FDO
252.eon:      g++ -O3 -msse2 -funroll-all-loops -ffast-math
              -finline-limit=5000
              Uses g++ style Feedback Directed Optimization:
                PASS1: -fprofile-arcs  PASS2: -fbranch-probabilities
              Previous feedback is removed prior to compiles, using:
                fdo_pre0 = rm -f *.da *.life analyz_prbprob.out
253.perlbnk:  -O3 -ipa -TENV:X=3 -IPA:min_hotness=5:plimit=20000 +FDO
254.gap:      basepeak=yes
255.vortex:   basepeak=yes
256.bzip2:    basepeak=yes
300.twolf:    -O2 -OPT:unroll_times=8:unroll_size=256:alias=disjoint:Ofast
              -CG:gcm=off:p2align_freq=100000 -TENV:X=4 +FDO -m32

```

Portability:

```

186.crafty:   -DLINUX_i386
252.eon:      -DHAS_ERRLIST -DSPEC_CPU2000_LP64 -lm
              srcalt = fmax_errno
253.perlbnk:  -DSPEC_CPU2000_LINUX_I386 -DSPEC_CPU2000_NEED_BOOL
              -DSPEC_CPU2000_GLIBC22 -DSPEC_CPU2000_LP64
254.gap:      -DSYS_IS_USG -DSYS_HAS_IOCTL_PROTO -DSYS_HAS_TIME_PROTO
              -DSYS_HAS_SIGNAL_PROTO -DSYS_HAS_ANSI -DSYS_HAS_CALLOC_PROTO
              -DSPEC_CPU2000_LP64
255.vortex:   -DSPEC_CPU2000_LP64

```

Notes:

BIOS build A5S1, default setting was used.