



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Advanced Micro Devices

Tyan Thunder K8QS Pro (S4882), AMD Opteron (TM) 850

SPECfp_rate2000 = 38.7

SPECfp_rate_base2000 = 35.2

SPEC license #: 49 | Tested by: AMD, Austin, TX | Test date: Aug-2004 | Hardware Avail: Jul-2004 | Software Avail: Aug-2004

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	94.5	39.3	2	79.9	46.5
171.swim	2	148	48.6	2	148	48.4
172.mgrid	2	123	34.0	2	113	36.9
173.applu	2	136	35.9	2	116	41.9
177.mesa	2	96.5	33.7	2	69.6	46.7
178.galgel	2	111	60.8	2	106	63.4
179.art	2	170	35.5	2	122	49.4
183.quake	2	97.8	30.8	2	103	29.3
187.facerec	2	106	41.7	2	98.3	44.9
188.amp	2	160	31.8	2	153	33.4
189.lucas	2	138	33.7	2	123	37.8
191.fma3d	2	150	32.4	2	145	33.6
200.sixtrack	2	151	16.9	2	150	17.0
301.apsi	2	171	35.4	2	169	35.6

Hardware

CPU: AMD Opteron (TM) 850
 CPU MHz: 2400
 FPU: Integrated
 CPU(s) enabled: 2 cores, 2 chips, 1 core/chip
 CPU(s) orderable: 4
 Parallel: No
 Primary Cache: 64KBI + 64KBD on chip
 Secondary Cache: 1024KB(I+D) on chip
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 8x512 MB PC3200 CL3.0 ECC Registered
 Disk Subsystem: SCSI, Seagate Cheetah ST336753LW
 Ultra 320, 15K rpm
 Other Hardware: None

Software

Operating System: SuSE Linux Enterprise Sever 8 for AMD64 (SP3)
 SuSE kernel 2.4.21-143-numa
 Compiler: PathScale EKO Compiler Suite, Release 1.3
 File System: Linux/ext3
 System State: Multi-user SuSE Run level 3

Notes/Tuning Information

Tested by Advanced Micro Devices

```
+FDO: PASS1= -fb_create fbdata PASS2= -fb_opt fbdata
+ACML is linking with AMD Core Math Library
```

Baseline optimization

```
C programs: -Ofast -WOPT:mem_opnds=on +FDO
Fortran programs: -Ofast -LNO:fusion=2
Portability Flags:
178.galgel: -fixedform
```

Peak Tuning:

```
168.wupwise: -Ofast -LNO:prefetch Ahead=5:prefetch=3
-OPT:unroll_times_max=8:unroll_size=128:IEEE_NaN_Inf=off:ro=3 -TENV:X=4
loader: -IPA:space=1000:linear=on:plimit=50000:callee_limit=5000
-INLINE:aggressive=on
```



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Advanced Micro Devices
Tyan Thunder K8QS Pro (S4882), AMD Opteron (TM) 850

SPECfp_rate2000 = 38.7
SPECfp_rate_base2000 = 35.2

SPEC license #: 49 | Tested by: AMD, Austin, TX | Test date: Aug-2004 | Hardware Avail: Jul-2004 | Software Avail: Aug-2004

Notes/Tuning Information (Continued)

```

171.swim: -Ofast -LNO:fusion=2:prefetch=2
172.mgrid: -O3 -LNO:fusion=2:blocking=off:prefetch=2
           -OPT:Ofast:unroll_times_max=8:unroll_size=256:ro=3
           -CG:gcm=off:cflow=off
173.applu: -Ofast -CG:local_fwd_sched=on
           -LNO:fusion=2:fission=2:full_unroll_size=10000:prefetch=3
           -OPT:ro=3 -TENV:X=3 -WOPT:val=2
177.mesa: -O2 -ipa -OPT:Ofast -fno-math-errno -CG:local_fwd_sched=on +FDO
178.galgel: -Ofast -OPT:fast_complex -CG:load_exe=0:use_movlpd=on +ACML
179.art: -O3 -OPT:ro=2:div_split=on:alias=typed -fno-math-errno -m32 +FDO
183.equake: -Ofast -WOPT:mem_opnds=on -CG:local_fwd_sched=on
187.facerec: -Ofast -OPT:treeheight=on:IEEE_NaN_Inf=off:ro=3 -CG:load_exe=0
            -LNO:fusion=2:prefetch=0 +FDO -IPA:plimit=1800
188.amp: -O3 -OPT:alias=disjoint:unroll_times_max=8:Ofast:ro=3 -LNO:prefetch=0 -fno-math-errno -TENV:X=4 +FDO
189.lucas: -Ofast -CG:prefetch=off:load_exe=2:local_fwd_sched
           -TENV:X=4 -WOPT:retype_expr=on +FDO
191.fma3d: -O2 -ipa -WOPT:mem_opnds=on:retype_expr=on -OPT:Ofast:IEEE_arith=3:ro=3
           +FDO -IPA:pu_reorder=1
200.sixtrack:= -Ofast +FDO
301.apsi: -Ofast -TENV:X=4 -LNO:fusion=2:prefetch=0
BIOS rev. 1.00

```

Taskset utility used to bind process to cpu(s)

All memory slots populated on CPU0 and CPU1

The tested system can be assembled using an SSI MEB footprint case, such as the CCSI RC0352 3U rackmount case, and a Tyan recommended 650W EPS-12V power supply, such as the Enermax 660W power supply (PEG851AX-VH)