



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire V490(4 processor)

SPECint_rate2000 = 65.2
SPECint_rate_base2000 = 59.0

SPEC license #: 6 Tested by: Sun Microsystems Test date: Dec-2004 Hardware Avail: Feb-2005 Software Avail: Jan-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.zip	8	281	46.2	8	244	53.3
175.vpr	8	240	54.0	8	239	54.4
176.gcc	8	165	62.0	8	154	66.2
181.mcf	8	311	53.7	8	255	65.4
186.crafty	8	152	61.2	8	119	78.0
197.parser	8	306	54.6	8	271	61.7
252.eon	8	177	68.2	8	171	70.7
253.perlbnk	8	285	58.6	8	249	67.0
254.gap	8	255	40.0	8	223	45.8
255.vortex	8	169	104	8	163	108
256.bzip2	8	211	66.0	8	203	68.5
300.twolf	8	476	58.4	8	459	60.7

Hardware

CPU: UltraSPARC IV
 CPU MHz: 1350
 FPU: Integrated
 CPU(s) enabled: 8 cores, 4 chips, 2 cores/chips
 CPU(s) orderable: 2,4 (order by # of chips)
 Parallel: No
 Primary Cache: 32KBI+64KBD per core on chip (64KBI+128KBD on chip)
 Secondary Cache: 8MB(I+D) per core off chip (16MB(I+D) off chip)
 L3 Cache: None
 Other Cache: None
 Memory: 32GB 8-way interleaved
 Disk Subsystem: 1 x 73GB
 Other Hardware: None

Software

Operating System: Solaris 10
 Compiler: Sun Studio 9
 File System: ufs
 System State: Multi-User

Notes/Tuning Information

Compiler invocation:

C: cc
CXX: CC

Integer base flags:

-fast -xipo=2 with ONESTEP=yes and feedback

Integer peak flags:

ONESTEP=yes and feedback for all benchmarks

164.zip: -xO4 -xbuiltin=%all -xtarget=native
 -xalias_level=std
 -xipo=2 -Wc,-Qeps:enabled=1,-Qeps:rp_filtering_margin=30,
 -Qeps:do_spec_load=1
 175.vpr: -fast -xalias_level=std -xipo=2
 -Wc,-Qeps:enabled=1,-Qeps:rp_filtering_margin=100,
 176.gcc: -fast -xipo=2 -l12amm
 181.mcf: -fast -xipo=2 -xprefetch_level=2 -Wc,-Qeps:enabled=1
 186.crafty: -fast -xinline= -xipo=2 -xalias_level=strong -W2,-Ashort_ldst
 Feedback adds -xlinkopt in PASS2



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire V490(4 processor)

SPECint_rate2000 = 65.2
SPECint_rate_base2000 = 59.0

SPEC license #: 6 | Tested by: Sun Microsystems | Test date: Dec-2004 | Hardware Avail: Feb-2005 | Software Avail: Jan-2005

Notes/Tuning Information (Continued)

```

197.parser: -fast -xipo=2 -xalias_level=strong
            -Wc,-Qgsched-T6,-Qipa:valueprediction
252.eon:    -fast -xipo=2 -noex
            -Qoption cg -Qeps:enabled=1,-Qeps:ws=32
253.perlbnk: -xO5 -xtarget=native -xmemalign=4s -xipo -Wc,-Qeps:enabled=1
            -Qeps:ws=8, -xalias_level=std -xsafe=mem -Wc,
            -Qiselect-funcalign=32
            -Qicache-chbab=1, -Wc,-Qiselect-sw_pf_tbl_th=20,
            -Qeps:do_spec_load=1 -xprefetch=no
254.gap:    -fast -xipo=2 -xalias_level=strong -xvector
            -xprefetch_level=3 -W2,-Abcopy
255.vortex: -fast -xrestrict -xipo=2
            -W2,-crit,-Ainline:recursion=1:cs=500:irs=6000
            -Wc,-Qeps:enabled=1,-Qdepgraph-early_cross_call=1,
            -Qiselect-funcalign=32,-Qpeep-Sh0 -ll2amm
256.bzip2:  -fast -xipo -xalias_level=strong -xrestrict
            -Wc,-Qeps:enabled=1 -xsafe=mem -Qeps:rp_filtering_margin=99
300.twolf:  -fast -xalias_level=strong -xsafe=mem -xipo=2
            -xprefetch=no%auto -Wc,-Qms_pipe+intdivusefp

```

Feedback is done as follows, unless otherwise noted:

```

fdo_pre0:  rm -rf ./feedback.profile ./SunWS_cache
PASS1:     -xprofile=collect:./feedback
PASS2:     -xprofile=use:./feedback

```

Portability:

```

176.gcc:   -Dalloca=__builtin_alloca -DHOST_WORDS_BIG_ENDIAN
186.crafty: -DSUN
252.eon:   -library=iostream
253.perlbnk: -DSPEC_CPU2000_SOLARIS
254.gap:   -DSYS_IS_USG -DSYS_HAS_TIME_PROTO -DSYS_HAS_SIGNAL_PROTO
            -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_IOCTL_PROTO

```

Shell Environments:

```

Stack size set to unlimited via "ulimit -s unlimited"
MPSSHEAP=512K
MPSSSTACK=512K
LD_PRELOAD=mpss.so.1

```

Kernel Parameters (/etc/system):

```

autoup=900
tune_t_fsflushr=1

```

Processes were bound to CPUs using submit=pbind