



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Limited
PRIMEPOWER900 (2160MHz)

SPECint2000 = 1594
SPECint_base2000 = 1456

SPEC license #: 19 | Tested by: Fujitsu Limited | Test date: Apr-2005 | Hardware Avail: Jun-2005 | Software Avail: Apr-2004

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
164.gzip	1400	129	1087	122	1143	
175.vpr	1400	105	1328	103	1359	
176.gcc	1100	102	1079	67.1	1639	
181.mcf	1800	115	1560	94.5	1905	
186.crafty	1000	70.3	1422	65.2	1535	
197.parser	1800	141	1276	130	1385	
252.eon	1300	78.6	1654	76.4	1703	
253.perlbnk	1800	117	1539	117	1544	
254.gap	1100	89.9	1223	86.2	1277	
255.vortex	1900	66.6	2854	64.7	2938	
256.bzip2	1500	105	1432	100	1493	
300.twolf	3000	186	1615	170	1767	

Hardware

CPU: SPARC64 V
CPU MHz: 2160
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip
CPU(s) orderable: 1 to 16 (increments of 1)
Parallel: None
Primary Cache: 128KBI + 128KBD on chip
Secondary Cache: 4MB(I+D) on chip
L3 Cache: None
Other Cache: None
Memory: 8192MB
Disk Subsystem: 1 x 36.4GB SCSI (10000rpm)
Other Hardware: None

Software

Operating System: Solaris 9 4/04
Compiler: (C/C++)
Fujitsu Parallelnavi 2.3 with patch 913287-01
Sun Studio 9
File System: ufs
System State: multi user

Notes/Tuning Information

```
FDO: (for Parallelnavi 2.3)
fdo_pre0=rm -rf `pwd`/*.f.d
PASS1=-Kpg
PASS2=-Kpu=$(EXEBASE).fbk
FDO: (for Sun Studio 9)
fdo_pre0=rm -rf ./feedback.profile ./SunWS_cache
PASS1=-xprofile=collect:./feedback
PASS2=-xprofile=use:./feedback
```

```
Integer base flags:
(using C compiler of Sun Studio 9)
-fast -xtarget=ultra3cu -xipo=2 ONESTEP=yes FDO
(using C++ compiler of Sun Studio 9)
-fast -xipo=2 ONESTEP=yes FDO
```

```
Integer peak flags:
(using C compiler of Parallelnavi 2.3)
300.twolf: -Kfast_GP2=3,GREG,eval,preex,cfunc -O3 ONESTEP=yes FDO
```



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Limited
PRIMEPOWER900 (2160MHz)

SPECint2000 = 1594
SPECint_base2000 = 1456

SPEC license #: 19 | Tested by: Fujitsu Limited | Test date: Apr-2005 | Hardware Avail: Jun-2005 | Software Avail: Apr-2004

Notes/Tuning Information (Continued)

(using C compiler of Sun Studio 9)

164.gzip: -xarch=v8plusb -xchip=ultra2 -xcache=128/64/2:4096/64/4
-xalias_level=std -xipo=2 -W2,-whole -xO5 ONESTEP=yes FDO

175.vpr: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:4096/64/4
-xalias_level=std -xchip=ultra2 -xipo=2 ONESTEP=yes FDO

176.gcc: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:4096/64/4
-xipo=2 -l12amm ONESTEP=yes FDO

181.mcf: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:4096/64/4
-xipo=2 -xprefetch_level=3 -W2,-Apf:l1list=3:noinnerl1list
ONESTEP=yes FDO

186.crafty: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:4096/64/4
-xalias_level=strong -xipo=2 -xpagesize=512K -W2,-Ashort_ldst
ONESTEP=yes FDO

197.parser: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:4096/64/4
-xalias_level=strong -xipo=2 -xregs=syst -Wc,-Qgsched-T6,
-Qgsched-trace_late=1,-Qipa:valueprediction ONESTEP=yes FDO

253.perlbnk: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:4096/64/4
-xipo=2 -xalias_level=std ONESTEP=yes FDO

254.gap: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:4096/64/4
-xalias_level=strong -xipo=2 -xprefetch_level=3 -xvector
-W2,-Abcopy ONESTEP=yes FDO

255.vortex: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:4096/64/4
-xipo=2 -xrestrict -W2,-crit,-Ainline:recursion=1:cs=500:irs=6000
-Wc,-Qdepgraph-early_cross_call=1 -l12amm ONESTEP=yes FDO

256.bzip2: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:4096/64/4
-xipo=2 -xalias_level=strong -xrestrict ONESTEP=yes FDO

(using C++ compiler of Sun Studio 9)

252.eon: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:4096/64/4
-noex -xalias_level=compatible -xipo=2 -xregs=syst
-Qoption cg -Qeps:enabled=1,-Qeps:ws=32 ONESTEP=yes FDO

Portability:

176.gcc: -Dalloca=__builtin_alloca -DHOST_WORDS_BIG_ENDIAN

186.crafty: -DSUN

252.eon: -library=iostream

253.perlbnk: -DSPEC_CPU2000_SOLARIS

254.gap: -DSYS_IS_USG -DSYS_HAS_TIME_PROTO -DSYS_HAS_SIGNAL_PROTO
-DSYS_HAS_CALLOC_PROTO -DSYS_HAS_IOCTL_PROTO

System Tunables:

(for /etc/system)

```
set consistent_coloring=1
set tune_t_fsflushr=86400
set autoup=86400
```

Shell Environments:

```
Stack size set to unlimited via "ulimit -s unlimited"
MPSSHEAP=4M
MPSSSTACK=4M
LD_PRELOAD=mpss.so.1
```

System board used with only ONE CPU present.

Small configuration memory system mode used ("4cpu mode", enabled via system console).



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Limited
PRIMEPOWER900 (2160MHz)

SPECint2000 =	1594
SPECint_base2000 =	1456

SPEC license #: 19 | Tested by: Fujitsu Limited | Test date: Apr-2005 | Hardware Avail: Jun-2005 | Software Avail: Apr-2004

Notes/Tuning Information (Continued)

Sun Studio 9, posted at URL <http://www.sun.com/software/products/studio/previous/9/index.xml> was used for this submission.