



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant BL45p (AMD Opteron (TM) 852)

SPECfp_rate2000 = 92.6
SPECfp_rate_base2000 = 83.5

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Apr-2005 Hardware Avail: May-2005 Software Avail: Apr-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	4	63.5	117	4	55.7	133
171.swim	4	129	111	4	129	111
172.mgrid	4	107	78.4	4	99.7	83.8
173.applu	4	110	88.6	4	97.5	99.9
177.mesa	4	83.8	77.5	4	65.3	99.4
178.galgel	4	95.4	141	4	85.3	158
179.art	4	118	102	4	80.7	150
183.equake	4	92.5	65.2	4	85.7	70.4
187.facerec	4	81.1	109	4	80.8	109
188.amp	4	153	66.8	4	142	71.7
189.lucas	4	99.5	93.2	4	99.9	92.9
191.fma3d	4	143	68.1	4	135	72.4
200.sixtrack	4	146	35.0	4	126	40.6
301.apsi	4	159	75.9	4	156	77.2

Hardware

CPU: AMD Opteron (TM) 852
CPU MHz: 2600
FPU: Integrated
CPU(s) enabled: 4 cores, 4 chips, 1 core/chip
CPU(s) orderable: 2,4
Parallel: No
Primary Cache: 64KBI + 64KBD on chip
Secondary Cache: 1024KB(I+D) on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 16x2048MB PC3200 CL3.0
Disk Subsystem: 1x36.4GB 15K Ultra320 SCSI
Other Hardware:

Software

Operating System: SuSE Linux Enterprise Server 9 (x86_64) SP 1
SuSE kernel 2.6.5-7.139-smp
Compiler: PathScale EKO Compiler Suite, Release 2.1
AMD Core Math Library 2.5.1
File System: Linux/ext2
System State: Multi-user run level 3

Notes/Tuning Information

+ACML: Linked with AMD Core Math Library
Base tuning for C programs: -Ofast -WOPT:mem_opnds=on +FDO
Base tuning for FORTRAN programs: -Ofast -LNO:fusion=2 -OPT:fast_complex
Portability flags:
178.galgel: -fixedform
Peak tuning:
168.wupwise: -Ofast -LNO:prefetch Ahead=5:prefetch=3
-OPT:unroll_times_max=8:unroll_size=128:IEEE_NaN_Inf=off:ro=3 -TENV:X=4
-IPA:space=1000:linear=on:plimit=50000:callee_limit=5000
-INLINE:aggressive=on +FDO
171.swim: -Ofast -LNO:fusion=2
172.mgrid: -O3 -LNO:fusion=2:blocking=off
-OPT:Ofast:unroll_times_max=8:unroll_size=256:ro=3 -CG:gcm=off:cflow=off
173.applu: -Ofast -CG:local_fwd_sched=on
-LNO:fusion=2:fission=2:full_unroll_size=10000:prefetch=3
-OPT:ro=3 -TENV:X=3 -WOPT:val=2
177.mesa: -O2 -ipa -OPT:Ofast -fno-math-errno -CG:local_fwd_sched=on +FDO



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant BL45p (AMD Opteron (TM) 852)

SPECfp_rate2000 = 92.6
SPECfp_rate_base2000 = 83.5

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: Apr-2005 | Hardware Avail: May-2005 | Software Avail: Apr-2005

Notes/Tuning Information (Continued)

```

178.galgel: -Ofast -OPT:fast_complex -CG:use_movlpd=on RM_SOURCES=lapak.f90 +ACML
179.art: -O3 -OPT:ro=2:div_split=on:alias=typed -fno-math-errno -m32 +FDO
183.quake: -Ofast -WOPT:mem_opnds=on -CG:local_fwd_sched=on -m32
187.facerec: -Ofast -OPT:treeheight=on:IEEE_NaN_Inf=off:ro=3 -CG:load_exe=0
-LNO:fusion=2 -IPA:plimit=1500 +FDO
188.ammp: -O3 -OPT:alias=disjoint:unroll_times_max=8:Ofast:ro=3
-fno-math-errno -TENV:X=4 -LNO:prefetch=0 +FDO
189.lucas: -Ofast -CG:local_fwd_sched=on -LNO:fusion=2 +FDO
191.fma3d: -O2 -ipa -CG:load_exe=1 -OPT:Ofast:IEEE_arith=3:ro=3
-WOPT:mem_opnds=on:retype_expr=on -IPA:pu_reorder=1 +FDO
200.sixtrack: -Ofast -CG:load_exe=1 +FDO
301.apsi: -Ofast -TENV:X=4 -LNO:fusion=2:prefetch=0
BIOS Configuration Notes
Node Interleaving is Disabled

```