



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers
PRIMERGY RX300 S2, 64-bit Intel Xeon processor 3.60 GHz

SPECfp_rate2000 = 32.3
SPECfp_rate_base2000 = 32.3

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: May-2005 | Hardware Avail: Mar-2005 | Software Avail: Jan-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	71.2	52.1	2	71.2	52.1
171.swim	2	266	27.1	2	266	27.1
172.mgrid	2	175	23.8	2	175	23.8
173.applu	2	211	23.1	2	211	23.1
177.mesa	2	90.2	36.0	2	90.2	36.0
178.galgel	2	93.6	71.9	2	93.6	71.9
179.art	2	82.0	73.5	2	82.0	73.5
183.quake	2	78.3	38.5	2	78.3	38.5
187.facerec	2	122	36.1	2	122	36.1
188.amp	2	205	24.9	2	205	24.9
189.lucas	2	178	26.1	2	178	26.1
191.fma3d	2	196	24.8	2	196	24.8
200.sixtrack	2	170	15.0	2	170	15.0
301.apsi	2	220	27.4	2	220	27.4

Hardware

CPU: 64-bit Intel Xeon processor (3.60 GHz, 800 MHz bus)
CPU MHz: 3600
FPU: Integrated
CPU(s) enabled: 2 cores, 2 chips, 1 core/chip (Hyper-Threading Technology disabled)
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 12k micro-ops I + 16KBD on chip
Secondary Cache: 2048KB(I+D) on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 8x512 MB DDRII-RAM PC2-3200R
Disk Subsystem: Fujitsu MAS3367NC (SCSI U320 15 krpm)
Other Hardware:

Software

Operating System: Windows Server 2003 Enterprise Edition + SP1
Compiler: Intel C++ and Fortran Compiler 8.1 Build 20050405
Microsoft Visual Studio .Net 2003 7.1.3088 (for libraries)
SmartHeap Library Version 6.03a from <http://www.microquill.com>
File System: NTFS
System State: default

Notes/Tuning Information

GENERAL

+FDO: PASS1= -Qprof_gen PASS2=-Qprof_use

Portability flags

178.galgel: -FI /F32000000

Base tuning flags

-fast -Qansi_alias +FDO shlw32M.lib

Peak tuning flags

same as baseline (basepeak=yes set globally)

The system bus runs at 800 MHz

This result was measured with 32-bit binaries using the 32-bit version of the operating system.



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers
PRIMERGY RX300 S2, 64-bit Intel Xeon processor 3.60 GHz

SPECfp_rate2000 = 32.3
SPECfp_rate_base2000 = 32.3

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: May-2005 | Hardware Avail: Mar-2005 | Software Avail: Jan-2005

Notes/Tuning Information (Continued)

For information about Fujitsu Siemens Computers in your country please see:
<http://www.fujitsu-siemens.com/countries>