



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Supermicro

X6DHP-8G2 Motherboard(Intel Xeon 3.0GHz 2M Cache)

SPECint_rate2000 = 33.6

SPECint_rate_base2000 = 33.5

SPEC license #01176 | Tested by: Supermicro | Test date: Jun-2005 | Hardware Avail: May-2005 | Software Avail: Aug-2004

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	4	209	31.1	4	210	31.0
175.vpr	4	286	22.7	4	280	23.2
176.gcc	4	112	45.7	4	112	45.7
181.mcf	4	440	19.0	4	440	19.0
186.crafty	4	176	26.4	4	174	26.6
197.parser	4	248	33.6	4	248	33.7
252.eon	4	151	39.9	4	151	39.8
253.perlbnk	4	235	35.5	4	235	35.6
254.gap	4	135	37.7	4	135	37.7
255.vortex	4	157	56.2	4	157	56.2
256.bzip2	4	239	29.1	4	237	29.3
300.twolf	4	331	42.0	4	330	42.2

Hardware

CPU: Intel Xeon 3.0GHz
CPU MHz: 3000
FPU: Integrated
CPU(s) enabled: 2 cores, 2 chips, 1 core/chip(Hyper-Threading Technology Enabled)
CPU(s) orderable: 1, 2
Parallel: No
Primary Cache: 12k micro-ops I + 16KBD on chip
Secondary Cache: 2048KB(I+D) on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 2 X 1GB DDR2 400 REG ECC
Disk Subsystem: WD 74GB 10000RPM SATA
Other Hardware:

Software

Operating System: Windows 2003 Enterprise Edition
Compiler: Intel C++ Compiler 8.1 Build 20040802Z (32-bit)
Microsoft Visual Studio .Net 2003(for libraries)
SmartHeap Library Version 6.0 from <http://www.microquill.com/>
File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs: -fast +FDO shlW32M.lib
Base tuning for C++ programs: -fast -Qcxx_features +FDO
Portability flags:
176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
252.eon: Approved stdcpp src.alt used
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
164.gzip: -fast -Qansi_alias -Oa +FDO
175.vpr: -fast -Qansi_alias +FDO
176.gcc: basepeak=yes
181.mcf: basepeak=yes
186.crafty: -fast -Qansi_alias -Oa +FDO
197.parser: -fast -Qansi_alias +FDO
252.eon: -fast +FDO
253.perlbnk: -fast -Qansi_alias +FDO shlW32M.lib
254.gap: basepeak=yes
255.vortex: basepeak=yes
```



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Supermicro

X6DHP-8G2 Motherboard(Intel Xeon 3.0GHz 2M Cache)

SPECint_rate2000 = 33.6

SPECint_rate_base2000 = 33.5

SPEC license #01176 | Tested by: Supermicro | Test date: Jun-2005 | Hardware Avail: May-2005 | Software Avail: Aug-2004

Notes/Tuning Information (Continued)

256.bzip2: -fast -Oa -Qunroll11 +FDO

300.twolf: -fast -O3 +FDO shlw32M.lib

Tested system configuration used an SC814+ Series chassis

with a 420W (minimum) ATX power supply [8-pin (+12V) and 24-pin are required]

See <http://www.supermicro.com/products/motherboard/Xeon800/E7520/X6DHP-8G2.cfm>

The system bus runs at 800 MHz