



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Advanced Micro Devices
TYAN S2865 K8E Tomcat, AMD Opteron (TM) 146

SPECint2000 = 1447
SPECint_base2000 = 1370

SPEC license #: 49 Tested by: AMD, Austin, TX Test date: Jul-2005 Hardware Avail: Aug-2005 Software Avail: Aug-2004

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
164.gzip	1400	126	1111	126	1111
175.vpr	1400	121	1160	116	1203
176.gcc	1100	73.0	1507	72.8	1511
181.mcf	1800	167	1076	139	1298
186.crafty	1000	77.6	1288	70.0	1428
197.parser	1800	137	1311	138	1308
252.eon	1300	69.4	1873	61.8	2103
253.perlbnk	1800	131	1370	131	1370
254.gap	1100	76.3	1441	76.3	1441
255.vortex	1900	91.8	2071	84.6	2246
256.bzip2	1500	133	1129	131	1148
300.twolf	3000	209	1433	186	1615

Hardware

CPU: AMD Opteron (TM) 146 (939-pin)
 CPU MHz: 2000
 FPU: Integrated
 CPU(s) enabled: 1 core, 1 chip, 1 core/chip
 CPU(s) orderable: 1
 Parallel: No
 Primary Cache: 64KBI + 64KBD on chip
 Secondary Cache: 1024KB(I+D) on chip
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 4x512 MB DDR400 CL2.0
 Disk Subsystem: SATA, Western Digital WD740GD, 10000 rpm
 Other Hardware: None

Software

Operating System: Microsoft Windows XP Pro SP2
 Compiler: Intel C++ 8.0 build 20040714Z
 Microsoft Visual Studio .NET 7.0.9466 (libraries)
 MicroQuill Smartheap Library 7.0
 File System: NTFS
 System State: Default

Notes/Tuning Information

shlw32M7.lib is the SmartHeap library V7.0 from MicroQuill www.microquill.com
 +FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

Portability:

176.gcc: -Dalloca=_alloca /F10000000
 186.crafty: -DNT_i386
 253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
 254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

Baseline C: -fast -arch:SSE2 -Oi- +FDO

Baseline C++: -fast -arch:SSE2 -GX -GR

Peak Tuning:

164.gzip: basepeak=yes
 175.vpr: -fast -arch:SSE2 +FDO
 -Qoption,c,-ip_ninl_max_stats=2000,-ip_ninl_max_total_stats=4500
 176.gcc: -fast -arch:SSE2 +FDO -Oi- -Qunroll3
 181.mcf: -fast -QaxN +FDO
 186.crafty: -fast -arch:SSE2 +FDO
 197.parser: -arch:SSE2 +FDO -Oi- -Qipo
 252.eon: -fast -arch:SSE2 +FDO -Qansi_alias
 -Qoption,c,-ip_ninl_max_stats=2000,-ip_ninl_max_total_stats=4500
 253.perlbnk: basepeak=yes



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Advanced Micro Devices
TYAN S2865 K8E Tomcat, AMD Opteron (TM) 146

SPECint2000 = 1447
SPECint_base2000 = 1370

SPEC license #: 49 | Tested by: AMD, Austin, TX | Test date: Jul-2005 | Hardware Avail: Aug-2005 | Software Avail: Aug-2004

Notes/Tuning Information (Continued)

```
254.gap:      basepeak=yes
255.vortex:   -fast -arch:SSE +FDO -Oi- shlw32M7.lib
              -Qoption,c,-ip_ninl_max_stats=2000,-ip_ninl_max_total_stats=4500
256.bzip2:    -fast -Qunroll2
300.twolf:    -fast -arch:SSE2 +FDO -Qunroll3 shlw32M7.lib -Qansi_alias
```

The tested system can be assembled using a standard ATX footprint, an Antec True 550 Watt EPS12V power supply, and a PCI or PCIe graphics card.
All memory slots were populated with Corsair CMX512-3200XL.
Memory timings manually set in BIOS: CAS=2, TRCD=2, TRAS=5, TRP=2
BIOS version 1.01