



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant BL35p (AMD Opteron (TM) 275)

SPECint_rate2000 = 17.4
SPECint_rate_base2000 = 15.8

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: Aug-2005 | Hardware Avail: Jun-2005 | Software Avail: Apr-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	1	107	15.2	1	105	15.5
175.vpr	1	131	12.4	1	126	12.9
176.gcc	1	72.5	17.6	1	72.5	17.6
181.mcf	1	276	7.57	1	172	12.2
186.crafty	1	53.4	21.7	1	53.2	21.8
197.parser	1	173	12.1	1	145	14.4
252.eon	1	62.2	24.3	1	56.2	26.8
253.perlbnk	1	120	17.4	1	112	18.6
254.gap	1	75.8	16.8	1	75.8	16.8
255.vortex	1	87.1	25.3	1	85.7	25.7
256.bzip2	1	121	14.3	1	121	14.3
300.twolf	1	246	14.2	1	193	18.1

Hardware

CPU: AMD Opteron (TM) 275
 CPU MHz: 2200
 FPU: Integrated
 CPU(s) enabled: 1 core, 1 chip, 2 cores/chip
 CPU(s) orderable: 1,2
 Parallel: No
 Primary Cache: 64KBI + 64KBD (on chip) per core
 Secondary Cache: 1024KB(I+D) (on chip) per core
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 2x2048MB PC3200 CL3.0
 Disk Subsystem: 1x60GB ATA100 5400RPM
 Other Hardware:

Software

Operating System: SuSE Linux Enterprise Server 9 (x86_64) SP 1
 SuSE kernel 2.6.5-7.139-default
 Compiler: PathScale EKO Compiler Suite, Release 2.1
 AMD Core Math Library 2.5.1
 File System: Linux/ext2
 System State: Multi-user run level 3

Notes/Tuning Information

```
+FDO: PASS1= -fb_create fbdata PASS2= -fb_opt fbdata
Base tuning for C programs: -O3 -ipa +FDO
Base tuning for C++ programs: -Ofast +FDO
Portability flags:
 186.crafty: -DLINUX_i386
 252.eon: -DHAS_ERRLIST -DSPEC_CPU2000_LP64 srcalt=fmax_errno
 253.perlbnk: -DSPEC_CPU2000_LINUX_I386 -DSPEC_CPU2000_NEED_BOOL
             -DSPEC_CPU2000_GLIBC22 -DSPEC_CPU2000_LP64
 254.gap: -DSYS_IS_USG -DSYS_HAS_IOCTL_PROTO -DSYS_HAS_TIME_PROTO
          -DSYS_HAS_SIGNAL_PROTO -DSYS_HAS_ANSI -DSYS_HAS_CALLOC_PROTO
          -DSPEC_CPU2000_LP64
 255.vortex: -DSPEC_CPU2000_LP64 srcalt=closed_files
Peak tuning:
 164.gzip: -Ofast
 175.vpr: -O2 -ipa -OPT:alias=disjoint -CG:p2align_freq=500000 -INLINE:aggressive=on
          -IPA:space=300:plimit=10000:callee_limit=5000:linear=on +FDO
 176.gcc: basepeak=true
 181.mcf: -O3 -ipa -IPA:field_reorder=on -m32
 186.crafty: -Ofast
 197.parser: -O3 -ipa -m32 -IPA:ctype=on +FDO
```



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant BL35p (AMD Opteron (TM) 275)

SPECint_rate2000 = 17.4
SPECint_rate_base2000 = 15.8

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: Aug-2005 | Hardware Avail: Jun-2005 | Software Avail: Apr-2005

Notes/Tuning Information (Continued)

```

252.eon:      -Ofast -CG:gcm=off:p2align_freq=1:prefetch=off -OPT:treeheight=on
              -TENV:X=4:frame_pointer=off -fno-exceptions -LNO:fu=10:full_unroll_outer=on
              -IPA:plimit=4000:pu_reorder=1 +FDO
253.perlbnk: -O3 -ipa -IPA:plimit=10000 +FDO
254.gap:      -O3 -ipa -OPT:transform_to_memlib=on
255.vortex:   -Ofast -IPA:space=70:plimit=3000
              -OPT:goto=off:unroll_analysis=off:unroll_size=0:unroll_times_max=8
              -LNO:opt=0 -TENV:X=4
256.bzip2:    basepeak=true
300.twolf:    -O2 -OPT:unroll_times=8:unroll_size=256:alias=disjoint:Ofast
              -CG:gcm=off:p2align_freq=100000 -WOPT:mem_opnds=on -m32

```

BIOS Configuration Notes
Node Interleaving Disabled

Other Configuration Notes
Taskset utility used to bind process to CPU(s)