



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company  
ProLiant BL35p (AMD Opteron (TM) 275)

SPECint\_rate2000 = 33.6  
SPECint\_rate\_base2000 = 32.4

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Aug-2005 Hardware Avail: Jun-2005 Software Avail: Jun-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	2	116	27.9	2	116	27.9
175.vpr	2	122	26.6	2	118	27.4
176.gcc	2	69.0	37.0	2	68.3	37.4
181.mcf	2	238	17.6	2	189	22.1
186.crafty	2	69.6	33.4	2	63.3	36.7
197.parser	2	133	31.4	2	133	31.5
252.eon	2	59.3	50.9	2	55.1	54.8
253.perlbnk	2	123	34.0	2	123	34.0
254.gap	2	75.8	33.7	2	95.9	26.6
255.vortex	2	85.0	51.9	2	84.7	52.1
256.bzip2	2	135	25.8	2	132	26.4
300.twolf	2	204	34.2	2	169	41.2

### Hardware

CPU: AMD Opteron (TM) 275  
 CPU MHz: 2200  
 FPU: Integrated  
 CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip  
 CPU(s) orderable: 1,2  
 Parallel: No  
 Primary Cache: 64KBI + 64KBD (on chip) per core  
 Secondary Cache: 1024KB(I+D) (on chip) per core  
 L3 Cache: N/A  
 Other Cache: N/A  
 Memory: 2x2048MB PC3200 CL3.0  
 Disk Subsystem: 1x60GB ATA100 5400RPM  
 Other Hardware:

### Software

Operating System: Windows Server 2003 Enterprise SP1  
 Compiler: Intel C++ Compiler for 32-bit applications, (Version 8.0 Build 20040318Z) Microsoft Visual Studio .NET 7.0.9466 (for libraries) MicroQuill Smartheap Library 7.0  
 File System: NTFS  
 System State: Default

## Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs: -fast -arch:SSE2 -Oi- +FDO ONESTEP=yes
Base tuning for C++ programs: -fast -GX -GR +FDO ONESTEP=yes
Portability flags:
 176.gcc: -Dalloca=_alloca /F10000000
 186.crafty: -DNT_i386
 253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
 254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
 164.gzip: basepeak=yes
 175.vpr: -fast -arch:SSE2 -Qoption,c,-ip_ninl_max_stats=2000
          -Qoption,c,-ip_ninl_max_total_stats=4500 +FDO ONESTEP=yes
 176.gcc: -fast -arch:SSE2 -Oi- -Qunroll3 +FDO
 181.mcf: -fast -QaxN +FDO ONESTEP=yes
 186.crafty: -fast -arch:SSE2 +FDO ONESTEP=yes
 197.parser: -arch:SSE2 -Oi- -Qipo +FDO ONESTEP=yes
 252.eon: -fast -arch:SSE2 -Qansi_alias -Qoption,c,-ip_ninl_max_stats=2000
          -Qoption,c,-ip_ninl_max_total_stats=4500 +FDO ONESTEP=yes
 253.perlbnk: basepeak=yes
 254.gap: basepeak=yes
```



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company  
ProLiant BL35p (AMD Opteron (TM) 275)

SPECint\_rate2000 = 33.6  
SPECint\_rate\_base2000 = 32.4

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Aug-2005 Hardware Avail: Jun-2005 Software Avail: Jun-2005

## Notes/Tuning Information (Continued)

255.vortex: -fast -arch:SSE -Oi- -Qoption,c,-ip\_ninl\_max\_stats=2000  
-Qoption,c,-ip\_ninl\_max\_total\_stats=4500 +FDO shlw32M.lib ONESTEP=yes  
256.bzip2: -fast -Qunroll2  
300.twolf: -fast -arch:SSE2 -Qansi\_alias +FDO shlw32M.lib ONESTEP=yes  
BIOS Configuration Notes  
Node Interleaving Disabled  
Other Configuration Notes  
The start /b /wait /affinity command is used to bind CPU(s) to processes.