



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Dell
PowerEdge 1850 (3.8GHz Intel Xeon)

SPECfp_rate2000 = 32.7

SPECfp_rate_base2000 = 32.5

SPEC license #: 55 | Tested by: Dell, Round Rock, TX | Test date: Aug-2005 | Hardware Avail: Oct-2005 | Software Avail: Mar-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	70.5	52.6	2	70.5	52.6
171.swim	2	271	26.5	2	271	26.5
172.mgrid	2	171	24.5	2	171	24.5
173.applu	2	211	23.1	2	207	23.6
177.mesa	2	85.5	38.0	2	85.5	38.0
178.galgel	2	90.3	74.5	2	90.3	74.5
179.art	2	88.4	68.3	2	88.4	68.3
183.quake	2	107	28.1	2	107	28.1
187.facerec	2	123	35.9	2	123	36.0
188.amp	2	183	28.0	2	176	29.1
189.lucas	2	187	24.8	2	187	24.8
191.fma3d	2	162	30.1	2	162	30.1
200.sixtrack	2	161	15.8	2	160	16.0
301.apsi	2	208	29.1	2	208	29.1

Hardware

CPU: Intel Xeon (3.8GHz, 2MB L2, 800MHz system bus)
 CPU MHz: 3800
 FPU: Integrated
 CPU(s) enabled: 2 cores, 2 chips, 1 core/chip (Hyper-Threading Technology disabled)
 CPU(s) orderable: 1,2
 Parallel: No
 Primary Cache: 12KB(I) + 16KB(D) on chip
 Secondary Cache: 2048KB(I+D) on chip
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 4x2GB (dual-ranked) ECC 400MHz DDR2 SDRAM
 Disk Subsystem: 1 x 36GB 15000RPM SCSI
 Other Hardware: None

Software

Operating System: Windows Server 2003, Standard Edition, Service Pack 1
 Compiler: Intel C/C++ Compiler 8.1 for IA32 (20041119Z)
 Microsoft Visual Studio .NET 2003(7.1.3088, for libraries)
 MicroQuill SmartHeap Library 7.1
 File System: NTFS
 System State: Default

Notes/Tuning Information

GENERAL

ONESTEP=yes
 +FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

PORTABILITY

178.galgel: -FI /F3200000
 191.fma3d: srcalt=windowsdp

BASE TUNING

C/F77/F90: -fast -Qansi_alias +FDO

PEAK TUNING

168.wupwise: basepeak=yes
 171.swim: basepeak=yes
 172.mgrid: basepeak=yes
 173.applu: -fast -Qansi_alias -Qscalar_rep- -Qauto +FDO
 177.mesa: basepeak=yes
 178.galgel: basepeak=yes
 179.art: basepeak=yes
 183.quake: -fast -Qansi_alias -Oa -Qrcd +FDO



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Dell
PowerEdge 1850 (3.8GHz Intel Xeon)

SPECfp_rate2000 = 32.7
SPECfp_rate_base2000 = 32.5

SPEC license #: 55 | Tested by: Dell, Round Rock, TX | Test date: Aug-2005 | Hardware Avail: Oct-2005 | Software Avail: Mar-2005

Notes/Tuning Information (Continued)

```
187.facerec: -fast -Qunroll11 -Qscalar_rep- +FDO
188.ammv: -Oa -QxP
189.lucas: -fast
191.fma3d: basepeak=yes
200.sixtrack: -QxP -Qipo +FDO*
301.apsi: basepeak=yes
```

NOTES
*+FDO does not include -QxP for PASS1 to enable cross-compilation.