



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation

IBM eServer xSeries x206m (3.0GHz Pentium 4 531, 1MB L2 Cache)

SPECint_rate2000 = 17.7

SPECint_rate_base2000 = 17.6

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Sep-2005 | Hardware Avail: Sep-2005 | Software Avail: Jun-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	2	210	15.5	2	207	15.7
175.vpr	2	302	10.8	2	294	11.1
176.gcc	2	123	20.8	2	123	20.8
181.mcf	2	235	17.7	2	231	18.1
186.crafty	2	173	13.4	2	174	13.3
197.parser	2	248	16.9	2	247	16.9
252.eon	2	138	21.9	2	138	21.9
253.perlbnk	2	214	19.5	2	213	19.6
254.gap	2	116	22.0	2	115	22.2
255.vortex	2	154	28.6	2	154	28.7
256.bzip2	2	231	15.1	2	230	15.1
300.twolf	2	458	15.2	2	458	15.2

Hardware

CPU: Intel Pentium 4 531 (800 MHz system bus)
CPU MHz: 3000
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip (Hyper-Threading Technology enabled)
CPU(s) orderable: 1
Parallel: No
Primary Cache: 12K(I) micro-ops + 16KB(D) on chip
Secondary Cache: 1024KB(I+D) on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 4 x 1024 MB ECC PC2-3200 Single Rank
Disk Subsystem: 73GB SAS 15K RPM
Other Hardware:

Software

Operating System: Windows Server 2003 Standard Edition
Compiler: Intel C/C++ Compiler 9.0 (20050624Z) for 32-bit applications
Intel Fortran Compiler 9.0 (20050624Z) for 32-bit applications
Microsoft Visual Studio .NET 13.0.9466 (for libraries)
MicroQuill Smartheap Library 7.30
File System: NTFS
System State: Default

Notes/Tuning Information

GENERAL

ONESTEP=yes
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

PORTABILITY FLAGS

176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
252.eon: srcalt=stdcpp
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

BASE TUNING

C: -fast -Qansi_alias +FDO shlw32M.lib
C++: -fast -Qcxx_features +FDO

PEAK TUNING

164.gzip: -fast +FDO
175.vpr: -fast +FDO
176.gcc: basepeak=yes
181.mcf: -fast +FDO shlw32M.lib
186.crafty: -fast -Oa +FDO shlw32M.lib
197.parser: -fast +FDO
252.eon: -fast +FDO



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation

IBM eServer xSeries x206m (3.0GHz Pentium 4 531, 1MB L2 Cache)

SPECint_rate2000 = 17.7

SPECint_rate_base2000 = 17.6

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Sep-2005 | Hardware Avail: Sep-2005 | Software Avail: Jun-2005

Notes/Tuning Information (Continued)

```
253.perlbnk: -fast -Oa +FDO shlw32M.lib
254.gap:      -fast +FDO
255.vortex   -fast +FDO shlw32M.lib
256.bzip2:   -fast -Qunroll1 -Oa +FDO shlw32M.lib
300.twolf:   -fast +FDO shlw32M.lib
EXTRA LIBRARIES
shlw32M.lib: MicroQuill SmartHeap Library 7.3
              www.microquill.com
```