



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Supermicro X6DHP-TG Motherboard

SPECfp2000 = 1802

SPECfp_base2000 = 1779

SPEC license #01176 Tested by: Supermicro Test date: Oct-2005 Hardware Avail: Sep-2005 Software Avail: Apr-2005

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	64.2	2494	64.0	2501	
171.swim	3100	156	1985	147	2110	
172.mgrid	1800	121	1487	118	1521	
173.applu	2100	144	1463	141	1488	
177.mesa	1400	85.8	1631	85.8	1631	
178.galgel	2900	80.2	3616	79.9	3631	
179.art	2600	63.9	4066	63.9	4066	
183.quake	1300	52.5	2475	52.2	2490	
187.facerec	1900	105	1816	104	1828	
188.amp	2200	198	1113	195	1127	
189.lucas	2000	108	1851	108	1852	
191.fma3d	2100	149	1409	149	1409	
200.sixtrack	1100	147	746	147	747	
301.apsi	2600	205	1267	196	1323	

Hardware

CPU: Intel Xeon Processor (3.80 GHz, 2MB L2, 800 MHz bus)
CPU MHz: 3800
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip (Hyper-Threading Technology Disabled)
CPU(s) orderable: 1
Parallel: No
Primary Cache: 12k micro-ops I + 16KBD on chip
Secondary Cache: 2048KB(I+D) on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 6GB (6x1GB 2 X 1GB DDR 333 REG ECC)
Disk Subsystem: 1 X 40GB IDE
Other Hardware: N/A

Software

Operating System: Windows 2003 EE SP1
Compiler: Intel C++ and Fortran Compiler 9.0 Build 20050430Z (32-bit)
Microsoft Visual Studio .Net 2003(for libraries)
SmartHeap Library Version 7.4 from <http://www.microquill.com/>
File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO: PASS1= -Qprof_gen PASS2=-Qprof_use
Base tuning for Fortran programs: -fast -Qansi_alias +FDO
Base tuning for C programs: -fast +FDO shlW32M.lib
shlW32M.lib is the SmartHeap Library
Portability:
178.galgel: -FI /F32000000
191.fmma3d approved windowsdp src.alt used
Peak tuning:
168.wupwise: -fast -Qansi_alias +FDO
171.swim: -fast -Qansi_alias +FDO
172.mgrid: -fast -Qansi_alias +FDO
173.applu: -fast -Qscalar_rep- -Qauto +FDO
177.mesa: basepeak=yes
178.galgel: -fast -Qansi_alias +FDO
179.art: basepeak=yes
183.quake: -QxP -Oa -Qrcd -Qipo shlW32M.lib +FDO
187.facerec: -fast -Qunroll1 -Qscalar_rep- +FDO
```



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Supermicro
X6DHP-TG Motherboard

SPECfp2000 = 1802

SPECfp_base2000 = 1779

SPEC license #01176 | Tested by: Supermicro | Test date: Oct-2005 | Hardware Avail: Sep-2005 | Software Avail: Apr-2005

Notes/Tuning Information (Continued)

188. ammp: -fast -Oa +FDO shlw32M.lib

189. lucas: -fast -Qprefetch- +FDO

191. fma3d: basepeak=yes

200. sixtrack: -Qipo -QxP +FDO

301. apsi: -fast +FDO

New 32-bit Windows tools used, approved in May-2005

Tested system was built with SC814+ Chassis.

Product description located as of:

<http://www.supermicro.com/products/motherboard/Xeon800/E7520/X6DHP-TG.cfm>

The system bus runs at 800MHz