



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Acer Incorporated  
Acer Altos R710 (3.0 GHz Intel Xeon)

SPECfp\_rate2000 = 19.6  
SPECfp\_rate\_base2000 = 19.5

SPEC license #: 97 Tested by: Acer Incorporated Test date: Nov-2005 Hardware Avail: Oct-2005 Software Avail: Apr-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	143	25.9	2	144	25.8
171.swim	2	264	27.2	2	265	27.2
172.mgrid	2	242	17.3	2	242	17.2
173.applu	2	342	14.2	2	342	14.2
177.mesa	2	206	15.8	2	206	15.8
178.galgel	2	206	32.7	2	206	32.6
179.art	2	167	36.0	2	167	36.0
183.quake	2	92.4	32.6	2	92.6	32.6
187.facerec	2	199	22.2	2	199	22.2
188.amp	2	414	12.3	2	363	14.1
189.lucas	2	243	19.1	2	244	19.0
191.fma3d	2	310	15.7	2	310	15.7
200.sixtrack	2	292	8.75	2	301	8.48
301.apsi	2	403	15.0	2	404	14.9

### Hardware

CPU: Intel Xeon (3.0 GHz, 2MB L2, 800MHz system bus)  
CPU MHz: 3000  
FPU: Integrated  
CPU(s) enabled: 1 core, 1 chip, 1 core/chip(Hyper-Threading Technology Enable)  
CPU(s) orderable: 1,2  
Parallel: No  
Primary Cache: 12KB(I) micro-ops + 16KB(D) on chip  
Secondary Cache: 2048KB(I+D) on chip  
L3 Cache: N/A  
Other Cache: N/A  
Memory: 6 x 512MB ECC DDR2-400 SDRAM  
Disk Subsystem: 1 x 146GB 10000RPM U320 SCSI HDD  
Other Hardware:

### Software

Operating System: Microsoft Windows Server 2003 Enterprise Edition (Build 3790)  
Compiler: Intel C++ 9.0 Build 20050430Z for IA32 and Fortran Compiler 9.0 Build 20050722Z for IA32  
Microsoft Visual Studio .Net 2003(7.1.3091, for libraries)  
shlw32M.lib is SmartHeap Library Version 7.4 from http://www.microquill.com/  
File System: NTFS  
System State: Default

## Notes/Tuning Information

```
+FDO: PASS1= -Qprof_gen PASS2=-Qprof_use
Base tuning for all Fortran Programs : -fast -Qansi_alias +FDO
Base tuning for all C Programs: -fast +FDO shlw32M.lib
Portability:
178.galgel: -FI /F32000000
192.fma3d: Approved windowsdp src.alt used
Peak tuning:
168.wupwise: -fast -Qansi_alias +FDO
171.swim: -fast -Qansi_alias +FDO
172.mgrid: -fast -Qansi_alias +FDO
173.applu: basepeak=yes
177.mesa: basepeak=yes
178.galgel: -fast -Qansi_alias +FDO
179.art: basepeak=yes
183.quake: -fast -Oa -Qrcd -Qprof_gen shlw32M.lib
187.facerec: basepeak=yes
188.amp: -Oa -QxP
```



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Acer Incorporated  
Acer Altos R710 (3.0 GHz Intel Xeon)

SPECfp\_rate2000 = 19.6  
SPECfp\_rate\_base2000 = 19.5

SPEC license #: 97 | Tested by: Acer Incorporated | Test date: Nov-2005 | Hardware Avail: Oct-2005 | Software Avail: Apr-2005

## Notes/Tuning Information (Continued)

```
189.lucas: -fast -Qprefetch- +FDO
191.fma3d: basepeak=yes
200.sixtrack: -Qipo -QxP +FDO
301.apsi: -fast +FDO
Enable hardware prefetching and adjacent cache line prefetch BIOS setting
Product description located at http://www.acer.com
```