



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company  
ProLiant DL145 G2 (AMD Opteron (TM) 275)

SPECint\_rate2000 = 68.9  
SPECint\_rate\_base2000 = 61.4

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Nov-2005 Hardware Avail: Sep-2005 Software Avail: Sep-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	4	104	62.2	4	105	62.1
175.vpr	4	136	47.7	4	128	50.9
176.gcc	4	73.8	69.2	4	73.3	69.6
181.mcf	4	380	22.0	4	243	34.3
186.crafty	4	50.8	91.3	4	49.8	93.2
197.parser	4	176	47.4	4	142	58.7
252.eon	4	56.5	107	4	48.4	125
253.perlbnk	4	118	70.9	4	108	77.0
254.gap	4	84.1	60.7	4	81.3	62.8
255.vortex	4	87.2	101	4	78.2	113
256.bzip2	4	124	56.3	4	124	56.3
300.twolf	4	247	56.4	4	192	72.6

### Hardware

CPU: AMD Opteron (TM) 275  
CPU MHz: 2200  
FPU: Integrated  
CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip  
CPU(s) orderable: 1,2  
Parallel: No  
Primary Cache: 64KBI + 64KBD (on chip) per core  
Secondary Cache: 1024KB(I+D) (on chip) per core  
L3 Cache: N/A  
Other Cache: N/A  
Memory: 8x2048MB PC3200 CL3.0  
Disk Subsystem: 1x36.4GB 15K Ultra320 SCSI  
Other Hardware:

### Software

Operating System: SuSE Linux Enterprise Server 9 (x86\_64) SP 2  
SuSE kernel 2.6.5-7.191-smp  
Compiler: PathScale EKOPath(TM) Compiler Suite, Release 2.2.1  
File System: Linux/ext2  
System State: Multi-user run level 3

## Notes/Tuning Information

```
+FDO: PASS1= -fb_create fbdata PASS2= -fb_opt fbdata
Base tuning for C programs: -Ofast +FDO
Base tuning for C++ programs: -Ofast +FDO
Portability flags:
186.crafty: -DLINUX_i386
252.eon: -DHAS_ERRLIST -DSPEC_CPU2000_LP64
253.perlbnk: -DSPEC_CPU2000_LINUX_I386 -DSPEC_CPU2000_NEED_BOOL
           -DSPEC_CPU2000_GLIBC22 -DSPEC_CPU2000_LP64
254.gap: -DSYS_IS_USG -DSYS_HAS_IOCTL_PROTO -DSYS_HAS_TIME_PROTO
          -DSYS_HAS_CALLOC_PROTO -DSPEC_CPU2000_LP64
255.vortex: -DSPEC_CPU2000_LP64
Peak tuning:
164.gzip: -O3 -ipa -WOPT:val=0 -OPT:unroll_size=0 +FDO
175.vpr: -O3 -ipa -m32 +FDO
176.gcc: -O3 -IPA:plimit=10000 -LNO:opt=0 -OPT:goto=off +FDO
181.mcf: -O3 -ipa -IPA:field_reorder=on -m32 +FDO
186.crafty: -Ofast -CG:local_fwd_sched=on -LNO:opt=0 -WOPT:val=0 +FDO
197.parser: -O3 -ipa -m32 -IPA:ctype=on +FDO
252.eon: -Ofast -CG:gcm=off:p2align_freq=1:prefetch=off -IPA:plimit=4000
          -OPT:treeheight=on -TENV:X=4:frame_pointer=off -fno-exceptions
```



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company  
ProLiant DL145 G2 (AMD Opteron (TM) 275)

SPECint\_rate2000 = 68.9  
SPECint\_rate\_base2000 = 61.4

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: Nov-2005 | Hardware Avail: Sep-2005 | Software Avail: Sep-2005

## Notes/Tuning Information (Continued)

```
-LNO:fu=10:full_unroll_outer=on -GRA:optimize_boundary=on +FDO
253.perlbnk: -O2 -ipa -OPT:Ofast:transform_to_memlib=off
              -fno-math-errno -IPA:plimit=10000 +FDO
254.gap:      -Ofast -IPA:min_hotness=5 -OPT:alias=disjoint -CG:movnti=1 +FDO
255.vortex:   -Ofast -OPT:goto=off +FDO
256.bzip2:    basepeak=true
300.twolf:    -O2 -CG:gcm=off:p2align_freq=100000
              -OPT:Ofast:unroll_times_max=8:unroll_size=256:alias=disjoint
              -WOPT:mem_opnds=on -m32 +FDO
```

### BIOS Configuration Notes

Node Interleaving Disabled

### Other Configuration Notes

Taskset utility used to bind process to CPU(s)