



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

## Acer Incorporated

Acer Altos G530 (3.6 GHz Intel Xeon processor, 2MB L2, 800MHz system bus)

SPECint\_rate2000 = 21.5

SPECint\_rate\_base2000 = 21.4

SPEC license #: 97 | Tested by: Acer Incorporated | Test date: Nov-2005 | Hardware Avail: Oct-2005 | Software Avail: Apr-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	2	177	18.3	2	177	18.3
175.vpr	2	240	13.6	2	233	14.0
176.gcc	2	92.1	27.7	2	92.1	27.7
181.mcf	2	223	18.8	2	223	18.8
186.crafty	2	149	15.6	2	149	15.6
197.parser	2	203	20.6	2	202	20.7
252.eon	2	117	25.7	2	118	25.5
253.perlbnk	2	183	22.8	2	182	22.9
254.gap	2	102	25.1	2	102	25.1
255.vortex	2	131	33.6	2	131	33.6
256.bzip2	2	194	18.0	2	194	18.0
300.twolf	2	277	25.1	2	276	25.2

### Hardware

CPU: Intel Xeon (3.6 GHz, 2MB L2, 800MHz system bus)  
CPU MHz: 3600  
FPU: Integrated  
CPU(s) enabled: 1 core, 1 chip, 1 core/chip(Hyper-Threading Technology Enable)  
CPU(s) orderable: 1,2  
Parallel: No  
Primary Cache: 12KB(I) micro-ops + 16KB(D) on chip  
Secondary Cache: 2048KB(I+D) on chip  
L3 Cache: N/A  
Other Cache: N/A  
Memory: 4 x 1GB ECC DDR2-400 SDRAM  
Disk Subsystem: 1 x 146GB 10000RPM U320 SCSI HDD  
Other Hardware:

### Software

Operating System: Microsoft Windows Server 2003 Enterprise Edition (Build 3790)  
Compiler: Intel C++ Compiler 9.0 Build 20050430Z for IA32  
Microsoft Visual Studio .Net 2003(7.1.3091, for libraries)  
shlw32M.lib is SmartHeap Library Version 7.4 from http://www.microquill.com/  
File System: NTFS  
System State: Default

## Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs: -fast +FDO shlw32M.lib
Base tuning for C++ programs: -fast -Qcxx_features +FDO shlw32M.lib
Portability flags:
176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
252.eon: Approved stdcpp src.alt used
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
164.gzip: basepeak=yes
175.vpr: -fast -Qansi_alias +FDO
176.gcc: basepeak=yes
181.mcf: basepeak=yes
186.crafty: basepeak=yes
197.parser: -fast -Qansi_alias +FDO
252.eon: -fast +FDO
253.perlbnk: -fast -Qansi_alias +FDO shlw32M.lib
254.gap: basepeak=yes
255.vortex: basepeak=yes
```



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

**Acer Incorporated**

Acer Altos G530 (3.6 GHz Intel Xeon processor, 2MB L2, 800MHz system bus)

SPECint\_rate2000 = 21.5

SPECint\_rate\_base2000 = 21.4

SPEC license #: 97 | Tested by: Acer Incorporated | Test date: Nov-2005 | Hardware Avail: Oct-2005 | Software Avail: Apr-2005

## Notes/Tuning Information (Continued)

256.bzip2: -fast -Oa -Qunroll1 +FDO

300.twolf: -fast +FDO shlw32M.lib

Enable hardware prefetching and adjacent cache line prefetch BIOS setting

Product description located at <http://www.acer.com>