



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Acer Incorporated

Acer Altos R510Mk2 (3.6 GHz Intel Xeon processor, 2MB L2)

SPECfp_rate2000 = 32.0

SPECfp_rate_base2000 = 32.0

SPEC license #: 97 Tested by: Acer Incorporated Test date: Jan-2006 Hardware Avail: Jan-2006 Software Avail: Nov-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	72.2	51.4	2	72.4	51.3
171.swim	2	285	25.3	2	285	25.3
172.mgrid	2	178	23.4	2	178	23.4
173.applu	2	218	22.3	2	218	22.3
177.mesa	2	89.7	36.2	2	89.7	36.2
178.galgel	2	91.8	73.3	2	91.9	73.2
179.art	2	83.8	72.0	2	83.8	72.0
183.quake	2	84.9	35.5	2	84.8	35.6
187.facerec	2	117	37.6	2	117	37.6
188.amp	2	198	25.8	2	192	26.5
189.lucas	2	192	24.2	2	192	24.2
191.fma3d	2	195	24.9	2	195	24.9
200.sixtrack	2	153	16.6	2	154	16.6
301.apsi	2	233	25.9	2	234	25.8

Hardware

CPU: Intel Xeon (3.6 GHz, 2MB L2, 800MHz system bus)
CPU MHz: 3600
FPU: Integrated
CPU(s) enabled: 2 cores, 2 chips, 1 core/chip(Hyper-Threading Technology disabled)
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 12KB(I) micro-ops + 16KB(D) on chip
Secondary Cache: 2048KB(I+D) on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 6 x 512MB ECC DDR2-400 SDRAM
Disk Subsystem: 1 x 160GB 7200RPM SATA HDD
Other Hardware:

Software

Operating System: Microsoft Windows Server 2003 Enterprise Edition (Build 3790)
Compiler: Intel C++ 9.0 Build 20051130Z for IA32 and Fortran Compiler 9.0 Build 20051130Z for IA32
Microsoft Visual Studio .Net 2003(7.1.3091, for libraries)
shlw32M.lib is Microquill SmartHeap Library Version 7.4
File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO: PASS1= -Qprof_gen PASS2=-Qprof_use
Base tuning for all Fortran Programs : -fast -Qansi_alias +FDO
Base tuning for all C Programs: -fast +FDO shlw32M.lib
Portability:
178.galgel: -FI /F32000000
Peak tuning:
168.wupwise: -fast -Qansi_alias +FDO
171.swim: -fast -Qansi_alias +FDO
172.mgrid: -fast -Qansi_alias +FDO
173.applu: basepeak=yes
177.mesa: basepeak=yes
178.galgel: -fast -Qansi_alias +FDO
179.art: basepeak=yes
183.quake: -fast -Oa -Qrcd +FDO shlw32M.lib
187.facerec: basepeak=yes
188.amp: -Oa -QxP
189.lucas: -fast -Qprefetch- +FDO
```



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Acer Incorporated

Acer Altos R510Mk2 (3.6 GHz Intel Xeon processor, 2MB L2)

SPECfp_rate2000 = 32.0

SPECfp_rate_base2000 = 32.0

SPEC license #: 97 | Tested by: Acer Incorporated | Test date: Jan-2006 | Hardware Avail: Jan-2006 | Software Avail: Nov-2005

Notes/Tuning Information (Continued)

191.fma3d: basepeak=yes

200.sixtrack: -Qipo -QxP +FDO

301.apsi: -fast +FDO

Enable hardware prefetching and adjacent cache line prefetch BIOS setting

Product description located at <http://www.acer.com>