



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers
CELSIUS V830, Opteron (TM) 254, Linux 64-bit

SPECint_rate2000 = 22.7
SPECint_rate_base2000 = 20.3

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Jan-2006 | Hardware Avail: Sep-2005 | Software Avail: Dec-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	1	82.2	19.7	1	82.1	19.8
175.vpr	1	102	15.9	1	99.0	16.4
176.gcc	1	56.5	22.6	1	56.9	22.4
181.mcf	1	230	9.07	1	144	14.5
186.crafty	1	40.0	29.0	1	38.9	29.8
197.parser	1	139	15.0	1	110	19.0
252.eon	1	44.7	33.8	1	38.6	39.1
253.perlbnk	1	94.0	22.2	1	84.0	24.9
254.gap	1	59.4	21.5	1	58.7	21.7
255.vortex	1	67.2	32.8	1	62.7	35.1
256.bzip2	1	95.5	18.2	1	95.5	18.2
300.twolf	1	195	17.9	1	152	22.8

Hardware

CPU: AMD Opteron 254
 CPU MHz: 2800
 FPU: Integrated
 CPU(s) enabled: 1 core, 1 chip, 1 core/chip
 CPU(s) orderable: 1,2
 Parallel: No
 Primary Cache: 64KBI + 64KBD (on chip)
 Secondary Cache: 1024KB(I+D) (on chip)
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 4 x 512 MB PC3200 CL3-3-3 DDR SDRAM
 Disk Subsystem: SCSI U320
 Other Hardware: None

Software

Operating System: SLES 9 with SP3 (AMD64) - kernel 2.6.5-7.244-smp
 Compiler: PathScale EKOPATH(TM) Compiler Suite, Release 2.3 (for C and C++)
 File System: Linux/ReiserFS
 System State: Multi-User SuSE Run Level 3

Notes/Tuning Information

Portability flags:

```
186.crafty: -DLINUX_i386
252.eon: -DHAS_ERRLIST -DSPEC_CPU2000_LP64
253.perlbnk: -DSPEC_CPU2000_LINUX_I386 -DSPEC_CPU2000_NEED_BOOL
            -DSPEC_CPU2000_GLIBC22 -DSPEC_CPU2000_LP64
254.gap: -DSYS_IS_USG -DSYS_HAS_IOCTL_PROTO -DSYS_HAS_TIME_PROTO
         -DSYS_HAS_CALLOC_PROTO -DSPEC_CPU2000_LP64
255.vortex: -DSPEC_CPU2000_LP64
```

Feedback Optimization:

```
+FDO: PASS1=-fb_create fbdata PASS2=-fb_opt fbdata
```

Baseline Optimization Flags:

```
C programs: -Ofast +FDO
C++ programs: -Ofast +FDO
```

Peak Tuning Flags:

```
164.gzip: -O3 -ipa -WOPT:val=0 -OPT:unroll_size=0 +FDO
175.vpr: -O3 -ipa -m32 +FDO
176.gcc: -O3 -IPA:plimit=10000 -LNO:opt=0 -OPT:goto=off +FDO
```



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers
CELSIUS V830, Opteron (TM) 254, Linux 64-bit

SPECint_rate2000 = 22.7
SPECint_rate_base2000 = 20.3

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Jan-2006 | Hardware Avail: Sep-2005 | Software Avail: Dec-2005

Notes/Tuning Information (Continued)

```

181.mcf:      -O3 -ipa -IPA:field_reorder=on -m32 +FDO
186.crafty:  -Ofast -CG:local_fwd_sched=on -LNO:opt=0 -WOPT:val=0 +FDO
197.parser:  -O3 -ipa -m32 -IPA:ctype=on +FDO
252.eon:     -Ofast -CG:gcm=off:p2align_freq=1:prefetch=off -IPA:plimit=4000
             -OPT:treeheight=on -TENV:X=4:frame_pointer=off -fno-exceptions
             -LNO:fu=10:full_unroll_outer=on -GRA:optimize_boundary=on +FDO
253.perlbnk:-O2 -ipa -OPT:Ofast:transform_to_memlib=off
             -fno-math-errno -IPA:plimit=10000 +FDO
254.gap:     -Ofast -IPA:min_hotness=5 -OPT:alias=disjoint -CG:movnti=1 +FDO
255.vortex:  -Ofast -OPT:goto=off +FDO
256.bzip2:   basepeak = true
300.twolf:   -O2 -CG:gcm=off:p2align_freq=100000
             -OPT:Ofast:unroll_times_max=8:unroll_size=256:alias=disjoint
             -WOPT:mem_opnds=on -m32 +FDO

```

BIOS default settings with
Node memory interleaved disabled, SRAT enabled
taskset has been used to bind processes to CPUs

For information about Fujitsu Siemens Computers in your country please see:
<http://www.fujitsu-siemens.com/countries>