



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant ML110 G3 (3.0GHz, Intel Pentium D Processor 930)

SPECfp2000 = 1742
SPECfp_base2000 = 1717

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Feb-2006 Hardware Avail: Feb-2006 Software Avail: Oct-2005

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
168.wupwise	1600	64.7	2473	64.8	2470
171.swim	3100	126	2456	127	2448
172.mgrid	1800	132	1363	131	1375
173.applu	2100	144	1454	143	1471
177.mesa	1400	107	1313	107	1314
178.galgel	2900	90.0	3222	89.8	3230
179.art	2600	62.9	4133	62.9	4133
183.quake	1300	57.6	2255	48.5	2678
187.facerec	1900	104	1826	104	1827
188.amp	2200	194	1136	194	1136
189.lucas	2000	99.3	2015	98.6	2029
191.fma3d	2100	152	1385	152	1385
200.sixtrack	1100	183	600	183	601
301.apsi	2600	221	1175	221	1175

Hardware

CPU: Intel Pentium D Processor 930 (3.0GHz, 2x2MB L2, 800MHz bus)
CPU MHz: 3000
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 2 cores/chip
CPU(s) orderable: 1
Parallel: No
Primary Cache: 12K micro-ops I + 16KBD (on chip) per core
Secondary Cache: 2048KB(I+D) (on chip) per core
L3 Cache: N/A
Other Cache: N/A
Memory: 4x512MB PC2-4200
Disk Subsystem: 1x80.0GB SATA
Other Hardware:

Software

Operating System: Windows Server 2003 Enterprise SP1
Compiler: Intel C++ Compiler for 32-bit applications, (Version 9.0 Build 20051020Z)
Intel Fortran Compiler for 32-bit applications, (Version 9.0 Build 20051020Z)
Microsoft Visual Studio .NET 7.0.9466 (for libraries)
MicroQuill Smarheap Library 7.0
File System: NTFS
System State: Default

Notes/Tuning Information

+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

Base tuning: -fast -Qansi_alias +FDO

Portability flags:

178.galgel: -FI /F32000000

Peak tuning:

168.wupwise: -fast -Qansi_alias +FDO

171.swim: -fast -f77rtl +FDO ONESTEP=yes

172.mgrid: -fast -Qansi_alias +FDO

173.applu: -fast -Qscalar_rep- -Qauto -f77rtl +FDO ONESTEP=yes

177.mesa: -fast +FDO ONESTEP=yes

178.galgel: -fast +FDO ONESTEP=yes

179.art: basepeak=1

183.quake: -fast -Oa -Qrcd +FDO ONESTEP=yes shlw32M.lib

187.facerec: -fast -Qunroll1 -Qscalar_rep- +FDO ONESTEP=yes

188.amp: basepeak=1

189.lucas: -fast



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant ML110 G3 (3.0GHz, Intel Pentium D Processor 930)

SPECfp2000 = 1742
SPECfp_base2000 = 1717

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: Feb-2006 | Hardware Avail: Feb-2006 | Software Avail: Oct-2005

Notes/Tuning Information (Continued)

```
191.fma3d:    basepeak=1
200.sixtrack: -fast          +FDO
301.apsi:     basepeak=1
Other Configuration Notes
/NUMPROC=1 flag was added to boot.ini to invoke the uniprocessor environment.
```