



# CFP2000 Result


Copyright ©1999-2005, Standard Performance Evaluation Corporation

Sun Microsystems  
Sun Fire V40z

SPECfp\_rate2000 = 106

SPECfp\_rate\_base2000 = 95.4

SPEC license #: 6 Tested by: Sun Microsystems, Santa Clara Test date: Mar-2006 Hardware Avail: May-2006 Software Avail: Jan-2006



### Hardware

CPU: AMD Opteron (TM) 856  
 CPU MHz: 3000  
 FPU: Integrated  
 CPU(s) enabled: 4 cores, 4 chips, 1 core/chip  
 CPU(s) orderable: 2,4 (order by # of chips)  
 Parallel: No  
 Primary Cache: 64KBI + 64KBD (on chip) per core  
 Secondary Cache: 1024KB (I+D) (on chip) per core  
 L3 Cache: N/A  
 Other Cache: N/A  
 Memory: 16GB (16x1GB, PC3200 CL3 DDR ECC Registered SDRAM)  
 Disk Subsystem: SCSI,72GB,10K RPM  
 Other Hardware: None

### Software

Operating System: Solaris 10 1/06  
 Compiler: Sun Studio 11  
 File System: ufs  
 System State: Multi-user

## Notes/Tuning Information

Compiler invocation:

```
C: cc
F90: f90
F77: f90
```

```
FDO: PASS1= -xprofile=collect:./feedback PASS2= -xprofile=use:./feedback
fdo_pre0: rm -rf ./feedback.profile
```

Floating point base flags:

```
F90: -fast -xipo=2 -xarch=amd64 -xprefetch_level=3 ONESTEP=yes
C: -fast -xcrossfile -xalias_level=std -xpagesize=2m ONESTEP=yes
```

Floating point peak flags:

ONESTEP=yes for all benchmarks

```
168.wupwise: -fast -xautopar -xpad=common:3969 -xipo=2 -xarch=amd64 -xprefetch_level=3 -xpagesize_heap=2m
171.swim: -fast -xpad=common:3969 -xipo=2 -xvector=simd -xprefetch_level=3 -Qoption iropt
```



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Sun Microsystems  
Sun Fire V40z

SPECfp\_rate2000 = 106

SPECfp\_rate\_base2000 = 95.4

SPEC license #: 6 Tested by: Sun Microsystems, Santa Clara Test date: Mar-2006 Hardware Avail: May-2006 Software Avail: Jan-2006

## Notes/Tuning Information (Continued)

```

-Atile:skewp,-Ainline:cs=700 -xarch=amd64 -Qoption ube_ipa -inl_alt
-xpagesize_stack=2m
172.mgrid: -fast -xautopar -stackvar -xpad=common:900 -xipo=2 -xarch=amd64 -xprefetch_level=3
-xvector -xpagesize=2m -Qoption ld -M,/usr/lib/ld/map.bssalign
173.applu: -fast -xautopar -unroll=5 -stackvar -x04 -xipo=2 -xprefetch_level=3 -xarch=amd64a
-qoption iropt -Rloop_dist -xpagesize_heap=2m
177.mesa: -fast -xautopar -x04 -xipo=2 -Wd,-iropt-prof -xarch=amd64 -xalias_level=strong -xpagesize=2m +FDO
178.galgel: -fast -xcache=64/32/4:1024/64/4 -xcrossfile -xpagesize_heap=2m -xprefetch_level=3 -xvector=simd -xarch=amd64
RM_SOURCES=lapak.f90
EXTRALIBS=-xlic_lib=sunperf
179.art: -fast -xipo=2 -xprefetch -xalias_level=strong -xpagesize=2m
183.quake: -fast -xipo=2 -xprefetch -xalias_level=strong -xpagesize=2m -lmopt -lm +FDO
187.facerec: -fast -x04 -xipo=2 -xprefetch_level=3 -xpagesize=2m
RM_SOURCES=cfftb.f90 cffti.f90 cfftf.f90
EXTRALIBS=-xlic_lib=sunperf
188.amp: -fast -xcache=64/32/4:1024/64/4 -x04 -xipo=2 -xarch=amd64a -xalias_level=std -xpagesize_heap=2m -lmopt -lm
189.lucas: -fast -Qoption ube_ipa -inl_alt -xipo=2 -xarch=amd64 -xprefetch_level=3
191.fma3d: -fast -xcache=64/32/4:1024/64/4 -unroll=5 -fsimple=1 -xipo=2
-xprefetch_level=3 -xarch=amd64 -xpagesize_heap=2m +FDO
200.sixtrack: -fast -xipo=2 -O -xprefetch_level=3 -xarch=amd64
-xpagesize_heap=2m -Qoption ld -M,/usr/lib/ld/map.bssalign +FDO
301.apsi: -fast -x04 -xipo=2 -xprefetch_level=3 -xarch=amd64a -xpagesize=2m

```

Portability:  
178.galgel: -fixed

Shell Environments:  
Stack size set to unlimited via "ulimit -s unlimited"

Kernel Parameters (/etc/system):  
autoup=900  
tune\_t\_fsflushr=1

Processes were bound to CPUs using submit=pbind  
Default BIOS setting was used