



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation

IBM System X 3550 (3.0 GHz Xeon 5160, 4MB L2 Cache)

SPECint_rate2000 = --

SPECint_rate_base2000 = 123

SPEC license #: 11 | Tested by: IBM Corporation | Test date: May-2006 | Hardware Avail: Jul-2006 | Software Avail: May-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	4	77.3	84.1			
175.vpr	4	75.3	86.3			
176.gcc	4	40.1	127			
181.mcf	4	80.8	103			
186.crafty	4	35.9	129			
197.parser	4	88.1	94.8			
252.eon	4	33.3	181			
253.perlbnk	4	51.3	163			
254.gap	4	43.8	117			
255.vortex	4	44.5	198			
256.bzip2	4	77.3	90.0			
300.twolf	4	87.2	160			

Hardware

CPU: Intel Xeon processor 5160 (3.0 GHz, 1333 MHz bus)
CPU MHz: 3000
FPU: Integrated
CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
CPU(s) orderable: 1, 2
Parallel: No
Primary Cache: 32KB(I) + 32KB(D) on chip (per core)
Secondary Cache: 4096KB(I+D) on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 8 x 1024 MB ECC PC2-5300
Disk Subsystem: 73GB SAS 15K RPM
Other Hardware:

Software

Operating System: Windows Server 2003 Enterprise Edition (32-bit)
Compiler: Intel C++ and Fortran Compiler 9.1 for 32-bit applications
Build 20060323Z Package ID: W_FC_P_9.1.020
Microsoft Visual Studio 2005 (for libraries)
SmartHeap Library Version 8.0 from <http://www.microquill.com/>
File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs: -fast +FDO shlw32M.lib
Base tuning for C++ programs: -fast -Qcxx_features +FDO
Portability flags:
176.gcc: -Dalloca=_alloca /F10000000
186.crafy: -DNT_i386
252.eon: -DHAS_ERRLIST
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
```