



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

## Dell

Precision Workstation 690 (Intel Xeon processor 5160, 3.00 GHz)

SPECint\_rate2000 = 62.0

SPECint\_rate\_base2000 = 62.0

SPEC license #: 55 | Tested by: Dell, Inc., Round Rock, TX | Test date: Jun-2006 | Hardware Avail: Jun-2006 | Software Avail: May-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	2	76.8	42.3	2	76.8	42.3
175.vpr	2	73.5	44.2	2	72.7	44.7
176.gcc	2	39.0	65.5	2	39.0	65.5
181.mcf	2	77.0	54.3	2	77.0	54.3
186.crafty	2	36.6	63.4	2	36.6	63.3
197.parser	2	83.2	50.2	2	82.8	50.4
252.eon	2	33.2	90.8	2	33.2	90.9
253.perlbnk	2	51.1	81.7	2	51.1	81.7
254.gap	2	43.2	59.1	2	42.7	59.8
255.vortex	2	44.7	98.6	2	44.7	98.6
256.bzip2	2	78.8	44.2	2	80.8	43.0
300.twolf	2	87.4	79.6	2	87.4	79.6

### Hardware

CPU: Intel Xeon processor 5160 (1333 MHz system bus)  
CPU MHz: 3000  
FPU: Integrated  
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip  
CPU(s) orderable: 1,2  
Parallel: No  
Primary Cache: 32KB(I) + 32KB(D) on chip, per core  
Secondary Cache: 4096KB(I+D) on chip  
L3 Cache: N/A  
Other Cache: N/A  
Memory: 8 x 1024MB 667MHz ECC CL5 FB-DIMM DDR2 SDRAM  
Disk Subsystem: 1 x 73GB SAS 10K RPM  
Other Hardware:

### Software

Operating System: Windows XP Professional x64 Edition  
Compiler: Intel C++ Compiler 9.1 for IA32(20060519Z)  
Microsoft Visual Studio .NET 2003(7.1.3088)  
MicroQuill SmartHeap Library 8.0  
File System: NTFS  
System State: Default

## Notes/Tuning Information

### GENERAL

ONESTEP=yes  
+FDO: PASS1=-Qprof\_gen PASS2=-Qprof\_use

### PORTABILITY FLAGS

176.gcc: -Dalloca=\_alloca /F10000000  
186.crafty: -DNT\_i386  
253.perlbnk: -DSPEC\_CPU2000\_NTOS -DPERLDLL /MT  
254.gap: -DSYS\_HAS\_CALLOC\_PROTO -DSYS\_HAS\_MALLOC\_PROTO

### BASE TUNING

C: -fast +FDO shlw32M.lib  
C++: -fast -Qcxx\_features +FDO

### PEAK TUNING

164.gzip: -fast +FDO  
175.vpr: -fast +FDO  
176.gcc: basepeak=yes  
181.mcf: basepeak=yes  
186.crafty: -fast -Oa +FDO shlw32M.lib  
197.parser: -fast +FDO  
252.eon: -fast +FDO  
253.perlbnk: basepeak=yes



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Dell

Precision Workstation 690 (Intel Xeon processor 5160, 3.00 GHz)

SPECint\_rate2000 = 62.0

SPECint\_rate\_base2000 = 62.0

SPEC license #: 55 | Tested by: Dell, Inc., Round Rock, TX | Test date: Jun-2006 | Hardware Avail: Jun-2006 | Software Avail: May-2006

## Notes/Tuning Information (Continued)

254.gap: -fast +FDO  
255.vortex basepeak=yes  
256.bzip2: -fast -Qunroll11 -Oa +FDO  
300.twolf: basepeak=yes