



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY TX600 S3, Intel Xeon processor 7041, 3.0 GHz

SPECint_rate2000 = 114

SPECint_rate_base2000 = 114

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Jun-2006 | Hardware Avail: May-2006 | Software Avail: May-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.zip	8	146	89.2	8	146	89.2
175.vpr	8	167	77.7	8	167	77.7
176.gcc	8	72.4	141	8	72.4	141
181.mcf	8	239	69.9	8	239	69.9
186.crafty	8	88.6	105	8	88.6	105
197.parser	8	156	107	8	156	107
252.eon	8	63.7	190	8	63.7	190
253.perlbnk	8	105	159	8	105	159
254.gap	8	109	93.3	8	109	93.3
255.vortex	8	93.5	189	8	93.5	189
256.bzip2	8	173	80.6	8	173	80.6
300.twolf	8	192	145	8	192	145

Hardware

CPU: Intel Xeon processor 7041 (3.0 GHz, 2x2MB L2, 800 MHz system bus)
 CPU MHz: 3000
 FPU: Integrated
 CPU(s) enabled: 8 cores, 4 chips, 2 cores/chip (Hyper-Threading Technology disabled)
 CPU(s) orderable: 1,2,4
 Parallel: No
 Primary Cache: 12k micro-ops I + 16KBD on chip, per core
 Secondary Cache: 2048KB(I+D) on chip, per core
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 16x1GB DDRII-RAM PC2-3200R (CAS 3-3-3)
 Disk Subsystem: Fujitsu MAS3367NC (SCSI, 15krpm, 36GB)
 Other Hardware: none

Software

Operating System: Windows Server 2003 Enterprise Edition + SP1 (32-bit)
 Compiler: Intel C++ Compiler 9.1
 Build 20060323Z (for 32-bit applications),
 Microsoft Visual Studio .Net 2003
 7.1.3088 (for libraries),
 SmartHeap Library Version 8.0
 from <http://www.microquill.com>
 File System: NTFS
 System State: Default

Notes/Tuning Information

GENERAL

+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

Portability flags

176.gcc: -Dalloca=_alloca /F10000000
 186.crafty: -DNT_i386
 253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
 254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

Base tuning flags

for C programs: -fast +FDO shlw32m.lib
 for C++ programs: -fast -Qcxx_features +FDO shlw32m.lib

Peak tuning flags

same as baseline (basepeak=true set globally)

The system bus runs at 800 MHz

This result was measured with 32-bit binaries using the 32-bit version of the operating system.



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY TX600 S3, Intel Xeon processor 7041, 3.0 GHz

SPECint_rate2000 = 114

SPECint_rate_base2000 = 114

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Jun-2006 | Hardware Avail: May-2006 | Software Avail: May-2006

Notes/Tuning Information (Continued)

BIOS Configuration:

Hardware Prefetch = Enable, Adjacent Sector Prefetch = Disable

For information about Fujitsu Siemens Computers in your country please see:
<http://www.fujitsu-siemens.com/countries>