



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers
PRIMERGY BX630, AMD Opteron (TM) 285

SPECint_rate2000 = 42.1
SPECint_rate_base2000 = 38.5

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Jul-2006 | Hardware Avail: Mar-2006 | Software Avail: Jul-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	2	98.0	33.1	2	101	32.3
175.vpr	2	105	30.9	2	103	31.4
176.gcc	2	57.4	44.5	2	57.7	44.2
181.mcf	2	208	20.1	2	156	26.8
186.crafty	2	58.8	39.4	2	52.5	44.2
197.parser	2	113	37.0	2	114	36.7
252.eon	2	51.3	58.8	2	40.7	74.1
253.perlbnk	2	92.3	45.2	2	86.0	48.5
254.gap	2	61.3	41.7	2	61.7	41.4
255.vortex	2	73.9	59.7	2	63.1	69.8
256.bzip2	2	118	29.4	2	110	31.6
300.twolf	2	173	40.3	2	144	48.4

Hardware

CPU: AMD Opteron (TM) 285 processor (2.60 GHz)
 CPU MHz: 2600
 FPU: Integrated
 CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
 CPU(s) orderable: 1,2
 Parallel: No
 Primary Cache: 64KBI + 64KBD on chip, per core
 Secondary Cache: 1024KB (I+D) on chip, per core
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 8x1GB DDR-RAM PC3200R (CAS 3-3-3)
 Disk Subsystem: Maxtor DiamondPLUS 9 (SATA)
 Other Hardware: None

Software

Operating System: Windows Server 2003 Enterprise Edition + SP1
 Compiler: Intel C++ 9.1
 Build 20060519Z (for 32-bit applications),
 Microsoft Visual Studio .Net 2003
 7.1.3088 (for libraries),
 SmartHeap Library Version 8.0
 from <http://www.microquill.com>
 File System: NTFS
 System State: Default

Notes/Tuning Information

GENERAL

+FDO: PASS1= -Qprof_gen PASS2= -Qprof_use

Portability flags

176.gcc: -Dalloca=_alloca /F10000000
 186.crafty: -DNT_i386
 253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
 254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

Base tuning flags

for C programs: -fast -arch:SSE2 -Oi- +FDO
 for C++ programs: -O3 -Qipo -Qcxx-features +FDO

Peak tuning flags

164.gzip: -O3 -Qipo -QxW +FDO
 175.vpr: -O3 -Qipo -QxW -Qoption,c,-ip_ninl_max_stats=2000,
 -ip_ninl_max_total_stats=4500 +FDO
 176.gcc: -O3 -Qipo -QxW -Oi- -Qunroll3 +FDO shlw32M.lib
 181.mcf: -O3 -Qipo -QaxN +FDO shlw32M.lib
 186.crafty: -O3 -Qipo -QxW +FDO shlw32M.lib



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers
PRIMERGY BX630, AMD Opteron (TM) 285

SPECint_rate2000 = 42.1
SPECint_rate_base2000 = 38.5

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Jul-2006 | Hardware Avail: Mar-2006 | Software Avail: Jul-2006

Notes/Tuning Information (Continued)

```
197.parser: -Oi -Qipo -QxW +FDO shlw32M.lib
252.eon:     -O3 -Qipo -QxW -Qansi_alias -Qoption,c,-ip_ninl_max_stats=2000,
            -ip_ninl_max_total_stats=4500 +FDO shlw32M.lib
253.perlbnk: -O3 -Qipo -QxW +FDO shlw32M.lib
254.gap:     -O3 -Qipo -QxW +FDO shlw32M.lib
255.vortex:  -O3 -Qipo -arch:SSE -Oi- -Qoption,c,-ip_ninl_max_stats=2000,
            -ip_ninl_max_total_stats=4500 +FDO shlw32M.lib
256.bzip2:   -O3 -Qipo -Qunroll2 shlw32M.lib
300.twolf:   -O3 -Qipo -QxW -Qunroll3 -Qansi_alias +FDO shlw32M.lib
```

'start /b /wait /affinity' command is used to bind CPU(s) to processes

Boot options: /execute /nopae /USEPMTIMER

BIOS settings: Memory timing=1T
DRAM Bank Interleave=AUTO

This result was measured with 32-bit binaries using the 32-bit version of the operating system.

For information about Fujitsu Siemens Computers in your country please see:
<http://www.fujitsu-siemens.com/countries>