



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

## Fujitsu Siemens Computers

PRIMERGY RX300 S3, Intel Xeon 5150 processor, 2.66 GHz

SPECint\_rate2000 = 56.6

SPECint\_rate\_base2000 = 56.6

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Jul-2006 | Hardware Avail: Jul-2006 | Software Avail: May-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	2	86.3	37.6	2	86.3	37.6
175.vpr	2	80.0	40.6	2	80.0	40.6
176.gcc	2	42.9	59.5	2	42.9	59.5
181.mcf	2	78.4	53.3	2	78.4	53.3
186.crafy	2	41.2	56.3	2	41.2	56.3
197.parser	2	90.7	46.1	2	90.7	46.1
252.eon	2	37.8	79.7	2	37.8	79.7
253.perlbnk	2	58.0	72.0	2	58.0	72.0
254.gap	2	45.3	56.4	2	45.3	56.4
255.vortex	2	48.0	91.8	2	48.0	91.8
256.bzip2	2	85.4	40.8	2	85.4	40.8
300.twolf	2	98.8	70.4	2	98.8	70.4

### Hardware

CPU: Intel Xeon 5150 processor (2.66 GHz, 4MB SLC, 1333 MHz system bus)  
CPU MHz: 2666  
FPU: Integrated  
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip  
CPU(s) orderable: 1,2  
Parallel: No  
Primary Cache: 32KB(I) + 32KB(D) on chip, per core  
Secondary Cache: 4096KB(I+D) on chip, per chip  
L3 Cache: N/A  
Other Cache: N/A  
Memory: 8x1GB DDRII-RAM PC2-5300F (CAS 5-5-5)  
Disk Subsystem: Seagate ST373454SS (SAS, 15.4krpm, 73GB)  
Other Hardware: none

### Software

Operating System: Windows Server 2003 Enterprise Edition + SP1 (32-bit)  
Compiler: Intel C++ Compiler 9.1  
Build 20060323Z (for 32-bit applications),  
Microsoft Visual Studio .Net 2003  
7.1.3088 (for libraries),  
SmartHeap Library Version 8.0  
from <http://www.microquill.com>  
File System: NTFS  
System State: Default

## Notes/Tuning Information

### GENERAL

+FDO: PASS1=-Qprof\_gen PASS2=-Qprof\_use

### Portability flags

176.gcc: -Dalloca=\_alloca /F10000000  
186.crafy: -DNT\_i386  
253.perlbnk: -DSPEC\_CPU2000\_NTOS -DPERLDLL /MT  
254.gap: -DSYS\_HAS\_CALLOC\_PROTO -DSYS\_HAS\_MALLOC\_PROTO

### Base tuning flags

for C programs: -fast +FDO shlw32m.lib  
for C++ programs: -fast -Qcxx\_features +FDO shlw32m.lib

### Peak tuning flags

same as baseline (basepeak=true set globally)

The system bus runs at 1333 MHz

This result was measured with 32-bit binaries using the 32-bit version of the operating system.



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

**Fujitsu Siemens Computers**

PRIMERGY RX300 S3, Intel Xeon 5150 processor, 2.66 GHz

SPECint\_rate2000 = 56.6

SPECint\_rate\_base2000 = 56.6

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Jul-2006 | Hardware Avail: Jul-2006 | Software Avail: May-2006

## Notes/Tuning Information (Continued)

BIOS configuration:

Adjacent Sector Prefetch = disable

This result was measured on the PRIMERGY TX300 S3. The PRIMERGY TX300 S3 and the PRIMERGY RX300 S3 are electronically equivalent.

For information about Fujitsu Siemens Computers in your country please see:  
<http://www.fujitsu-siemens.com/countries>