



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Advanced Micro Devices
Tyan Thunder K9HM (S3992), AMD Opteron (TM) 2218

SPECint2000 = 1807
SPECint_base2000 = 1598

SPEC license #: 49 Tested by: AMD Austin, TX Test date: Jul-2006 Hardware Avail: Sep-2006 Software Avail: Sep-2005

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
164.gzip	1400	111	1258	97.6	1434	
175.vpr	1400	122	1147	97.4	1438	
176.gcc	1100	82.6	1331	57.2	1922	
181.mcf	1800	153	1173	123	1467	
186.crafty	1000	57.2	1750	54.5	1834	
197.parser	1800	111	1622	111	1617	
252.eon	1300	54.4	2389	48.6	2674	
253.perlbnk	1800	94.0	1914	91.9	1958	
254.gap	1100	62.5	1759	62.5	1759	
255.vortex	1900	78.3	2428	73.2	2596	
256.bzip2	1500	108	1394	105	1427	
300.twolf	3000	188	1596	146	2062	

Hardware

CPU: AMD Opteron (TM) 2218
CPU MHz: 2600
FPU: Integrated
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
CPU(s) orderable: 1,2
Parallel: no
Primary Cache: 64KBI + 64KBD on chip per core
Secondary Cache: 1024KB (I+D) on chip per core
L3 Cache: N/A
Other Cache: N/A
Memory: 4x512MB, DDR2-667 CL4 ECC Reg
Disk Subsystem: IDE, 120 GB
Other Hardware: None

Software

Operating System: Windows Server 2003 Enterprise Edition SP1 (32-bit)
Compiler: Intel C++ 9.0 build 20050912Z for IA32
Microsoft Visual Studio .NET 7.0.9466 (libraries)
MicroQuill SmartHeap Library 7.0
File System: NTFS
System State: default

Notes/Tuning Information

shlw32M.lib is the SmartHeap library V7.0 from MicroQuill (www.microquill.com)

+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

Portability:

176.gcc: -Dalloca=_alloca /F10000000

186.crafty: -DNT_i386

253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT

254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

Baseline C: -O3 -Qipo -Op +FDO

Baseline C++: -O3 -Qipo -Qcxx-features +FDO

Peak Tuning:

164.gzip: -O3 -Qipo -QxW +FDO

175.vpr: -O3 -Qipo -QxW +FDO

-Qoption,c,-ip_ninl_max_stats=2000,-ip_ninl_max_total_stats=4500

176.gcc: -O3 -Qipo -QxW -Oi- -Qunroll3 +FDO

181.mcf: -O3 -Qipo -QaxN +FDO

186.crafty: -O3 -Qipo -QxW +FDO

197.parser: -QxW +FDO -Oi- -Qipo

252.eon: -O3 -Qipo -QxW +FDO -Qansi_alias

-Qoption,c,-ip_ninl_max_stats=2000,-ip_ninl_max_total_stats=4500

253.perlbnk: -O3 -Qipo -QxW +FDO

Standard Performance Evaluation Corporation

info@spec.org

<http://www.spec.org>



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Advanced Micro Devices

Tyan Thunder K9HM (S3992), AMD Opteron (TM) 2218

SPECint2000 = 1807

SPECint_base2000 = 1598

SPEC license #: 49 | Tested by: AMD Austin, TX | Test date: Jul-2006 | Hardware Avail: Sep-2006 | Software Avail: Sep-2005

Notes/Tuning Information (Continued)

```
254.gap:          basepeak = yes
255.vortex:       -O3 -Qipo -arch:SSE +FDO -Oi- shlw32M.lib
                  -Qoption,c,-ip_ninl_max_stats=2000,-ip_ninl_max_total_stats=4500
256.bzip2:        -O3 -Qipo          -Qunroll2
300.twolf:        -O3 -Qipo -QxW +FDO    -Qunroll3 shlw32M.lib -Qansi_alias
system can be built using a standard ATX case and a Zippy 700W PSL-6701P power supply
Half memory slots populated on CPU in dual channel configuration
```