



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

**Advanced Micro Devices**  
Tyan Thunder K9HM (S3992), AMD Opteron (TM) 2218

SPECfp\_rate2000 = 47.2  
SPECfp\_rate\_base2000 = 43.0

SPEC license #: 49 | Tested by: AMD Austin, TX | Test date: Jul-2006 | Hardware Avail: Sep-2006 | Software Avail: Jan-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	60.4	61.5	2	53.0	70.0
171.swim	2	163	44.1	2	160	45.0
172.mgrid	2	115	36.4	2	107	39.0
173.applu	2	106	45.9	2	92.3	52.8
177.mesa	2	71.4	45.5	2	61.5	52.8
178.galgel	2	94.0	71.6	2	85.8	78.4
179.art	2	106	57.0	2	73.8	81.8
183.quake	2	86.3	35.0	2	78.0	38.7
187.facerec	2	74.4	59.3	2	74.4	59.3
188.amp	2	144	35.4	2	134	38.0
189.lucas	2	110	42.3	2	104	44.7
191.fma3d	2	132	37.0	2	130	37.4
200.sixtrack	2	128	19.9	2	123	20.8
301.apsi	2	157	38.5	2	149	40.4

### Hardware

CPU: AMD Opteron (TM) 2218  
 CPU MHz: 2600  
 FPU: Integrated  
 CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip  
 CPU(s) orderable: 1,2  
 Parallel: No  
 Primary Cache: 64KBI + 64KBD on chip per core  
 Secondary Cache: 1024KB (I+D) on chip per core  
 L3 Cache: N/A  
 Other Cache: N/A  
 Memory: 4x512MB, DDR2-667 CL4 ECC Reg  
 Disk Subsystem: IDE, 120 GB  
 Other Hardware: None

### Software

Operating System: SuSE Linux Enterprise Server 9 SP3 (64-bit)  
 Compiler: PathScale EKOPath(TM) Compiler Suite, Release 2.3  
 File System: Linux/ext3  
 System State: Multi-user, run level 3

## Notes/Tuning Information

+FDO: PASS1= -fb\_create fbdata PASS2= -fb\_opt fbdata  
 +ACML means -L<acml2.7.0-install-dir>/pathscale64/lib -lacml,  
 which causes linking with AMD Core Math Library V2.7.0

### Baseline optimization

C programs: -Ofast -WOPT:mem\_opnds=on +FDO  
 Fortran programs: -Ofast -LNO:fusion=2 -OPT:fast\_complex=on +FDO  
 Portability Flags:  
 178.galgel: -fixedform

### Peak Tuning:

168.wupwise: -Ofast -LNO:prefetch Ahead=5:prefetch=3  
 -OPT:unroll\_times\_max=8:unroll\_size=128:IEEE\_NaN\_Inf=off:ro=3  
 -IPA:linear=on:plimit=50000:callee\_limit=5000  
 -INLINE:aggressive=on  
 171.swim: -Ofast -CG:local\_fwd\_sched=on -LNO:fusion=2 -m3dnow



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Advanced Micro Devices

Tyan Thunder K9HM (S3992), AMD Opteron (TM) 2218

SPECfp\_rate2000 = 47.2

SPECfp\_rate\_base2000 = 43.0

SPEC license #: 49 | Tested by: AMD Austin, TX | Test date: Jul-2006 | Hardware Avail: Sep-2006 | Software Avail: Jan-2006

## Notes/Tuning Information (Continued)

```

172.mgrid: -Ofast -CG:gcm=off -OPT:IEEE_arith=3:unroll_size=200
           -LNO:fusion=2:fission=1:blocking=off:prefetch_ahead=2
           -WOPT:mem_opnds=on:aggstr=0
173.applu: -Ofast -CG:local_fwd_sched=on -OPT:ro=3 -TENV:X=3
           -LNO:fusion=2:fission=2:full_unroll_size=10000 +FDO
177.mesa: -O2 -ipa -OPT:Ofast -fno-math-errno -CG:local_fwd_sched=on -WOPT:mem_opnds=on +FDO
178.galgel: -Ofast -OPT:fast_complex=on +ACML +FDO
           RM_SOURCES=lapak.f90
179.art: -O3 -OPT:Ofast -fno-math-errno -mno-sse2 -m32
183.quake: -Ofast -CG:load_exe=2 -WOPT:mem_opnds=on -m32 +FDO
187.facerec: -Ofast -LNO:fusion=2
           -OPT:fast_complex=on:IEEE_NaN_Inf=off:unroll_size=0 +FDO
188.ammp: -O3 -OPT:alias=disjoint:unroll_times_max=8:Ofast:ro=3
           -fno-math-errno -TENV:X=4 +FDO
189.lucas: -Ofast -OPT:ro=3:fast_nint=off:unroll_size=256 -WOPT:mem_opnds=on +FDO
191.fma3d: -O2 -ipa -CG:load_exe=1 -OPT:Ofast:IEEE_arith=3:ro=3
           -WOPT:mem_opnds=on:retype_expr=on -IPA:pu_reorder=1 +FDO
200.sixtrack: -O3 -OPT:Ofast:Olimit=6000:early_intrinsics=on
           -fno-math-errno -CG:load_exe=1 +FDO
301.apsi: -Ofast -CG:load_exe=0 -LNO:prefetch=0:simd=2

```

system can be built using a standard ATX case and a Zippy 700W PSL-6701P power supply  
 Half memory slots populated on CPU in dual channel configuration  
 taskset utility used to bind CPU(s) to processes.