



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Advanced Micro Devices
ASUS M2N-LR/SATA, AMD Opteron (TM) 1220SE

SPECint_rate2000 = 43.9
SPECint_rate_base2000 = 39.0

SPEC license #: 49 | Tested by: AMD Austin, TX | Test date: Jul-2006 | Hardware Avail: Sep-2006 | Software Avail: Jan-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	2	82.1	39.6	2	81.8	39.7
175.vpr	2	109	29.9	2	103	31.4
176.gcc	2	57.3	44.5	2	57.4	44.5
181.mcf	2	285	14.7	2	173	24.1
186.crafty	2	40.1	57.9	2	39.0	59.6
197.parser	2	142	29.3	2	111	37.5
252.eon	2	44.6	67.6	2	38.7	78.0
253.perlbnk	2	95.8	43.6	2	86.3	48.4
254.gap	2	61.7	41.4	2	61.7	41.4
255.vortex	2	68.7	64.1	2	64.1	68.7
256.bzip2	2	98.2	35.4	2	98.2	35.4
300.twolf	2	202	34.5	2	154	45.3

Hardware

CPU: AMD Opteron (TM) 1220SE
 CPU MHz: 2800
 FPU: Integrated
 CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
 CPU(s) orderable: 1
 Parallel: No
 Primary Cache: 64KBI + 64KBD on chip per core
 Secondary Cache: 1024KB (I+D) on chip per core
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 2x1024MB, DDR2-800 CL3
 Disk Subsystem: IDE, 120GB
 Other Hardware: None

Software

Operating System: SuSE Linux Enterprise Server 9 SP3 (64-bit)
 Compiler: PathScale EKOPath(TM) Compiler Suite, Release 2.3
 File System: Linux/ext3
 System State: Multi-user, run level 3

Notes/Tuning Information

+FDO: PASS1= -fb_create fbdata PASS2= -fb_opt fbdata

Baseline optimization flags:

C programs: -Ofast +FDO
 C++ programs: -Ofast +FDO

Portability Flags:

186.crafty: -DLINUX_i386
 252.eon: -DHAS_ERRLIST -DSPEC_CPU2000_LP64
 253.perlbnk: -DSPEC_CPU2000_LINUX_I386 -DSPEC_CPU2000_NEED_BOOL
 -DSPEC_CPU2000_LP64
 254.gap: -DSYS_IS_USG -DSYS_HAS_IOCTL_PROTO -DSYS_HAS_TIME_PROTO
 -DSYS_HAS_CALLOC_PROTO -DSPEC_CPU2000_LP64
 255.vortex: -DSPEC_CPU2000_LP64

Peak Tuning:

164.gzip: -O3 -ipa -WOPT:val=0 -OPT:unroll_size=0 +FDO
 175.vpr: -O3 -ipa -m32 +FDO
 176.gcc: -O3 -IPA:plimit=10000 -LNO:opt=0 -OPT:goto=off +FDO



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Advanced Micro Devices
ASUS M2N-LR/SATA, AMD Opteron (TM) 1220SE

SPECint_rate2000 = 43.9
SPECint_rate_base2000 = 39.0

SPEC license #: 49 | Tested by: AMD Austin, TX | Test date: Jul-2006 | Hardware Avail: Sep-2006 | Software Avail: Jan-2006

Notes/Tuning Information (Continued)

```

181.mcf:      -O3 -ipa -IPA:field_reorder=on -m32 +FDO
186.crafty:   -Ofast -CG:local_fwd_sched=on -LNO:opt=0 -WOPT:val=0 +FDO
197.parser:   -O3 -ipa -m32 -IPA:ctype=on +FDO
252.eon:      -Ofast -CG:gcm=off:p2align_freq=1:prefetch=off -IPA:plimit=4000
              -OPT:treeheight=on -TENV:X=4:frame_pointer=off -fno-exceptions
              -LNO:fu=10:full_unroll_outer=on -GRA:optimize_boundary=on +FDO
253.perlbmk:  -O2 -ipa -OPT:Ofast:transform_to_memlib=off
              -fno-math-errno -IPA:plimit=10000 +FDO
255.vortex:   -Ofast -OPT:goto=off -CG:p2align=on
              -GRA:optimize_boundary=on -IPA:min_hotness=120 +FDO
256.bzip2:    basepeak = true
300.twolf:    -O2 -CG:gcm=off:p2align_freq=100000
              -OPT:Ofast:unroll_times_max=8:unroll_size=256:alias=disjoint
              -WOPT:mem_opnds=on -m32 +FDO

```

The tested system can be assembled using a standard ATX case and an Antec True 550 watt EPS12V Power Supply.
Half memory slots populated in dual channel configuration.
taskset utility used to bind CPU(s) to processes.