



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

ASUS Computer International
Asus M2N32-SLI Deluxe, AMD Athlon (TM) 64 FX-62

SPECfp2000 = **2133**
SPECfp_base2000 = **1944**

SPEC license #: 13 Tested by: Intel Corporation Test date: Jul-2006 Hardware Avail: Jun-2006 Software Avail: Jun-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	52.4	3051	52.8	3032	
171.swim	3100	112	2758	110	2829	
172.mgrid	1800	100	1794	100	1794	
173.applu	2100	123	1701	110	1915	
177.mesa	1400	140	998	70.1	1998	
178.galgel	2900	89.5	3239	82.4	3518	
179.art	2600	51.3	5064	51.3	5064	
183.quake	1300	68.2	1906	66.9	1943	
187.facerec	1900	85.3	2229	85.3	2229	
188.amp	2200	171	1284	144	1527	
189.lucas	2000	97.5	2052	82.0	2439	
191.fma3d	2100	117	1790	115	1825	
200.sixtrack	1100	129	855	128	857	
301.apsi	2600	170	1531	170	1527	

Hardware

CPU: AMD Athlon (TM) 64 FX-62
 CPU MHz: 2800
 FPU: Integrated
 CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
 CPU(s) orderable: 1
 Parallel: no
 Primary Cache: 64KBI + 64KBD on chip, per core
 Secondary Cache: 1MB (I+D) on chip, per core
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 2x1 GB, Corsair CM2X1024-8500C5 DDR2-1066 5-5-15
 Disk Subsystem: SATA, Western Digital WD740GD, 10000 rpm
 Other Hardware: None

Software

Operating System: Microsoft Windows XP SP2
 Compiler: Intel C++ 9.1 build 20060519Z for IA32, Intel Fortran 9.1 build 20060519Z for IA32, PGI Fortran compiler 6.0-5 for Windows XP, PGI C compiler 6.0-5 for Windows XP, ACML Version 2.5.3 (bundled with PGI 6.0-5)
 File System: NTFS
 System State: default

Notes/Tuning Information

```
+FDO:
  icl, ifort : PASS1=-Qprof_gen PASS2=-Qprof_use
  pgf90      : PASS1=-Mpfi      PASS2=-Mpfo
ifort is the Intel Fortran compiler, icl is the Intel C++ compiler and
pgf90 is the PGI Fortran 90 compiler.
pgcc is the PGI C compiler.
ONESTEP is set to 1 for every compile with the PGI compilers.
Portability:
178.galgel: -Mfixed
Baseline: C : pgcc -fastsse -Mipa=fast,inline
Baseline: Fortran: pgf90 -fastsse -Mipa=fast,inline +FDO
Peak tuning:
168.wupwise: pgf90 -fastsse -Mipa=fast,inline -Mvect
171.swim: ifort -Qipo -O3 -QaxN -QxW -Qunroll0 +FDO
172.mgrid: pgf90 -fastsse -Mipa=fast,inline
173.applu: ifort -Qipo -O3 -QaxN -QxW -auto +FDO
177.mesa: icl -Qipo -arch:SSE2 -Qunroll1 -Qansi_alias +FDO
```



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

ASUS Computer International
Asus M2N32-SLI Deluxe, AMD Athlon (TM) 64 FX-62

SPECfp2000 = 2133
SPECfp_base2000 = 1944

SPEC license #: 13 | Tested by: Intel Corporation | Test date: Jul-2006 | Hardware Avail: Jun-2006 | Software Avail: Jun-2006

Notes/Tuning Information (Continued)

-Qoption,f,-ip_ninl_max_stats=1500,-ip_ninl_max_total_stats=4500

```

178.galgel:          pgf90  -fastsse -Mipa=fast,safe -Munix -lacml
                    RM_SOURCES=lapak.f90
179.art:             pgcc    basepeak=yes
183.quake:           icl     -fast -arch:SSE2 -QaxW +FDO
187.facerec:         pgf90  -fastsse -Mipa=fast,inline +FDO
188.ampp:            icl     -Oa  -arch:SSE2 -Zp4 -Qansi_alias
189.lucas:           ifort   -Qipo -QxW -Qunroll1
191.fma3d:           pgf90  -Mipa=fast,inline -fastsse -Mnovect +FDO
200.sixtrack:        pgf90  -fastsse -Mipa=fast,inline
301.apsi:            pgf90  -fastsse -Mipa=fast,inline

```

The system under test can be built with an ATI X1900 XTX graphics card and an ATX APE-300x power supply.