



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Intel Corporation

Intel D975XBX motherboard(3.73 GHz, Intel(R) Pentium(R) 4 processor Extreme Edition supporting Hyper-Threading Technology)

SPECfp2000 = 2144

SPECfp_base2000 = 2138

SPEC license #: 13 Tested by: Intel Corporation Test date: Jul-2006 Hardware Avail: Mar-2006 Software Avail: May-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	39.8	4017	39.8	4017	
171.swim	3100	112	2779	112	2776	
172.mgrid	1800	111	1628	111	1628	
173.applu	2100	110	1913	110	1913	
177.mesa	1400	88.0	1591	88.0	1591	
178.galgel	2900	75.4	3845	75.4	3844	
179.art	2600	50.4	5158	50.4	5158	
183.quake	1300	41.7	3117	40.3	3224	
187.facerec	1900	87.8	2164	87.8	2163	
188.amp	2200	167	1317	166	1327	
189.lucas	2000	84.8	2358	84.3	2372	
191.fma3d	2100	121	1738	121	1738	
200.sixtrack	1100	152	724	153	719	
301.apsi	2600	180	1445	180	1445	

Hardware

CPU: Intel(R) Pentium(R) 4 processor Extreme Edition supporting Hyper-Threading Technology (3.73 GHz, 1066 MHz bus)
CPU MHz: 3733
FPU: Integrated
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip (Hyper-Threading Technology enabled)
CPU(s) orderable: 1
Parallel: No
Primary Cache: 12k micro-ops I + 16KBD on chip per core
Secondary Cache: 2MB(I+D) on chip per core
L3 Cache: N/A
Other Cache: N/A
Memory: 2 GB (2 1GB Micron DDR2 667 CL5-5-5 DIMMs)
Disk Subsystem: Maxtor DiamondMax 10 6B300S0 300GB NCQ Serial ATA (7200 RPM, 16MB cache)
Other Hardware: ATI Radeon X850 XT PCI express graphics card

Software

Operating System: Windows XP Professional SP2
Compiler: Intel C++ and Fortran Compiler 9.1 for 32-bit applications
Build 20060323Z Package ID: W_FC_P_9.1.020
Microsoft Visual Studio 2005(for libraries)
SmartHeap Library Version 8.0 from <http://www.microquill.com/>
File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO: PASS1= -Qprof_gen PASS2=-Qprof_use
Base tuning for Fortran programs: -fast -Qansi_alias +FDO
Base tuning for C programs: -fast +FDO shlW32M-80.lib
Portability:
178.galgel: -FI /F32000000
Peak tuning:
168.wupwise: -fast -Qansi_alias +FDO
171.swim: -fast -Qansi_alias +FDO
172.mgrid: -fast -Qansi_alias +FDO
173.applu: basepeak=yes
177.mesa: basepeak=yes
178.galgel: -fast -Qansi_alias +FDO
179.art: basepeak=yes
183.quake: -QxP -Oa -Qrcd -Qipo +FDO shlW32M-80.lib
187.facerec: -fast -Qunroll1 -Qscalar_rep- +FDO
188.amp: -fast -Oa +FDO shlW32M-80.lib
189.lucas: -fast -Qprefetch- +FDO
```



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Intel Corporation

Intel D975XBX motherboard(3.73 GHz, Intel(R) Pentium(R) 4 processor Extreme Edition supporting Hyper-Threading Technology)

SPECfp2000 = 2144

SPECfp_base2000 = 2138

SPEC license #: 13 | Tested by: Intel Corporation | Test date: Jul-2006 | Hardware Avail: Mar-2006 | Software Avail: May-2006

Notes/Tuning Information (Continued)

191.fma3d: basepeak=yes

200.sixtrack: -Qipo -QxP +FDO

301.apsi: -fast +FDO

Tested systems can be used with Shin-G ATX case, Delta Inc. power supply PS-300GB-1 B

Product description located as of 07/2006

<http://www.intel.com/products/motherboard/d975xbx/index.htm>

The system bus runs at 1066 MHz