



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

## Intel Corporation

Intel D975XBX motherboard( 3.73 GHz, Intel(R) Pentium(R) 4 processor Extreme Edition supporting Hyper-Threading Technology)

SPECint\_rate2000 = 23.5

SPECint\_rate\_base2000 = 23.4

SPEC license #: 13 | Tested by: Intel Corporation | Test date: Jul-2006 | Hardware Avail: Mar-2006 | Software Avail: May-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	2	174	18.7	2	174	18.7
175.vpr	2	214	15.2	2	209	15.5
176.gcc	2	85.9	29.7	2	85.9	29.7
181.mcf	2	171	24.4	2	171	24.4
186.crafty	2	140	16.6	2	140	16.6
197.parser	2	212	19.7	2	209	20.0
252.eon	2	97.2	31.0	2	97.4	31.0
253.perlbnk	2	170	24.6	2	169	24.7
254.gap	2	93.8	27.2	2	93.8	27.2
255.vortex	2	119	37.0	2	119	37.0
256.bzip2	2	170	20.5	2	171	20.4
300.twolf	2	268	26.0	2	268	25.9

### Hardware

CPU: Intel(R) Pentium(R) 4 processor Extreme Edition supporting Hyper-Threading Technology (3.73 GHz, 1066 MHz bus)  
CPU MHz: 3733  
FPU: Integrated  
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip (Hyper-Threading Technology enabled)  
CPU(s) orderable: 1  
Parallel: No  
Primary Cache: 12k micro-ops I + 16KBD on chip per core  
Secondary Cache: 2MB(I+D) on chip per core  
L3 Cache: N/A  
Other Cache: N/A  
Memory: 2 GB (2 1GB Micron DDR2 667 CL5-5-5 DIMMs)  
Disk Subsystem: Maxtor DiamondMax 10 6B300S0 300GB NCQ Serial ATA (7200 RPM, 16MB cache)  
Other Hardware: ATI Radeon X850 XT PCI express graphics card

### Software

Operating System: Windows XP Professional SP2  
Compiler: Intel C++ and Fortran Compiler 9.1 for 32-bit applications  
Build 20060323Z Package ID: W\_FC\_P\_9.1.020  
Microsoft Visual Studio 2005(for libraries)  
SmartHeap Library Version 8.0 from <http://www.microquill.com/>  
File System: NTFS  
System State: Default

## Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs: -fast +FDO shlw32M-80.lib
Base tuning for C++ programs: -fast -Qcxx_features +FDO shlw32M-80.lib
Portability flags:
176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
252.eon: -DHAS_ERRLIST
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
164.gzip: -fast -Qansi_alias -Oa +FDO
175.vpr: -fast -Qansi_alias +FDO
176.gcc: basepeak=yes
181.mcf: basepeak=yes
186.crafty: -fast -Qansi_alias -Oa +FDO
197.parser: -fast -Qansi_alias +FDO
252.eon: -fast +FDO
253.perlbnk: -fast -Qansi_alias +FDO shlw32M-80.lib
254.gap: basepeak=yes
255.vortex: basepeak=yes
```



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

**Intel Corporation**

Intel D975XBX motherboard( 3.73 GHz, Intel(R) Pentium(R) 4 processor Extreme Edition supporting Hyper-Threading Technology)

SPECint\_rate2000 = 23.5

SPECint\_rate\_base2000 = 23.4

SPEC license #: 13 | Tested by: Intel Corporation | Test date: Jul-2006 | Hardware Avail: Mar-2006 | Software Avail: May-2006

## Notes/Tuning Information (Continued)

256.bzip2: -fast -Oa -Qunroll11 +FDO

300.twolf: -fast -O3 +FDO shlw32M-80.lib

Tested systems can be used with Shin-G ATX case, Delta Inc. power supply PS-300GB-1 B

Product description located as of 07/2006

<http://www.intel.com/products/motherboard/d975xbx/index.htm>

The system bus runs at 1066 MHz