



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

ION
A20 (Intel Xeon processor 5060, 3.2GHz)

SPECfp_rate2000 = 60.1
SPECfp_rate_base2000 = 60.1

SPEC license #: 2697 | Tested by: ION | Test date: Jul-2006 | Hardware Avail: Jul-2006 | Software Avail: Jun-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	4	79.1	93.9	4	79.1	93.9
171.swim	4	293	49.0	4	293	49.0
172.mgrid	4	184	45.4	4	184	45.4
173.applu	4	205	47.6	4	205	47.6
177.mesa	4	84.7	76.7	4	84.7	76.7
178.galgel	4	106	127	4	106	127
179.art	4	70.4	171	4	70.4	171
183.quake	4	150	40.1	4	150	40.1
187.facerec	4	135	65.5	4	135	65.5
188.amp	4	188	54.2	4	188	54.2
189.lucas	4	199	46.7	4	199	46.7
191.fma3d	4	201	48.6	4	201	48.6
200.sixtrack	4	176	29.0	4	176	29.0
301.apsi	4	235	51.3	4	235	51.3

Hardware

CPU: Intel Xeon Processor 5060 (1066Mhz System Bus)
CPU MHz: 3200
FPU: Integrated
CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip (HyperThreading Technology disabled)
CPU(s) orderable: 1,2 chips
Parallel: No
Primary Cache: 12KB(I) + 16KB(D) on chip, per core
Secondary Cache: 2MB (I+D) on chip, per core
L3 Cache: None
Other Cache: None
Memory: 8 GB (8*1GB PC2-5300 FB-DIMMs)
Disk Subsystem: 1 x 400GB SATA, 7200rpm
Other Hardware: None

Software

Operating System: Red Hat Enterprise Linux ES 4 Update 3 for AMD64/Intel EM64T
Compiler: Intel(R) Fortran Compiler for EM64T, V9.1 (Build 20060519)
Intel(R) C++ Compiler for EM64T, V9.1 (Build 20060519)
File System: ext3
System State: Multi-user

Notes/Tuning Information

Tested by ION Computer Systems
BIOS 2.00 Build 54
HyperThreading Technology Disabled in BIOS
Enhanced SpeedStep Disabled in BIOS
kernel 2.6.9-34.0.1.ELsmp
+FDO: PASS1=-prof_gen PASS2=-prof_use

SPEC CFP2000 Baseline optimization flags
C programs: -fast -ansi_alias +FDO
Fortran programs: -fast +FDO
+FDO: PASS1=-prof_gen PASS2=-prof_use

SPEC CFP2000 Peak optimization flags:
basepeak=yes set globally

Portability Flags:
178.galgel: -FI